



U.S. Department of Transportation
Federal Aviation Administration
Washington, D.C.

FLIGHT STANDARDIZATION BOARD REPORT

Revision: 2

Hawker Beechcraft Corporation

BE-300

(Models 300, 300LW, B300, B300C)

Date: 08/02/2012

Johnathon Vetter, Chairman
Flight Standardization Board

Federal Aviation Administration
Kansas City Aircraft Evaluation Group
MKC-AEG, ACE-211
901 Locust Street #332
Kansas City, MO 64104

Telephone: (816) 329-3233
FAX: (816) 329-3241

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

RECORD OF REVISIONS

Revision	Sections	Date	Chairman
300/1900	Original	01/25/1984	Argil L. Axford
300LW	Original	06/17/1988	Troy D. Sims
B300	Original	02/09/1990	Kenneth W. Davis
BE-300, BE-1900 Original (1900, 300, 300LW, B300, 300FF)	Original Composite Report	11/21/1990	Kenneth W. Davis
BE-300 Rev.1 (300,300LW,B300, B300C)	1 & 3 Separate 1900 from 300 type rating	03-23-1993	Douglas Edwards
B300 R1	1 & 4	03-23-1993	Douglas Edwards
300FF Rev.1	Delete separate type rating	05-17-2002	Fred Beeman
BE-300 Rev. 2 (300,300LW,B300, B300C,300FF)	ALL	08/02/2012	Johnathon Vetter

Highlights of Changes:

Revision Original Changes

Model 300 added as BE-300, BE-1900 Pilot Type Rating January 25, 1984 with AFS Memo dated December 6, 1984.

Model 300LW independent report determines 300LW requires same training and type rating as Model 300.

Model B300 independent report determines B300 is same pilot type rating as 300 with B/B/B differences per AFS Memo dated February 15, 1990.

Model 300 (FF Serials) independent report determines 300(FF Serials) are Separate Pilot Type Rating BE-300F per AFS Memo dated May 24, 1990.

Revision 1 Changes (2 separate Revision 1 reports issued)

Separates BE-300 Pilot Type Rating from BE-1900 Type Rating reference AFS Memo dated November 6, 1991.

BE-300 Report did not include 300(FF Serials) because they were separate pilot type rating at the time.

Separate 300(FF Serials) report revision 1 issued deleting BE-300F pilot type rating as separate and make 300(FF Serials) part of the Same Pilot Type Rating BE-300 with C/D/D differences per AEG Memo dated May 21, 2002.

Revision 2 Changes

Consolidate all previous FSB Reports for Model 300 Type Rating airplanes into single report.

Add G1000 differences

Address Specific Compliance Items for section 8.0, Aircraft Regulatory Compliance Checklist.

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

CONTENTS

PART 1 - Training, Checking and Currency

MANAGEMENT COORDINATION PAGE

RECORD OF REVISIONS

CONTENTS

- 1 PURPOSE AND APPLICABILITY
- 2 PILOT TYPE RATING DETERMINATION
- 3 MASTER DIFFERENCE REQUIREMENTS
- 4 OPERATOR DIFFERENCE REQUIREMENTS TABLES
- 5 FSB SPECIFICATIONS FOR TRAINING
- 6 FSB SPECIFICATIONS FOR CHECKING
- 7 FSB SPECIFICATIONS FOR CURRENCY
- 8 AIRCRAFT REGULATORY COMPLIANCE
- 9 FSB SPECIFICATIONS FOR DEVICES AND SIMULATORS
- 10 APPLICATION OF FSB REPORT
- 11 ALTERNATE MEANS OF COMPLIANCE

APPENDIX 1 – MDR TABLE (ATTACHED)

APPENDIX 2 – ODR TABLES (ATTACHED)

APPENDIX 3 – SAMPLE TRAINING PROGRAM (RESERVED)

APPENDIX 4 – COMPLIANCE CHECKLIST (RESERVED)

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

1. PURPOSE AND APPLICABILITY

1.1 Purpose

This FSB report specifies master training, checking, and currency requirements applicable to flight crewmembers operating Hawker Beechcraft Corporation (HBC) **BE-300** type rated airplanes. This report provides guidance to operators under 14 CFR Part 91 & 135, FAA Principal Inspectors, Part 142 Training Centers, Part 141 Approved Schools and other training providers.

The Model 300, 300LW, B300 & B300C Flight Standardization Board (FSB) Report addresses training, checking, and currency requirements for pilots operating the BE-300 type rated aircraft. The FSB evaluates operating characteristics and techniques to propose training, checking and currency requirements applicable to the BE-300 aircraft. The objectives of this FSB were to:

- Determination of Pilot Type Rating.
- Identify training, checking and currency requirements.
- Establish Master Common Requirements.
- Establish Master Difference Requirements.
- Provide sample Differences Tables.
- Review AFM and Checklist procedures for operational suitability.
- Describe acceptable training program and training device characteristics.
- Provide determination of regulatory compliance status

1.2 Applicability

In accordance with existing 14 CFRs, the provisions of this report apply to all operations of a BE-300 airplane identified as Model 300, 300LW, B300 and B300C on TCDS A24CE. This report is also applicable to all training and checking conducted in the aircraft, as well as the currency and experience provisions.

The guidelines in this report determine minimum requirements for approval by FAA applicable to: Operations Aviation Safety Inspectors, Principal Operations Inspectors (POIs), Training Center Program Managers (TCPMs), Aircrew Program Managers (APMs), 14 CFR Part 135 Air Carrier Check Airmen and Instructors, Airline Transport Pilots instructing in air transportation service, Certificated Flight Instructors, Aircrew Program Designees, and Training Center Evaluators.

Determinations made in this report are based on the evaluations of specific BE-300 type rated aircraft equipped in a given configuration and in accordance with current regulations and guidance. Modifications and upgrades made to the models described herein, or introduction of new related aircraft, may require amendment of the findings in this report. The FSB reserves responsibility/authority to re-evaluate and modify sections of this report based on new or revised Advisory Circular material or CFR, aircraft operating experience, or the testing of new or modified aircraft under the provisions of AC 120-53A and/or the Common Procedures Document for conduction Operational Evaluation Boards, 10 June, 2004.

The provisions of this Flight Standardization Board (FSB) report are effective until amended, superseded, or withdrawn by subsequent revisions to this report

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

2. PILOT TYPE RATING DETERMINATION

2.1 Pilot Type Rating Background

This report assigns the “**BE-300**” pilot type rating to the Hawker Beechcraft Corporation Model 300, 300LW, B300 and B300C from TCDS A24CE. The Board utilized pertinent CFRs and the evaluation process outlined in Advisory Circular AC 120-53 and the Common Procedures Document for Conducting Operational Evaluation Boards (JAA, TCCA, FAA) dated 10 June 2004. For the purpose of design and operating characteristics the BE-300 type rating designation is a SFAR 41(300 & 300LW) and Commuter Category (B300 & B300C), Multiengine, Turbo-Propeller, Land aircraft certificated for both One and/or Two Pilot Flight Crewmembers.

2.1.1 Model 300

The Beechcraft Model 300 aircraft is a complex, high performance, turboprop aircraft powered by 2 P&W PT6A-60, 1050 shp engines. Rudder Boost is required to be installed and operative; if inoperative, 180lb. pressure may be required for single engine operation. Autofeather is required to be armed and operative for takeoff, climb, approach and landing. The aircraft is certified for operations up to 35,000 feet but flight above 11,000 feet is prohibited without Yaw Damper operating. Maximum takeoff / landing weight is 14,000 pounds and maximum seating is 15, including crew.

The Model 300 was type certified under 14 CFR Part 23 and Special Federal Aviation Regulation (SFAR)41C.

The FSB convened January 10-13, 1984 in Wichita, KS to consider pilot training, checking, currency and pilot type rating requirements for the Model 300. The FSB evaluated the Model 300 in all maneuvers required by 14 CFR 61, Appendix A using aircraft serial number FA-1. The Model 300 was evaluated as a proposed Common Pilot Type Rating with the BE-1900. The FSB evaluated the systems of the Model 300 and compared them with the Model 1900 systems. The Board concluded the systems on the two aircraft were basically the same regarding pilot actions. The exceptions were the power steering on the Model 1900 and the propeller pitch lights and rudder boost on the Model 300. Training was used to resolve these areas of difference. Some flight characteristics of the Model 300 associated with the shorter fuselage are not apparent in the Model 1900. However, most control and basic flight characteristics of the two airplanes are similar.

One area of concern identified by the board was Avionics/EFIS. Beech intended to use EFIS in the Model 300 airplane but changed certification to conventional instruments during the certification program. The evaluation airplane, FA-1, had conventional mechanical instruments but Beech intends production airplanes to have EFIS. The Board concluded a different pilot type rating would not be required based solely on Avionics/EFIS differences but that effective training was needed on the operation of Avionics/EFIS equipment.

The FSB concluded a pilot type rating was required by regulation for the Model 300. The FSB recommended the Model 300 be included with the Model 1900 pilot type rating. The FAA established a Pilot Type Rating **BE-300, BE-1900** for the Model 300 and 1900 on the Pilot Certificate Aircraft Type Rating List December 6, 1984.

Hawker Beechcraft Corporation, Model 300 Flight Standardization Board Report

2.1.2 Model 300LW

The Model 300LW FSB was convened May 3, 1988 in Wichita, KS. The FSB was to evaluate the Model 300LW to determine if a pilot type rating specified by 14 CFR 61.31(a)(4) would be required. The difference in the Model 300LW from the Model 300 described in section 2.1.1 of this report is the Model 300LW has a maximum takeoff / landing weight of 12,500 pounds, the airspeed limitations and indicator markings are changed reference the new weight and the LW designation is added to the Data Plate.

A Model 300 was used for the FSB evaluation because no Model 300LW had been completed or in production at the time. The manufacturer stated the Model 300 and Model 300LW were identical airplanes with the Model 300LW operating at a reduced weight. The Aircraft Type Rating Evaluation Matrix was used to evaluate differences. All systems, procedures and limitations remain the same between the two models.

The FSB concluded that a pilot type rating is required under the provisions of 14 CFR 61.31(a)(4) for the Model 300LW. The Model 300LW requires the same proficiency and competency for safe operation as the existing Model 300. The existing Model 300 has a pilot type rating requirement and training/service history that indicates the level of proficiency required by the pilot type rating is essential for safe operation of both the Model 300 and Model 300LW. The Model 300LW FSB concluded the Model 300LW is the same pilot type rating as the Model 300 because the airplanes are identical in design and operation. The Model 300 has a same pilot type rating designation with the Model 1900, therefore the Model 300LW pilot type rating is designated as **BE-300, BE-1900**.

2.1.3 Model B300 / B300C

The Model B300 FSB convened on February 5, 1990 in Wichita, KS to evaluate the Model B300 to determine the Pilot Type Rating. The requesting proposal was to determine if the Model B300 should be part of the Same Pilot Type Rating for the Model 300 and 1900.

The Model B300 is a follow-on version to the Model 300 with increased gross weight and performance changes. The B300 has a 34 inch increase in cabin length, 14 inches ahead of the wing and 20 inches aft of the wing. Wingspan is increased by approximately 3 feet plus winglets adding 7 square feet of wing area. The B300 gross weight is increase to 15,000 pounds with 17 maximum occupants. The B300 is equipped with EFIS on the left side with optional EFIS for the right side. The Model B300C is identical to the B300 except the addition of a large top hinged Cargo Door in place of the bottom hinged passenger airstair door.

The B300 is certificated in the Commuter Category of Part 23 through amendment 34, 14 CFR Part 36-1, and SFAR 27 through amendment 27-4. Commuter Category certification affects minimum crew requirements for the B300 reference 91.531(formerly 91.213). 2 pilots are required with passenger seating configurations of 10 or more.

The FSB concluded the differences between the Model 300 and B300 where not significant enough to warrant as separate type rating. The FSB recommended the Model B300 be given the same type rating as the Model 300 which at the time was the same pilot type rating as the Model 1900. Therefore the pilot type rating for the Model B300 is designated as **BE-300, BE-1900**.

Hawker Beechcraft Corporation, Model 300 Flight Standardization Board Report

2.1.4 Model 300(FF serials) (BE-300F)

The Model 300(FF serials) is a Model 300 modified for use as a flight inspection aircraft and issued FF series serial numbers. The modification consists primarily of an electronic testing equipment installation. The major difference in type design is a large center console, installed in the 300(FF serials) variant that houses some of this flight inspection equipment. The center console restricts either pilot from reaching required items on the opposite side of the cockpit. Because of this condition, the "Pedestal Equipment Location" was cited as the reason for the minimum crew determination of two pilots for all operations. A total of nineteen Model 300's were built with FF series serial numbers. Eighteen of them remain in service.

Modifications to the Model 300 specific to the 300(FF serials) include:

1. Dual EFIS and dual autopilots.
2. The pressurization controller has been moved to the rear of the center console.
3. The FD and AP controls have been relocated to the glareshield.
4. An auxiliary air conditioner to cool the flight test equipment. See supplement 13.
5. Several switches have been relocated and additional mission buses have been installed.
6. An APU that was originally installed in every 300(FF serial), has been subsequently removed from all.
7. Because of the extra flight test equipment, load shedding is different. For example, if a generator fails, the A/C will automatically shed, provided the gear is in the up position.
8. Performance figures are more conservative than those of the Model 300. (to meet ICAO requirements)
9. A battery temperature monitor, which is a requirement for the Nicad batteries, and a battery warning & caution lights.
10. Center pedestal location resulting in minimum crew determination of 2 pilots. AFM Limitation, two pilots are required.
11. Certified for CAT II operations with 2 pilot crew.

NOTE The BE-300 and the BE-300F have identical flight characteristics. An evaluation conducted during engine cuts and single engine operations determined that although the rudder boosts are manufactured by King Avionics on the BE-300F and Collins Avionics on the BE-300, they operate the same. Documentation of this effort was recorded on March 11, 1987.

2.1.4.1 300FF Separate Type Rating (2 pilot airplane)

On April 25, 1990, the FSB recommended that the BE-300(FF serials) have a separate Type Rating to accommodate the 2 pilot minimum crew requirement different from existing BE-300, BE-1900 minimum crew of 1 pilot. AFS-800 issued a Memo dated May 24, 1990 that designated the BE-300FF as a separate Type Rating rescinding the AFS-800 Memo issued April 4, 1990 that authorized operation of 300(FF Serials) with the same BE-300, BE-1900 pilot type rating without supporting FSB justification to do so. On June 12, 1990, the designation was changed to **BE-300F** to accommodate 7 digit limit for pilot type rating designation.

Hawker Beechcraft Corporation, Model 300 Flight Standardization Board Report

2.1.4.2 300FF Same Type Rating Determination (2 pilot airplane)

Aviation System Standards (AVN), the sole operator of the BE-300F, requested by letter dated December 9, 1999, that the FSB be reconvened to consider eliminating the BE-300F as a separate Type Rating. This would allow AVN pilots to receive all of their aircraft training at Flight Safety International(FSI), including the Type Rating flight tests. Currently, FSI administers 85% of the aircraft training and testing in flight simulators. AVN then completes the remaining 15% in the BE-300F aircraft. This action would streamline the training program by affording AVN the opportunity to concentrate primarily on variant, differences, and on the job training. On August 21, 2001, the FSB convened in Wichita, Kansas to consider making the BE-300 and BE-300F the same pilot type rating. Aircraft systems were among several items discussed to determine the level of differences between the BE-300 and the BE-300F.

FSB recommended as of May 21, 2002 the BE-300F no longer be a separate Pilot Type Rating. It will share a same type rating with the BE-300, and become a variant of the BE-300. Upon satisfactory demonstration of his/her ability to pilot a BE-300, in accordance with the Practical Test Standards, a pilot will be qualified to pilot the BE-300F, without further testing. Differences and currency training is required as outlined in this report. Minimum crew determination for 2 pilots is unchanged by this same type rating determination.

The current holder of a BE-300F type rating would be authorized to have the BE-300 type rating added to his/her pilot certificate, without further testing. BE-300 type ratings obtained by this method, would carry the limitation "second in command required," until the pilot demonstrated single pilot competency, in accordance with the Practical Test Standards. The BE-300F type rating designation should remain on the pilot certificate.

2.1.4.3 300FF Same Type Rating (1 pilot airplane) (STC # SA01267WI-D)

Model 300(FF Serials) modified by installation of Rockwell Collins Proline 21 EFIS per STC # SA01267WI-D, approved July 27, 2007, have a minimum crew determination of 1 pilot for STC type design. The FSB convened in Cedar Rapids, IA on July 25, 2007 to evaluate the differences for installation of Proline 21 EFIS in Model 300(FF Serials) previously equipped with Bendix King EFS-10. Model 300(FF Serials) modified by STC# SA01267WI-D require 1 pilot with the "**BE-300**" pilot type rating. Model 300(FF Serials) not modified by STC# SA01267WI-D continue to require a minimum crew of 2 pilots.

Hawker Beechcraft Corporation, Model 300 Flight Standardization Board Report

2.2 Pilot Type Rating Determination

In accordance with 14 CFR Parts 1 and 61, the pilot type rating for the Model 300 (including FF serials), 300LW, B300, B300C is designated as “**BE-300**”. All maneuvers required by the Airline Transport Pilot and Aircraft Type Rating Practical Test Standards are applicable. No aircraft specific flight characteristics are specified. Airmen who successfully complete a practical examination in the Model 300, 300LW, B300, B300C receive a “**BE-300**” pilot type rating on their pilot certificate. The BE-300 type rated aircraft have minimum crew determinations for 1 pilot operations except for Model 300(FF Serials) unmodified by STC# SA01267WI-D which have minimum crew determination for 2 pilots in all operations.

NOTE: The Model 300 pilot type rating was added as the same “BE-1900” pilot type rating February 7, 1984. The pilot type rating was subsequently revised December 6, 1984 to a common pilot type rating “BE-300, BE-1900” for Models 300, 1900 & 1900C. The Model 300LW was included to the common pilot type rating “BE-300, BE-1900” on June 17, 1988. The Model B300 was added to the common pilot type rating “BE-300, BE-1900” on February 15, 1990. The Model B300C was included in the common pilot type rating “BE-300, BE-1900” as identical to the Model B300 except for the cargo door. The Model 300 (FF Serials) is determined a separate pilot type rating May 24, 1990 because the minimum crew determination is 2 pilots. The “BE-300, BE-1900” pilot type rating was issue to pilots for a Practical Test completed in any Model 300 series until November 6, 1991. After November 6, 1991 the BE-300 and BE-1900 are issued as separate pilot type ratings with pilots completing a Practical Test in any Model 300 series receiving the “BE-300” pilot type rating. The Model 300(FF serials) were deleted as a separate pilot type rating and included in the “BE-300” pilot type rating as of May 21, 2002.

2.2.1 Inactive Pilot Type Rating (**BE-300F**)

When the Model 300(FF serials) entered service they were designated a separate BE-300F pilot type rating May 24, 1990 to accommodate the 2 pilot minimum crew and other differences. Model 300(FF serials) continue as a separate BE-300F pilot type rating until May 21, 2002 when the separate pilot type rating was deleted to allow the Model 300(FF serials) to be the same BE-300 pilot type rating as the rest of the Model 300 series. At the time this occurred the Model 300 series had been separated from the Model 1900 series pilot type rating and the use of a “Second-in-Command Required” type rating limitation was recognized to accommodate the 2 pilot minimum crew requirement for the Model 300(FF serials).

After May 21, 2002 any pilot completing Practical Test in a Model 300(FF serial) airplane received a BE-300 pilot type rating with a “Second-in-Command Required” Limitation. The holder of a BE-300F pilot type rating on their pilot certificate is authorized to have the BE-300 pilot type rating added to their pilot certificate without any further testing. BE-300 pilot type rating obtained by this method would carry the limitation “Second-in-Command Required”. The BE-300F pilot type rating should remain on the pilot certificate. The BE-300F pilot type rating remains valid to operate the Model 300(FF serials) airplane only. The BE-300 pilot type rating is required to operate any other Model 300 series airplane except Model 300(FF serials). The holder of a BE-300 pilot type rating is authorized to operate a Model 300(FF serial) airplane after May 21, 2002 provided pilot certificate limitations and airplane minimum crew requirements are met.

Model 300(FF Serials) modified by installation of Rockwell Collins Proline 21 EFIS per STC # SA01267WI-D, approved July 27, 2007 changed minimum crew requirement to 1 pilot. Any pilot completing a practical test in a Model 300(FF serial) modified per STC # SA01267WI-A and operated with 1 pilot for the practical test may receive a BE-300 pilot type rating without a “Second-in-Command Required” limitation.

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

2.3 “Second-In Command Required” Limitation Pilot Type Rating

In accordance with the provisions of 14 CFR 61.43(b)(3), FAA Order 8900.1 and AC 120-53A, a pilot type rating with a “Second-in-Command Required” Limitation is assigned to the BE-300 pilot type rating whenever a pilot practical test is completed utilizing a 2 pilot flight crew. This assignment of limitation is based on practical test demonstrated ability for the flight crew utilized regardless of whether the airplane’s minimum required certificated flight crew is 1 pilot or 2 pilots.

A “Second-in-Command Required” Limitation is always applicable for pilot practical test given in Model 300(FE serials) unmodified by STC# SA01267WI-D or if the holder of a BE-300F pilot type rating is issued a BE-300 pilot type rating without any further testing.

2.3.1 Removing SIC Limitation

Removing a “Second-in-Command Required” limitation issued in accordance with provisions of 14 CFR 61.43(b)(3), FAA Order 8900.1 and AC 120-53A may be accomplished with a partial practical test in accordance with FAA Order 8900.1, Vol.5, Chp.2, Sec.19 or the Designated Pilot Examiners Handbook.

2.4 Determination of Second-In-Command Pilot Type Rating

The Second-In-Command Pilot Type Rating (BE-300 SIC PRIVILEGES ONLY) may be issued in accordance with 14 CFR Part 61.55. In addition to training in accordance with 61.55, the items identified in paragraph 5.2.5 Seat Dependant Task Training must be performed and 5.2.3 Flight Crew Emergency Training must be accomplished for all SIC qualifications in the BE-300.

3. MASTER REQUIREMENTS

3.1 Master Common Requirements

- No “Specific Flight Characteristics” are designated for training or checking.
- Landing Minima Category for the BE-300 is generally Category “B” for normal straight in approaches (Flaps Down) and Category “C” for normal circling approaches (Flaps Approach) unless otherwise required by 14 CFR or Operations Specifications. (14 CFR 97.3)
- Normal “Landing Flap Setting” is Flap Down.(14 CFR 91.126(c))
- Normal “Takeoff Flap Setting” is Flap Up or Flap Takeoff.
- “No Flap” Approach & Landing is not waived. Training and checking is required.
- For Model 300(SFAR 41) normal straight-instrument approaches are flown with Flaps Approach until landing is assured due to lack of Approach Climb Gradient data. For Model B300 (Commuter Category) or 300(SFAR 41) with ICAO Annex 8 Performance, landing configuration may be selected at the final approach fix. Use of constant angle non-precision approaches is recommended.
- Normal Circling approaches are flown Flaps Approach from the FAF until landing is assured.
- Minimum Altitude for Autopilot use is determined by specific autopilot options. Evaluated procedures were with Autopilot engagement for Departure/Cruise at 1000 ft AGL and 200 ft AGL on Approach with Collins FCS-65 Autopilot. Bendix/King KFC-400 Autopilot is 500 ft AGL for Climb, 1000 ft AGL for Cruise and 200 ft AGL for Approach. Collins Proline 21 Integrated Autopilot is 400 ft AGL for Takeoff, 1000 ft AGL for Cruise, 79 ft AGL on coupled Approach, and 160 ft AGL for Steep Approach. Proline 21 Integrated APS-300 Autopilot per STC # SA01267WI-D is 300 ft AGL for Takeoff, 1000 ft AGL for Cruise, and 100 ft AGL for Approach. Garmin GFC-700 Autopilot is 400 ft AGL for Takeoff, 1000 ft AGL for Cruise, 200 ft AGL for coupled Approach with vertical guidance, and 400 ft AGL or MDA for Approach without vertical guidance.

Hawker Beechcraft Corporation, Model 300 Flight Standardization Board Report

3.1.1 Areas of Special Emphasis

The FSB has determined that certain aspects of pilot knowledge, skills and abilities are especially critical to safe operation of the BE-300 and must be emphasized during training and evaluated during checking for the BE-300.

- Training for High Altitude Operation is required 14 CFR 61.31 for all Model 300 airplanes
- Knowledge of aircraft performance determination should be emphasized. Specific performance factors vary with different certification categories for SFAR 41 and Commuter Category.

3.2 Master Difference Requirements (MDR)

The Master Difference Requirements for related aircraft of the BE-300 are shown in Appendix 1. These provisions apply when differences between related BE-300 aircraft exist which affect crew knowledge, skills, or abilities related to flight safety. (e.g. Level A or greater differences)

Footnotes to MDR requirements define acceptable "required means" or "alternate means" of compliance. A footnote can indicate requirements that are less restrictive than the basic designation, or more restrictive than the basic designation, depending on the significance of the differences between related aircraft.

4. OPERATOR DIFFERENCE REQUIREMENTS TABLES (ODR)

4.1 ODR Tables

ODR tables are used to show an operator's compliance method. ODR tables for operators conducting mixed fleet operations, using the BE-300 are shown in Appendix 2. The ODR tables represent an acceptable means to comply with MDR provisions based on those differences and compliance methods shown. The tables do not necessarily represent the only acceptable means of compliance for operators with airplanes having other differences, where compliance methods (e.g., devices, simulators, etc.) are different. For operators flying the BE-300 the ODR tables in Appendix 2 have been found acceptable, and therefore, may be approved by a POI for a particular operator. The three types of ODR Tables are Design, System and Maneuver Differences Tables. Design differences account for equipment model changes. System differences account for specific system level changes. Maneuver differences account for changes in operating procedures of changed equipment.

4.2 Operator Preparation of ODR Tables

Operators flying a "mixed fleet" of BE-300 aircraft must have approved ODR tables pertinent to their fleet

4.3 ODR Table Coordination

Unless identical or equivalent ODR tables have been previously approved by the FAA, new ODR tables proposed by operators should be coordinated with the FSB prior to FAA approval and implementation. FSB coordination ensures consistent treatment of related BE-300 aircraft between various operators, and compatibility of each ODR table with MDR provisions

4.4 ODR Table Distribution

Original FAA approved ODR tables are to be retained by the operator. Copies of FAA approved ODR tables are to be retained by the Certificate Holding District Office (CHDO) and should be provided to the BE-300 FSB Chairman at the applicable AEG

5. FSB SPECIFICATIONS FOR TRAINING

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

5.1 General

5.1.1 Assumptions Regarding Airmen's Previous Experience. The provisions of this Section apply to programs for airmen who have experience in multi-engine turboprop aircraft including various avionics suites and navigation experience. For airmen not having this experience, additional requirements may be appropriate as determined by the POI, FSB, and/or AFS-200.

5.1.2 Training for Seat Dependent Tasks. Accomplishment of certain tasks, procedures, or maneuvers requires training of a crewmember for a particular crew position when other than single pilot operation (e.g. captain, first officer, check airman, etc.). Training programs should recognize and address the necessary seat/position related tasks for the applicable crewmember. Accordingly, training programs should address seat dependent tasks or maneuvers to the extent necessary to satisfy crew qualification objectives and should be in accordance with ODR tables when applicable.

5.1.3 Second-In-Command Training Tasks. Flight Crews qualify to serve as SIC must accomplish certain tasks, procedures or maneuvers for the SIC crew position. Training programs should address all training elements of the 14 CFR 61.55 and/or 14 CFR 135.345 in accordance with FAA Order 8900.1. SIC Pilot Type Rating may be issued in accordance with the 14 CFR 61.55(d) or (e) provided training required by the 14 CFR and FAA Order 8900.1, including tasks stipulated by this report, are completed.

5.2 Initial / Transition / Upgrade Training:

5.2.1 Pilots Initial, Transition and Upgrade Ground Training. Initial, transition, or upgrade ground training for the BE-300 is accomplished as specified by 14 CFR and FAA Order 8900.1. No unique provisions or requirements are specified. Training program hours may be reduced as specified in 14 CFR and FAA Order 8900.1.

5.2.2 Pilots Initial, Transition and Upgrade Flight Training. Initial, transition, or upgrade flight training for the BE-300 is accomplished as specified by 14 CFR and FAA Order 8900.1. No unique provisions or requirements are specified. Training program hours may be reduced as specified in 14 CFR and FAA Order 8900.1.

5.2.3 Crewmember Emergency Training. Crewmember emergency training should be conducted for the BE-300 in accordance with 14 CFR and FAA Order 8900.1. The objective of emergency training for the BE-300 aircraft is to provide crewmembers with the necessary knowledge concerning emergency equipment, situations, and procedures, to ensure implementation of the correct actions in the event of an emergency.

Emergency training consists of instruction on the location, function, and operation of emergency equipment in each related aircraft of the BE-300. Where emergency equipment is common, instruction may be adjusted for crewmembers qualified and current on this equipment, provided records are available which demonstrate that crewmembers meet 14 CFR and FAA Order 8900.1 requirements. For example, if the fire extinguishers are common to fire extinguishers on other aircraft in the operator's fleet, training may be credited for all applicable aircraft. Conversely, for equipment that is unique to the BE-300, training on the emergency equipment for each related aircraft is required.

Emergency training also consists of instruction in crewmember emergency assignments and procedures including crew coordination and communication, the handling of emergency or other unusual situations, and emergency performance and observation drills specific to BE-300 aircraft.

Hawker Beechcraft Corporation, Model 300 Flight Standardization Board Report

In accordance with the 14 CFR and FAA Order 8900.1, emergency training requirements refer to two types of training: "general" emergency training and "aircraft-specific" emergency training. General emergency training is instruction on those emergency items that are common to the BE-300 and all aircraft in the operator's fleet, e.g., instruction on fire extinguishers and firefighting procedures, if common to all aircraft. Aircraft-specific emergency training is training on those items that are specific to the BE-300 aircraft. An example of aircraft-specific emergency training is instruction on the location of emergency equipment.

As part of an approved training program, an operator may use many methods when conducting aircraft-specific emergency training, including classroom instruction, pictures, videotape, ground training devices, computer-based instruction, and static aircraft training.

There are no specified training program hours for Crewmember Emergency Training. A chart addressed in 8900.1 provides "national norms" for the approval of the general emergency training program hours. The complexity of the different related aircraft of the BE-300 and the complexity of the type of operation to be conducted should be considered when approving the BE-300 aircraft-specific emergency training.

5.2.4 Areas of Special Emphasis Training. The following areas of emphasis should be addressed during ground and flight training:

- a) Aircraft performance calculations and the differences in certification rules between SFAR 41 and Commuter Category performance. Gross versus Net climb gradients for TERPS and obstacles.
- b) Navigation means with various installed equipment and area navigation systems.
- c) Primary Flight Display format and function for mechanical, electronic and PFD displays.
- d) EFIS function and procedures should be emphasized throughout training. Special significance should be placed on Display Processor Unit (DPU) failures and EFIS Reversionary Switching. Use of Composite Mode should be trained to conduct Precision and Non-Precision Approaches, with and without the Flight Director.

5.2.5 Training for Seat Dependent Tasks. Accomplishment of certain tasks, procedures, or maneuvers require training of a crewmember for a particular crew position (i.e. captain, first officer, check airman, etc.). Training programs should recognize and address the necessary seat/position related tasks for the applicable crewmember. Accordingly, training programs should address seat dependent tasks or maneuvers to the extent necessary to satisfy crew qualification objectives, and per ODR tables when applicable.

Procedures which could have Seat Dependent Elements when operating with 2 pilot crew (as determined by each operator and/or POI). These may include the following:

- a) Cockpit Preflight
- b) Rejected Takeoff
- c) Engine Fire and Failure During Takeoff after V1
- d) Abnormal Procedures for One-Engine-Inoperative and Landing
- e) Manual Gear Extension

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

5.2.6 Second-In-Command Crew Training. SIC crew training is accomplished as specified in 14 CFR 61.55 and/or 14 CFR 135.345. Training programs should address tasks stipulated in FSB Specifications for Training; Areas of Emphasis, Training for Seat Dependent Tasks and SIC Crew Training are accomplished.

5.3 Differences Training:

5.3.1 General. Unless an initial or transition program is completed for each related aircraft, differences training is necessary for each related aircraft or type, as provided in MDR and ODR tables. Detailed sample ODR tables are available in Appendix 2.. These ODR tables may not include items that are applicable to particular operators.

- a) A Differences Training Program prerequisite is that a trainee has completed initial, upgrade, or transition training in one related aircraft and will receive differences training for the other related aircraft.
- b) When a Differences Training Program involves related aircraft having the same Pilot Type Rating, coverage of differences may be completed either coincident with each phase of an initial, upgrade, or transition training course, or following completion of that training course. The differences training must be consistent with the provisions of the approved applicable MDR/ODR Tables.
- c) When a Differences Training Program involves related aircraft having different Pilot Type Ratings, coverage of a differences course must be completed in accordance with the prerequisites defined in 5.1.1, and applicable MDR/ODR provisions.

5.3.2 Differences Ground Training. Differences ground training is required on the topics applicable to the pertinent related aircraft and is shown by applicable ODR tables.

5.3.3 Differences Flight Training. Difference flight training is required in the topics and maneuvers applicable to the pertinent related aircraft that is shown by applicable ODR tables.

5.4 Recurrent Training

5.4.1 Recurrent Ground Training. Courses must include appropriate training in accordance with 14 CFR 135.351 for each related BE-300 aircraft as specified by MDR and ODR tables for differences training.

5.4.2 Recurrent Flight Training. Courses require appropriate maneuvers and procedures identified in the 14 CFR, FAA Order 8900.1 or as otherwise described in this report. Maneuvers and procedures must account for differences between each related BE-300 aircraft operated. The ODR table(s) must identify the differences.

5.4.3 Recurrent training consideration for Mixed Fleet Flying Operations. When different pilot type ratings are assigned between the related aircraft, an alternate plan for recurrent training and checking is acceptable.

5.4.4 Training program hours for Recurrent Training may be reduced as specified in 14 CFR and/or FAA Order 8900.1.

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

5.5 Operating Experience

Initial Operating Experience, Supervised Operating Experience, and Supervised Line Flying are in accordance with existing 14 CFRs for assigned flight crew position in the BE-300.

For the purpose of obtaining operating experience or receiving a line check, the Pilot-in-Command of the BE-300 aircraft must occupy the left pilot seat due to orientation of equipment controls.

5.5.1 Supervised Operating Experience(SOE). SOE required for a PIC Type Rating in accordance with the 14 CFR pilot certification must be accomplished from the left pilot seat.

5.6 Other Training

5.6.1 LOFT Programs(14 CFR 121.409(b)(3)). When operators have LOFT programs and related BE-300 aircraft, POIs should review LOFT credits to assure suitability for each BE-300 aircraft.

5.6.2 Instrument Approaches. Only Model 300(FF serials) are certified for CAT II operations.

Note: Operators should assure that flight crews are familiar with appropriate use of the Flight Guidance System and FMS or navigation radios, including modes to be used, for the types of instrument approaches to be flown, when using Area Navigation methods in lieu of or in conjunction with NDB, VOR, localizer, or back course localizer procedures. This emphasis is also appropriate for aircraft that do not have certain navigation system sensors, such as ADF, installed.

5.6.3 Aircraft Dispatchers. Initial and transition training should be conducted in accordance with 14 CFR and FAA Order 8900.1.

6. FSB SPECIFICATIONS FOR CHECKING

6.1 Checking Requirements

The BE-300 is considered a separate type of aircraft as described in 14 CFR 135.293(b) for the purpose of recurrent checking. Twelve month testing currency applies to the BE-300 exclusively for compliance with 14 CFR 135.293.

All checking must include evaluation of the subjects and maneuvers listed in the Master Requirements, Areas of Special Emphasis, of this report and the following subject areas, if equipped:

- Takeoff Safety, Performance planning & decisions, contaminated runways
- High altitude conditions and aerodynamics
- RVSM, TCAS, TAWS and Windshear functions and procedures
- Inflight and Ground Icing Awareness
- CRM and CFIT procedures

A pilot being checked for the addition of a type rating or PIC proficiency check must occupy the left pilot seat due to an inability to access all equipment controls from the right seat.

Hawker Beechcraft Corporation, Model 300 Flight Standardization Board Report

6.1.1 Checking Items. Pertinent knowledge, procedures, and maneuvers specified by 14 CFR 61, FAA Practical Test Standards (PTS), 14 CFR 135.293, 297, & 299, and 14 CFR 121, Appendix F, pertinent to multi-engine turboprop aircraft apply.

6.1.2 Specific Flight Characteristics. No Specific Flight Characteristics are applicable to the Model 300

6.1.3 Areas of Checking Emphasis. The following areas of emphasis should be addressed during checks:

- a) Aircraft Performance calculation and aircraft handling to achieve performance.
- b) Demonstration of FMS navigation (departures, arrivals, approaches) proficiency.
- c) Selection and use of EFIS displays, raw data, flight director, and Reversion/Composite modes, including DPU failure when applicable.

6.1.4 No Flap Landings. Demonstration of a No Flap approach and landing during an 14 CFR 61, 14 CFR 135 or 14 CFR 121 Appendix F check is appropriate. In accordance with Order 8900.1, when the flight test is conducted in the airplane in actual flight, a touchdown from a no flap is not required. However, the performance and handling of the Model 300 is such that it is acceptable to conduct No Flap Landings to a full stop.

6.2 Type Ratings

6.2.1 Oral Examinations. Oral examinations for the BE-300 may be completed at the end of the academic phase of training. Oral test items need only address the model for which the test is being conducted when qualification is sought on only the one 300 variant being tested.

6.2.2 Practical Tests. Practical tests may follow standard provisions of 14 CFR 61. The satisfactory completion of a practical type rating evaluation in any BE-300 will meet the requirement for the BE-300 type rating. In order to operate another related aircraft, crewmembers operating under 14 CFR Part 135 are required to satisfactorily comply with the requirements of the MDR and ODR tables in Appendices 1 and 2. The same requirement should be followed by flight crewmembers operating under 14 CFR Parts 91.

6.2.3 Application for and Issuance of Type Ratings. Airmen completing pertinent 14 CFR 61 requirements in either a BE-300 in accordance with FSB requirements described in this report, may apply to the FAA for the BE-300 type rating endorsement. Upon completion of required tests, and submission of an application (FAA Form 8710-1), authorized FAA inspectors or designees may issue the necessary pilot certificate with type rating.

6.3 Proficiency Checks

6.3.1 General. Proficiency Checks are administered as designated in 14 CFR and FAA Order 8900.1. These checks must be administered by an authorized check airman, or FAA Aviation Safety Inspector. A proficiency check in any Model 300 suffices for the BE-300 type rating provided the check is administered by a Designee, or FAA Aviation Safety Inspector. Satisfactory completion of a proficiency check may be substituted for recurrent flight training as permitted in 14 CFR 135.

6.3.2 Proficiency Checks for Mixed Fleet Flying. Proficiency Checks for Mixed Fleet Flying should alternate checks each 6 months for PICs and annually for SICs between 300 and B300 aircraft. Aircraft Differences must be addressed in accordance with the MDR and ODR tables for that operator

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

6.4 Instructors, Check Airman and Examiners

For the purpose of checking, FAA Aviation Safety Inspectors, Designated Pilot Examiners, Training Center Evaluators and Check Airmen must be PIC qualified in the BE-300. Examiners and Check Airmen should have 100 hours PIC in the BE-300 and maintain currency in accordance with this report to provide checking in the aircraft.

7. FSB SPECIFICATIONS FOR CURRENCY

Currency requirements (14 CFR 61.55, 61.56, 61.57, and 135.247) for the BE-300 require BE-300 experience in accordance with applicable 14 CFRs. No “Group” or similar type rated airplane credit is given.

7.1 Recent Flight Experience: 14 CFR 61.57. BE-300 type is considered separate experience for 14 CFR 61.57(a)&(b).

7.1.1 Take off and landing credit is permitted. Takeoffs and landings performed in any Model 300 aircraft may be credited to all BE-300 aircraft. Recency of experience should include operation/programming of the Navigation System and Flight Guidance System.

7.2 Instrument Currency: Instrument experience to satisfy 14 CFR 61.57(c) is not BE-300 exclusive provided BE-300 Recent Flight Experience requirements are maintained.

7.3 Currency for Mixed Fleet Flying Operations. These are shown in MDR/ODR tables

7.4 Methods to Reestablish Currency

Re-establishing currency for the BE-300 is in accordance with existing 14 CFRs and FAA guidance for Recent Flight Experience and/or Requalification.

7.4.1 When MDR/ODR specifies Level B Currency, currency is maintained by operating the variant aircraft within the previous 180 days. Currency may be reestablished by a review of Placards, Limitations and Operating Procedures prior to operating the variant airplane.

7.4.2 When MDR/ODR specifies Level C Currency, currency is maintained by operating the variant aircraft through a complete flight cycle including an instrument approach procedure within the previous 90 days. Currency may be reestablished by operating the variant with a qualified PIC for at least one flight segment, completing a Line Check with a Line Check Airman, completing a Proficiency Check in the variant aircraft or compliance with 14 CFR 61.57(c) or (d) recent flight experience requirements in the variant airplane.

7.4.3 When MDR/ODR specifies Level D Currency, currency is maintained by operating the variant aircraft through 3 complete flight cycles (takeoff, departure, arrival, approach and landing) within the previous 90 days. Currency may be reestablished by completing a Line Check with a Line Check Airman, completion on a Proficiency Check in the variant aircraft or compliance with 14 CFR 61.57(c) or (d) recent flight experience requirements in the variant airplane.

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

8. AIRCRAFT REGULATORY COMPLIANCE CHECKLIST

No Compliance Checklist has been published for the BE-300. Appendix 4 to this report is reserved. Model 300 series aircraft have been in service for an extended period of time so the methods of compliance with regulatory requirements are established.

8.1 Specific Compliance Items

- 8.1.1 Emergency Evacuation Demonstration has not been conducted. Operators must comply with 135.331(3)(iii).
- 8.1.2 Ditching Demonstration and compliance with 25.801 has not been demonstrated. Operators must comply with 135.331(3)(iii).
- 8.1.3 Forward Observer Seat Available forward passenger seats were evaluated and found suitable for conducting enroute inspections per 135.75(b). The right front passenger seat has been demonstrated suitable with the standard passenger seat / seatbelt, passenger oxygen and a splitter cord for audio. Audio jacks may be installed at the forward seat to provide for enroute inspection.
- 8.1.4 Proving Tests to satisfy 14 CFR 135.145 have not been conducted and should be conducted in accordance with FAA Order 8900.1.
- 8.1.5 Validation Tests to satisfy 14 CFR 135.145(d) should not be given credit for previous operation of turbojet airplane of the same make due to lack of similarity of aircraft system automation and integration with other aircraft of the same make. It may be acceptable to give credit for of turbojet airplanes of similar design provided design similarity can be substantiated.
- 8.1.3 Electronic Flight Bag
Electronic Checklists (Proline 21 Only)
Printed Pilot Checklist remains required for compliance with 14 CFR 91.503, 135.83. The Electronic Pilot Checklist does not contain all required procedures due to inability to function in all non-normal flight operation situations. The Electronic Pilot Checklist is acceptable for use for those Normal Procedures it contains provided the aircraft operator ensures the Electronic Pilot Checklist procedures remain current for the aircraft.

Electronic Charts (Proline 21 Only)

Electronic Approach Charts (SIDS, STARS, Approach Charts & Airport Diagrams) are available through the IFIS-5000 File Server Unit. Dual redundancy is not met due to single MFD Display, File Server Unit, and Cursor Control Panel. Memory button selection on the Cursor Control Panel is required to allow single pilot action to change between Navigation Display, Electronic Checklist Display and Electronic Charts Display to mitigate single pilot workload using these functions. The enhanced map overlays do not meet requirements for Enroute charts therefore another suitable source of Enroute Chart information must be available at the pilot station.

(G1000 Only)

Electronic Approach Charts (SIDS, STARS, Approach Charts & Airport Diagrams) are available through the GDU-1500 MFD SD Card. Dual redundancy is not met due to single MFD Display and SD Card. Display does not meet criteria for full chart displayed equally viewable to paper being replaced however the zoom and pan feature allows a single pilot action to view the remainder of a chart when set to a readable size. In addition, the chart display function has softkeys for Briefing, Plan, Profile & Minimums chart sections to be selected with single pilot action.

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

9. FSB SPECIFICATIONS FOR SIMULATORS AND DEVICES

Requests for device approval should be made in accordance with FAA procedures.

Flight Training Device and Flight Simulator characteristics must comply with applicable 14 CFRs. Credit for training, checking and currency in an approved Flight Training Device (FTD) or Simulator is allowed in accordance with the Simulator Task Credit given in accordance with Airline Transport Pilot and Aircraft Type Rating Practical Test Standards or current guidance in FAA Order 8900.1, as applicable, except where this report is more restrictive.

10. APPLICATION OF FSB REPORT

All BE-300 operations are subject to the provisions of this report. This report becomes effective when given final approval by the FAA. Training, checking and currency for the BE-300 aircraft must be conducted in accordance with all provisions of this report. All FAA Approved Training Programs must incorporate the latest FAA Approved AFM Procedures, AFM compliant checklist, manufacturer's recommendations for training maneuvers and all provisions of this report.

11. ALTERNATE MEANS OF COMPLIANCE

11.1 Approval Level and Approval Criteria

Alternate means of compliance to the requirements of this report must be approved by the FSB. If alternate compliance is sought, operators must show that the proposed alternate means provides an equivalent level of safety to the provisions of AC 120-53 and this FSB report. Analysis, demonstrations, proof of concept testing, differences documentation or other evidence may be required.

11.2 Equivalent Safety

Significant restrictions may apply in the event alternate compliance is sought, and the reporting requirements may be increased to ensure equivalent safety. FAA will generally not consider relief through alternate compliance unless sufficient lead-time has been planned by an operator to allow for any necessary testing and evaluation.

11.3 Interim Programs

In the event of clearly unforeseen circumstances in which it is not possible for an operator to comply with provisions of this report, the operator may seek an interim program approval rather than a permanent alternate compliance method. Financial arrangements, scheduling adjustments and other such reasons are not considered "unforeseen circumstances" for the purposes of this provision. Interim program approvals must be approved by the FSB Chairman.

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

APPENDIX 1 - AIRCRAFT MDR TABLES
MASTER DIFFERENCE REQUIREMENTS TABLE

		FROM Aircraft (Base Aircraft)							
		*	*	*	*	**	***		
		300	300LW	B300 B300C Except Proline 21	B300 B300C Proline21	300 (FF serial) EFS-10	300 (FF serial) Proline21		
T O A i r c r a f t	* 300	A/A/A (1)(2)(3) (4)(5)(6)	B/A/B (1) (2) (3)(4)(5)	B/B/B (1)(2) (3)(4)(5)	D/C/C	Not Evaluated	D/D/D		
	* 300LW	B/A/B (1) (2) (3)(4)(5)	A/A/A (1)(2)(3) (4)(5)(6)	B/B/B (1)(2) (3)(4)(5)	D/C/C	Not Evaluated	D/D/D		
	* B300 B300C Except Proline 21	B/B/B (1)(2) (3)(4)	B/B/B (1)(2) (3)(4)	A/A/A (1)(2) (3)(4)(6)	D/C/C	Not Evaluated	D/D/D		
	* B300 B300C Proline 21	D/C/C	D/C/C	D/C/C	A/A/B (3)(7)	D/C/D	B/B/C (3)		
	** 300 (FF serial) EFS-10	C/D/D	C/D/D	C/D/D	D/D/D	A/A/B	D/C/D		
	*** 300 (FF serial) Proline 21	D/D/D	D/D/D	C/D/D	C/C/C	D/C/D	A/A/B (3)		

NOTES

* Pilot Type Rating BE-300

** Pilot Type Rating BE-300F applicable to FF serials(FF-1 to 19) Type Certificated for 2 pilots, June 12, 1990 to May 21, 2002. Pilot Type Rating BE-300 applicable to FF serials(FF-1 to 19) Type Certificated for 2 pilots after May 21, 2002 and BE-300F Pilot Type Rating is no longer issued after May 21, 2002.

*** Pilot Type Rating BE-300 for FF serials(FF-1 to 19) with STC# SA01267WI-A for Proline 21 and single pilot operation.

(1) Primary Flight Instruments may include mechanical, electro-mechanical, Collins EFIS-74A & EFIS 85 (3, 4 or 5 tube), Sperry EDZ 600/800 (3 or 5 tube), Bendix EFS-10 (3 or 4 tube). Differences in primary flight instruments from mechanical and electro-mechanical (servo) to EFIS or between EFIS systems installations is C/B/C. Differences in primary flight instruments from EFIS to mechanical and electro-mechanical (servo) or between mechanical and electro-mechanical (servo) is B/B/B.

(2) Installation of Proline 21 on aircraft equipment listed in NOTE (1) is D/C/C.

(3) For Collins Proline 21 equipped aircraft, the installation of IFIS-5000 FSU is C/B/C.

(4) Installation of Collins IDS-3000 ON EFIS 85 aircraft is D/C/C.

(5) Installation of Honeywell EPIC CDS/R on EDZ-600/800 aircraft is D/C/C.

(6) Installation of GARMIN G1000 is D/C/D.

(7) Installation of GARMIN G1000 is C/C/C for basic equipped or D/C/D if optional SVS & ESP.

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

APPENDIX 2 - AIRCRAFT SAMPLE ODR TABLES

SAMPLE DIFFERENCE TABLE

Definitions used in the ODR Tables:	
X	= Pilot's Operating Handbook and or Flight Manual Supplement
CPT	= Cockpit Procedure Training
SI	=Self Instruction
AI	=Aided Instruction

DIFFERENCE AIRCRAFT: 300(FF Serials)				COMPLIANCE METHOD					
BASE AIRCRAFT: Model 300				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
21 Air Conditioning	Auto Pressure Controller located at rear of Center Pedestal	No	Minor	SI				A	B
21 Auxiliary Air Conditioner	Initially installed then later removed.	No	Minor		AI			B	B
22 Autopilot/Yaw Damper	Yaw Damper-King vs Collins. Both operate identically.	No	No	SI				A	A
23 Communication	Addition audio panel and communication equipment.	No	No	AI				B	B
24 Electrical Power	Load Shedding	No	Yes		AI			B	C
25. Flight Inspection Panel System	Mission specific equipment installed.	No	Yes			AI		B	B
26 Fire Protection	Location of Portable Fire Extinguishers.	No	No	SI				A	A
34 Navigation	Bendix King EFS-10 Electronic Flight Instruments System (EFIS) – Symbol Generators. FMS operation. Flight Inspection Control Display Unit.	No	Yes			CPT		D	D

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

DIFFERENCE AIRCRAFT: 300(FF Serials)				COMPLIANCE METHOD					
BASE AIRCRAFT: Model 300				TRAINING				CHKG/CURR	
DESIGN	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
Inst Panel Layout	Dual EFS-10 EFIS and Multi-function Displays. Caution/Warning Panel and Flight Director mode controllers relocated to glareshield. Standby Attitude Indicator required for Dual EFS-10 system.	No	Minor		AI			A	B
Flight Deck	Pressurization controller relocated to rear of center console.	No	Minor		AI			A	B
MANUEVER	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
	No Change								

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

Definitions used in the ODR Tables:	
X	= Flight Manual/Pilot's Operating Handbook and/or FM Supplement
AI	= Aided Instruction
CBT	= Computer Based Training
ICBT	= Interactive Computer Based Training
FTD	= Flight Training Device (Level 1 to 7)
FBS	= Fixed Base Simulator (Level 5 to 7)
FFS	= Full Flight Simulator (Level A, B, C, D)

SAMPLE DIFFERENCES TABLE					COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: B300, B300C (commuter category)										
BASE AIRCRAFT: 300, 300LW (SFAR 41C)					TRAINING				CHKG/CURR	
DESIGN	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR	
General Airplane Configuration	Commuter Category certification basis 34 inches longer cabin, 14 fwd, 20 aft 3 feet wingspan by 18 inch wingtips Cockpit 14 inches fwd reference nacelles	NO	NO		AI			B	B	
Weights	Increase to 15,000 pounds MGTW	NO	NO	X				A	B	
Limitations	VMO/MMO Overspeed Aural Warning Single Engine Reversing Prohibited	NO	YES		AI			B	B	
Placards and Markings	Numerous Annunciator Panel changes.	NO	YES		AI			B	B	
Servicing										
Engines										
Flight Deck										
Instrument Panel Layout	Left side EFIS standard, Right side option. Auto Feather annunciators relocated	NO	YES	X				A	B	
Cabin										
Flight Controls	Flaps preset positions only	NO	YES		AI			B	B	
Aerodynamic Controls	Reduction in roll control forces 3 position Flaps, no intermediate	YES	YES		AI			B	B	

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: B300, B300C (commuter category)									
BASE AIRCRAFT: 300, 300LW (SFAR 41C)				TRAINING				CHKG/CURR	
MANEUVER	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
Preflight									
Engine Start									
Taxi									
Takeoff	Improved Performance for Commuter Category Takeoff, Climb, Approach Climb Changes in propeller Ground Low Pitch Stop at 68 to 70% N1 prevents engine acceleration surges on takeoff.	NO	YES		AI			B	B
RTO Or V1 Fail	B300 meets Engine Failure performance requirements for Commuter Category	NO	YES		AI			B	B
Climb Cruise Decent									
Instrument Approaches									
Landing	Demonstrated Crosswind no 25 Kts	NO	NO	X				A	B
Shutdown	Hot Battery Buss Switch	NO	YES		AI			A	B
Normal Procedures	Changed Normal Procedures for design changes and Commuter Category	NO	YES		AI			B	B
Abnormal Procedures	Changed and New Abnormal Procedures for design changes and Commuter Category.	NO	YES		AI			B	B
Emergency Procedures	No Single Engine Reverse	NO	YES		AI			A	B
In-Flight Maneuvers	Roll Control forces reduced approx. 35%	YES	NO		AI			A	B

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: B300, B300C (commuter category)									
BASE AIRCRAFT: 300, 300LW (SFAR 41C)				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
21 Air Conditioning	Cabin Pressure White Annunciator at 10,000 feet with Aural Tone. Cabin Altitude Red warning annunciator and Aural Tone at 12,000 feet.	NO	YES		AI			B	B
22 Auto-Flight	Control Wheel Disconnect button is 2 position for trim interrupt & AP Disconnect. Autofeather is Torque activated versus bleed air activated previous	NO	YES		AI			B	B
23 Communications	Various radio suite options (See MDR NOTES)	NO	YES						
24 Electrical Power	Both AC Inverters ON full time Hot Battery Buss & Switch added, several power distribution changes	NO	YES		AI			A	B
25 Equipment / Furn.									
26 Fire Protection									
27 Flight Controls	Flap selection 3 position with no intermediate settings.	NO	YES		AI			A	B
28 Fuel	Optional Extended Range Fuel tanks	NO	NO	X				A	B
29 Hydraulic									
30 Ice / Rain	2 Deice Boot green annunciators to monitor boot operation.	NO	YES	X				A	B
31 Indicating/Record	Propeller Pitch Lights now White to preclude transient Master Cautions. Pitch Trim annunciator now caution Add Annunciators: AC Buss, Cabin Overpressure, Auto Feather OFF, Oxygen Not Armed, Rudder Boost OFF, Wing Deice, Tail Deice, 10,000 ft Cabin Altitude, Cabin Differential High, Aural Warning on Airspeed Overspeed.	NO	YES		AI			B	B
32 Landing Gear									
33 Lights	Hot Battery Buss cockpit flood light	NO	YES		AI			A	B
34 Navigation	Various Avionics Suites available as options and may be different from base airplane. (See MDR NOTES)	NO	YES						
35 Oxygen	Add Passenger Oxygen Light	NO	YES		AI			B	B

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: B300, B300C (commuter category)									
BASE AIRCRAFT: 300, 300LW (SFAR 41C)				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
36 Pneumatics	Brake Deice now ON for Takeoff & Landing Remove Rudder Boost from Bleed Air system.	NO	YES		AI			B	B
37 Vacuum									
49 APU									
52 Doors	Cargo Door Model, Large cargo door hinged at top replaces narrow passenger door airstair hinged at bottom.	NO	YES		AI			B	B
53 Fuselage	34 inches longer cabin, 14 in. fwd of wing, 20 in. aft of wing	NO	NO	X				A	A
54 Nacelles/Pylons									
55 Horizontal & Vertical Stab.									
56 Windows									
57 Wings	3 feet wingspan increase by 18 inch wingtips	NO	NO	X				A	A
61 Propellers	Low Pitch Stop resets from Ground Idle to Flight Idle at 68-70% N1 (or Kit # 130-9600)	NO	NO	X				A	A
72 Engine (turbine)									
73 Fuel Controls									
74 Engine Ignitions									
75 Engine Bleed Air									
76 Engine Controls									
77 Engine Indicating									
78 Exhaust									
79 Engine Oil									
80 Engine Starting									

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

Definitions used in the ODR Tables:	
X	= Flight Manual/Pilot's Operating Handbook and/or FM Supplement
AI	= Aided Instruction
CBT	= Computer Based Training
ICBT	= Interactive Computer Based Training
FTD	= Flight Training Device (Level 1 to 7)
FBS	= Fixed Base Simulator (Level 5 to 7)
FFS	= Full Flight Simulator (Level A, B, C, D)

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300, 300LW, B300, B300C Proline 21									
BASE AIRCRAFT: 300, 300LW, B300, B300C Proline 2 EFIS-85				TRAINING				CHKG/CURR	
DESIGN	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
General Airplane Configuration	Change from individual flight instruments to composite PFD format.	No	Yes		AI			C	C
Weights	Revised BOW	No	No	X				A	B
Limitations	New Limitations for new equipment	No	No	X				B	B
Placards and Markings	Changed Placards & Markings for avionics. AFM changed to new P/N	No	Yes	X				B	B
Servicing	No Change								
Engines	No Change								
Flight Deck	Configuration and controls to accommodate Proline 21 system.	No	Yes		AI			C	C
Instrument Panel Layout	EFIS-85 EADI, EHSD, ALT, AS, VSI, TC replaced with Proline 21 PFD(2) & MFD(1)	No	Yes		AI			C	C
Cabin	No Change								
Flight Controls	No Change								
Aerodynamic Controls	No Change								

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300, 300LW, B300, B300C Proline 21									
BASE AIRCRAFT: 300, 300LW, B300, B300C Proline 2 EFIS-85				TRAINING				CHKG/CURR	
MANEUVER	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
Preflight	PFD/MFD power distribution	No	Yes			FTD		B	B
Engine Start	Use of MFD Engine Display and PFD/MFD power distribution.	No	Yes			FTD		B	B
Taxi	Flight Instrument checks.	No	Yes			FTD		B	C
Takeoff	V-speed and Altitude Selection. Airspeed Indication on tape format.	No	Yes			FTD		B	C
RTO Or V1 Fail	Airspeed Indication on tape format. Attitude indications on PFD format. Low Speed Awareness cues.	No	Yes				FFS	B	C
Climb Cruise Decent	PFD format for all flight instruments. Low Speed Awareness cues. Selection and use of Nav Sources Instrument scan skill in PFD format.	No	Yes			FTD		B	C
Instrument Approaches	Nav Source Selection & display format. Instrument scan skill in PFD format.	No	Yes				FFS	C	C
Landing	V-speed and Altitude Selection. Airspeed Indication on tape format	No	Yes			FTD		B	C
Normal Procedures	Nav Source selection, Nav Display format, Autopilot & FD control. IFIS-5000 use procedures. TCAS & TAWS use procedures.	No	Yes				FFS	C	C
Abnormal Procedures	Abnormal procedures for Avionics / Flight Instruments of Proline 21 system	No	Yes			FTD		B	B
Emergency Procedures	Emergency procedures for Dual Generator Failure, AC Inverter Failures, Emergency Power Management, and Standby Flight Instruments	No	Yes			FTD		C	C
In-Flight Maneuvers	Tape format & Low Speed Awareness for Steep Turns and Stalls. Instrument scan skill in PFD format.	No	Yes				FFS	C	C

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300, 300LW, B300, B300C Proline 21									
BASE AIRCRAFT: 300, 300LW, B300, B300C Proline 2 EFIS-85				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
All System Chapters	Chapters not listed on this table are unchanged by this modification.								
22 Auto-Flight	FCP-65 Control, Mode Control Panel and respective annunciation panels in pedestal replaced by FGP-3000 on glare shield and mode annunciation on PFD. AP Mode Annunciation now on PFD.	No	Yes		AI			B	B
23 Communications	CTL-22 VHF Comm controls replaced with RTU-4200 on center instrument panel for primary control and CDU-3000 as secondary control. Audio Panel control moved from upper center instrument panel to outboard instrument panel.	No	Yes		AI			B	B
24 Electrical Power	AC Powered use equipment reduced. Avionics Buss items changed ESIS Standby Power.	No	Yes		AI			B	B
31 Indicating/Record	Install Integrated Avionics Processor System. Several Annunciations now on PFD	No	No	X				A	A
33 Lights	Display Dimming controls changed	No	No	X				A	A
34 Navigation	Flight Instruments ADI, HSI, ALT, AS, VSI, TC "Basic T" replaced with Proline 21 PFD format. DME, RMI & Radio Altimeter integrated into PFD. (2) Attitude Heading Computers AHC-3000, (2) Flux Detector Units FDU-3000 and (2) External Concentrator Units ECU provide Attitude and Heading information to PFD (2) Air Data Computers ADC-85A provide PFD data for AS, ALT & VS. Airspeed data includes Overspeed Alerts and Low Speed Warnings on PFD. Altitude Selector and Alerter control moved to FGP. Altimeter Baro Selection on DCP and configurable for Ft/M & In/hPa. Standby Instruments Add GH-3100 (ESIS) Electronic Standby Instrument System provides ATT, ALT, AS, TS, HDG, Baro-set, NAV 1.	No	Yes			FTD		C	C

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300, 300LW, B300, B300C Proline 21									
BASE AIRCRAFT: 300, 300LW, B300, B300C Proline 2 EFIS-85				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
34 Navigation	EFIS Controls Added (2) DCP-3000 on instrument panel (1) FGP-3000 on glare shield (1) CDU-3000 on center pedestal Flight Display (FD) Bezel Buttons control display configuration. Reversion controls on lower center Inst. Panel CHP-86B Course Heading Panel replaced by Flight Guidance Panel FGP-3000 FGP-3000 includes Flight Director Mode Selection	No	Yes			FTD		C	C
34 Navigation	FMS UNS-1K replaced by FMS-3000 controlled by CDU-3000. CTL-32 Nav Radio tuning replaced with RTU-4200 and CDU-3000 backup tuning.	No	Yes			FTD		C	C
34 Navigation	AFD-3010 MFD display replaces MFD-85. Weather Radar overlay selectable on MFD Radar control on FD Bezel and DCP.	No	Yes		AI			B	B
34 Navigation	TAWS/GPWS display on PFD and MFD with control on FD Bezel and DCP. Remote switch/annunciators on Inst. Panel for FLAP/OVRD, G/S INHIB, TERR INHIB and STEEP APPR.	No	Yes		AI			B	B
34 Navigation	TCAS I with Traffic Display selectable on PFD and MFD with Nav Display overlay. TCAS control on FD Bezel and DCP. TCAS Mode Selections On/Stby & Test/Alt on lower center Inst. Panel. Transponder control on RTU & CDU.	No	Yes			ICBT		B	B
45 Maintenance Computer	MDC-3100 series Maintenance Computer added.	No	No	X				A	A
46 Information Systems	IFIS-5000 File Server Unit (FSU) option FSU provides Charts, Geo-Political and WX Data functions on MFD.	No	Yes			FTD		B	C
53 Fuselage	New Exterior Antenna for Wx Data options.	No	No	X				A	B
61 Propellers	Propeller Syncro-Scope moved to MFD EIS AFX green annunciation on EIS near Trq/ITT instrument.	No	No	X				A	B

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300, 300LW, B300, B300C Proline 21									
BASE AIRCRAFT: 300, 300LW, B300, B300C Proline 2 EFIS-85				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
77 Engine Indicating	Separate Analog Engine Instruments replaced Engine Display. (Normal on MFD, Reversion on PFD) Exceedences are annunciated in Red. Abnormal indications are annunciated in Amber. Primary for power Torque and ITT combined round dial gauge & digital display, Propeller RPM is round dial gauge & digital display: N1 is round dial gauge & digital display. Fuel Flow, Oil Pressure & Oil Temp are digital only. Engine Fire Indication added to Engine Display inside TRQ/ITT indicator. EIS Reversion to PFD if MFD fails	No	Yes			FTD		C	C
80 Engine Starting	Engine Instruments on MFD EIS for start	No	No			FTD		C	C

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

Definitions used in the ODR Tables:	
X	= Flight Manual/Pilot's Operating Handbook and/or FM Supplement
AI	= Aided Instruction
CBT	= Computer Based Training
ICBT	= Interactive Computer Based Training
FTD	= Flight Training Device (Level 1 to 7)
FBS	= Fixed Base Simulator (Level 5 to 7)
FFS	= Full Flight Simulator (Level A, B, C, D)

SAMPLE DIFFERENCES TABLE					COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: BE-300 (FF Serial) With Proline 21 (1 pilot)										
BASE AIRCRAFT: BE-300 (FF Serial) With Bendix/King EFS-10 (2 pilot)					TRAINING				CHKG/CURR	
DESIGN	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR	
General Airplane Configuration	No Change									
Weights	No Change									
Airworthiness Limitations	See Maintenance Manual Supplement	NO	YES	X				B	B	
Placards, Markings and Limitations	See Airplane Flight Manual Supplement Minimum Crew 1 Pilot	NO	NO	X				A	A	
Servicing	See Maintenance Manual Supplement	NO	YES		X			B	B	
Engines	No Change									
Flight Deck	Remove Bendix EFIS Install Collins Pro Line 21	NO	YES				FFS	C	D	
Instrument Panel Layout	Changed to accommodate Pro Line 21 Change from AS, EADI/EHSI, ALT, VSI to PFD/ND, RMI removed Engine Gauges replaced to MFD Replaced Standby ADI with 4 in 1 ESIS	NO	YES				FFS	C	D	
Cabin	Three new avionics racks installed	NO	NO	X				A	A	
Flight Controls	No Change									
Aerodynamic Controls	No Change									

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: BE-300 (FF Serial) With Proline 21 (1 pilot)									
MANEUVER	REMARKS	FLT CHAR	PROC CHNG	TRAINING				CHKG/CURR	
				LVL A	LVL B	LVL C	LVL D	CHK	CURR
Engine Start	Engine Gauges changed to electronic display	NO	NO		X			A	A
Preflight	Avionics Preflight	NO	YES		X			B	B
Taxi	No Change								
Takeoff	PFD replaces separate Basic T inst. Engine Power Instruments changed to electronic display	NO	NO				FFS	C	D
RTO Or V1 Fail	No Change								
Climb Cruise Decent	No Change								
Instrument Approaches	All new PFD/ND, FMS, Autopilot	NO	YES				FFS	C	D
Landing	No Change								
Normal Procedures	See Airplane Flight Manual Supplement	NO	YES			FTD		C	D
Abnormal Procedures	See Airplane Flight Manual Supplement	NO	YES			FTD		C	D
Emergency Procedures	See Airplane Flight Manual Supplement	NO	YES			FTD		C	D
In-Flight Maneuvers	Steep Turns, Slow Flight, Approach to Stall, because affected by PFD display changes	NO	NO				FFS	C	D

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: BE-300 (FF Serial) With Proline 21 (1 pilot)									
BASE AIRCRAFT: BE-300 (FF Serial) With Bendix/King EFS-10 (2 pilot)				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
21 Air Conditioning	No Change								
22 Auto-Flight	Bendix Autopilot with KMC-440 control panel and KMS-446 Mode control replaced by Collins Pro Line 21 with APS-300 Autopilot System & FGP-3000 control panel	YES	YES				FTD	C	D
23 Communications	Collins Pro Line 21 Communication Transceivers are installed (dual VHF-300E, single VHF-300) Replaced Audio Control Panel with New panel mounted ACP(NAT-804/805) Removed Bendix Radios and replace with CDU-3000 radio tuning with CTL-23D for Ground Comm and Standby Tuning	NO	YES			FTD		C	C
24 Electrical Power	Individual Circuits & Circuit Breakers change with new labels and locations, Emergency Power requirements for ESIS	NO	YES		X			B	B
25 Equipment / Furn.	Three New Avionics Racks	NO	NO	X				A	A
26 Fire Protection	Firewall Shutoff and Fire Extinguisher Buttons relocated on glareshield	NO	NO	X				A	A
31 Indicating/Record	Replaced A/P TRIM FAIL and A/P DISC lamp assemblies with Blank lamp assemblies on warning panel. Added RUD BOOST OFF lamp to caution panel	NO	YES			FTD		C	C
33 Lights	Pilot and Copilot dimming control added to the overhead panel for EFIS display system brightness control.	NO	NO	X				A	A
34 Navigation	Install Collins Pro Line 21 (dual FMS-3000, dual NAV-300 for VOR/ILS/ADF/MKR, dual DME-300, dual GPS-300S) & single Laseref V available in reversion modes. (FMS has fixed priority for NAV Data source GPS/GPS/DME/VOR/IRS) MMR and control head added for LAAS Turn Coordinator removed, pointer on PFD provides slip/skid indication Honeywell TCAS II (TPA-81A) replaces TCAS I Additional functions added to EGPWS with Honeywell Mark V, add RAAS Bendix/King TRA-67A Transponders replace Collins TDR-94 and tuning moves to CDU-3000 with Ident on Inst. Panel also WX-1000 added for Lightning Detection with Storm Clear button on reversion panel	NO	YES				FTD	C	D

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				<u>COMPLIANCE METHOD</u>					
DIFFERENCE AIRCRAFT: BE-300 (FF Serial) With Proline 21 (1 pilot)									
BASE AIRCRAFT: BE-300 (FF Serial) With Bendix/King EFS-10 (2 pilot)				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
45 Maintenance Computer	MDC-3110 added for maintenance diagnostics	NO	NO	X				A	A
46 Information Systems	IFIS-5000 System installed with single CCP-3000 and single FSU-5010 XMWR-1000 XM Receiver installed CMU-300 provides VHF Data Link for ACARS and Textual Weather only DBU-5000 Flashdrive Data Loader installed	NO	YES			ICBT		C	B
77 Engine Indicating	Analog Engine Indicators replaced by digital engine indications on Pro Line 21 Multi-Function Display (MFD)	NO	YES			FTD		C	B

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

Definitions used in the ODR Tables:	
X	= Pilot's Operating Handbook and or Flight Manual Supplement
CBT	= Computer Based Training
ICBT	= Interactive Computer Based Training
FTD	= Flight Training Device (Level 1 to 7)
FBS	= Fixed Base Simulator (Level 5 to 7)
CPT	= Cockpit Procedures Trainer
FFS	= Full Flight Simulator (Level A, B, C, D)

DIFFERENCES TABLE					COMPLIANCE METHOD				
DIFFERENCE AIRCRAFT: 300/300LW/B300/B300C with G1000									
BASE AIRCRAFT: 300/300LW/B300/B300C (MDR NOTE (1) equipment only)					TRAINING			CHKG/CURR	
DESIGN	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
General Airplane Configuration	No Change								
Weights	Reduces Basic Operating Weight	NO	NO	X				A	B
Airworthiness Limitations	New aircraft Limitations (See Airplane Flight Manual Supplement)	NO	YES	X				A	A
Placards and Markings	New aircraft Placarding (See Airplane Flight Manual Supplement)	NO	NO	X				A	A
Servicing	AFMS Section 8, new service & handling (ref. G1000/GFC 700 System Maint. Manual)	NO	YES		X			B	B
Engines	No Change								
Flight Deck	Remove Collins EFIS-85B, FCP-65 Mode Control Panel, Mode Control Annun. Panel, AP Control, AP Annun. Panel Install Garmin G1000	NO	YES				FFS	C	D
Instrument Panel Layout	<ul style="list-style-type: none"> • Separate AS, EADI/EHSI, ALT, VSI to dual PFD Format • RMI removed • Engine Gauges replaced to MFD • Replaced standby ADI with mechanical standby AI, altimeter and airspeed ind. • Prop sync switch moved to instrument panel • Standby instrument power switch moved to instrument panel • GMC 710 autopilot controller beneath glareshield in center instrument panel • GMA-1347 audio panels outboard of PFD • GCU-477 MFD control in center pedestal 	NO	YES				FFS	C	D
Cabin	No Change								
Flight Controls	Electric Trim has added speed schedule.	YES	NO		X			A	A
Aerodynamic Controls	Garmin Electronic Stability & Protection (ESP) Garmin Under Speed Protection (USP) and Overspeed Protection Systems added (option)	YES	YES				FFS	D	B

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE					COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300/300LW/B300/B300C with G1000										
BASE AIRCRAFT: 300/300LW/B300/B300C (MDR NOTE (1) equipment only)					TRAINING				<u>CHKG/CURR</u>	
MANEUVER	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR	
Preflight	Avionics Preflight	NO	YES		X			B	B	
Engine Start	Engine Gauges changed to electronic display on the MFD	NO	NO		X			B	B	
Taxi	Taxi and Runup Checklist Procedures - See Airplane Flight Manual Supplement	NO	YES		X			B	B	
Takeoff	PFD replaces separate Basic T inst. Engine Power Instruments moved to MFD. Speed displayed on tape with Low Speed Awareness. Altitude displayed on tape with RAD ALT interface collocated.	NO	NO				FFS	C	D	
RTO Or V1 Fail	No Change									
Climb Cruise Decent	No Change									
In-Flight Maneuvers	Steep Turns, Slow Flight, Approach to Stall affected by PFD display changes for Low Speed Awareness cues. SVS function and use. ESP & USP function and use	NO	NO				FFS	C	D	
Instrument Approaches	All new PFD, MFD, FMS, Autopilot WAAS procedures, LNAV & LPV approaches USP function and use	NO	YES				FFS	C	D	
Landing	PFD Primary Flight Inst. with Vref on speed tape. RAD Alt & Mins on Altitude tape.	NO	YES				FFS	B	B	
Shutdown	No Change									
Normal Procedures	See Airplane Flight Manual Supplement for review of all Normal Procedures	NO	YES			FTD		C	D	
Abnormal Procedures	See Airplane Flight Manual Supplement for new or changed Abnormal Procedures	NO	YES			FTD		C	D	
Emergency Procedures	See Airplane Flight Manual Supplement for new or changed Emergency Procedures	NO	YES			FTD		C	D	

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300/300LW/B300/B300C with G1000									
BASE AIRCRAFT: 300/300LW/B300/B300C (MDR NOTE (1) equipment only)				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
21 Air Conditioning	No Change								
22 Auto-Flight	Collins APS-65 autopilot & FCP-65 mode control replaced by Garmin GFC 700 autopilot with GMC 710 mode control. Alt. Alerter integrated on PFD using DCU. Remote Mode Annun. Panel removed for GFC-700 Mode Annun. now integrated on PFD. RED Autopilot Disconnect on yoke now single stage switch for Trim, YD, RB, AP Rudder Boost using AP servo for Vmcg per Exemption 5599 (B300, B300C only)	YES	YES			FTD		C	C
22 Auto-Flight	Garmin ESP System software, default to ON Garmin USP System software AP coupled Go-Around only with ESP installed	YES	YES				FFS	C	D
23 Communications	Dual Garmin GIA 63W Communication Transceivers are installed. Replaced Audio Control Panel with dual Garmin GMA 1347 audio panels outboard of each PFD. Emer. Freq. push button add on Center Pedestal	NO	YES		X			B	B
24 Electrical Power	Individual Circuits & Circuit Breakers change with new EL Panel labels and locations. (No circuit breaker source color code provide) Power Distribution for new systems (AFMS Sec.7) Standby battery powered items changed AC Inverters and associated switches removed by G1000 installation	NO	YES		X			B	B
25 Equipment / Furn.	Several New Avionics Racks behind instrument panel and in forward avionics bay	NO	NO	X				A	A
26 Fire Protection	No Change								
27 Flight Controls	Electric Trim Circuit Breaker Switch removed. Trim interrupt (Yoke Trim Button) new function Electric Pitch Trim speed schedule added.	YES	YES		X			B	A
28 Fuel	No Change								
29 Hydraulic	No Change								
30 Ice / Rain	No Change								

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300/300LW/B300/B300C with G1000									
BASE AIRCRAFT: 300/300LW/B300/B300C (MDR NOTE (1) equipment only)				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
31 Indicating/Record	Replaced A/P TRIM FAIL, INVERTER, AP DISC, AP TRIM FAIL and ELEC TRIM OFF lamp assemblies with blank annunciators Removed Autofeather (AFX) annunciators and relocated to MFD. Remove AFX indicators for B300/B300C models only Add Rudder Boost Off Ann. for Model 300	NO	YES		X			B	B
32 Landing Gear	No Change								
33 Lights	Pilot and Copilot dimming control added to the overhead panel for EFIS display system brightness control.	NO	NO	X				A	A
34 Navigation	Install dual Garmin GIA 63W GPS/VHF Navigation receivers Turn Coordinator removed, pointer on PFD provides slip/skid indication GRS-77 AHRS source for Attitude data GDC-7400 ADC for Air Data. Collins TDR-94 tuning & Ident moves to PFDs. Added Standby AS & Alt. on RH Pitot System Overspeed Test removed(if installed), now part of GIA built-in-test. GWX-68 WX radar installed GCU-477 controls Nav Display on MFD. GTS-TAS/TCAS or TCAS II system. GDU contains TAWS A or B	NO	YES			FTD		B	B
34 Navigation	SVS selectable on PFD Display & transition. Formats differ for attitude scale, Reference Zero vs. Zero Pitch Line depiction and Flight Path Marker.	NO	YES				FFS	C	C
35 Oxygen	No Change								
36 Pneumatics	No Change								
37 Vacuum	No Change								
38 Waste / Water	No Change								
45 Maintenance Computer	No Change								

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

SAMPLE DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: 300/300LW/B300/B300C with G1000									
BASE AIRCRAFT: 300/300LW/B300/B300C (MDR NOTE (1) equipment only)				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
46 Information Systems	Optional datalink equipment available that provides XM data (GDL-59) or (GFDS)Garmin Flight Data Service International service (GDL-69). Also provided are the abilities to send and receive telephone calls and SMS text messaging	NO	YES	X				A	A
46 Information Systems	EFB , Electronic Charts, Airport Diagrams Selectable display format using GDU-1500. SAFETAXI not AMMD AC20-159 compliant.	NO	YES			FTD		B	B
49 APU	No Change								
52 Doors	No Change								
53 Fuselage	Added (2) GPS antennae	NO	NO	X				A	A
54 Nacelles/Pylons	No Change								
55 Horizontal & Vertical Stab.	No Change								
61 Propellers	Prop Syncroscope on MFD engine display. G1000 STC includes 4-Blade propeller airplanes only	NO	NO	X				A	A
72 Engine (turbine)	No Change								
73 Fuel Controls	No Change								
74 Engine Ignitions	No Change								
75 Engine Bleed Air	No Change								
76 Engine Controls	No Change								
77 Engine Indicating	Analog Engine Indicators replaced by engine indications on G1000 MFD AFX Indicators on MFD engine display	NO	YES			FTD		C	B
78 Exhaust	No Change								
79 Engine Oil	No Change								
80 Engine Starting	Analog Engine Indicators replaced by digital engine indications on G1000 Multi-Function Display (MFD) – ITT gauge changes scale during start sequence	NO	YES			FTD		C	B

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

Definitions used in the ODR Tables:	
X	= Flight Manual/Pilot's Operating Handbook and/or FM Supplement
AI	= Aided Instruction
CBT	= Computer Based Training
ICBT	= Interactive Computer Based Training
FTD	= Flight Training Device (Level 1 to 7)
FBS	= Fixed Base Simulator (Level 5 to 7)
FFS	= Full Flight Simulator (Level A, B, C, D)

DIFFERENCES TABLE					COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: B300 / B300C with G1000										
BASE AIRCRAFT: B300 / B300C with Proline 21					TRAINING				CHKG/CURR	
DESIGN	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR	
General Airplane Configuration	No Change									
Weights	Reduced Basic Operating Weight	NO	NO	X				A	B	
Limitations	New aircraft Limitations (See Airplane Flight Manual Supplement)	NO	YES	X				A	A	
Placards and Markings	New aircraft Placarding (See Airplane Flight Manual Supplement)	NO	NO	X				A	A	
Servicing	AFMS Section 8, new service & handling (ref. G1000/GFC 700 System Maint. Manual)	NO	YES		X			B	B	
Engines	No Change									
Flight Deck	Replace Collins ProLine 21 with G1000 Collins CDU & CCD replaced with GDU-477	NO	YES			FTD		C	C	
Instrument Panel Layout	<ul style="list-style-type: none"> • Collins dual PFD and single MFD changed to G1000 dual PFD single MFD. • Collins Flight Guidance Panel removed and replaced with GMC 710 controller • Removed Display Control Panels • Replaced standby ESIS with mechanical standby AI, Altimeter and Airspeed • Standby instrument power switch moved to instrument panel • Replaced audio panels outboard of PFD • Removed source select panel on lower instrument panel. 	NO	YES			FTD		C	C	
Cabin	No Change									
Flight Controls	Electric Trim has added speed schedule.	YES	NO		X			A	A	
Aerodynamic Controls	Garmin Electronic Stability & Protection (ESP) Garmin Under Speed Protection (USP) and Overspeed Protection Systems added (option)	YES	YES				FFS	D	C	

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: B300 / B300C with G1000									
BASE AIRCRAFT: B300 / B300C with Proline 21				TRAINING				CHKG/CURR	
MANEUVER	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
Preflight	Avionics Preflight	NO	YES		X			B	B
Engine Start	Engine Gauges electronically displayed on the MFD. Format differs from ProLine 21.	NO	NO		X			B	B
Taxi	Taxi and Runup Checklist Procedures - See Airplane Flight Manual Supplement	NO	YES		X			B	B
Takeoff	Garmin PFD differs from Collins PFD format Garmin Speed Awareness cues.	NO	NO			FTD		B	C
RTO Or V1 Fail	No Change								
Climb Cruise Decent	No Change								
In-Flight Maneuvers	SVS function and use. ESP & USP function and use	NO	NO				FFS	C	D
Instrument Approaches	New PFD, MFD, FMS, Autopilot WAAS procedures, LNAV & LPV approaches	NO	YES			FTD		C	D
Landing	PFD Primary Flight Inst. with Vref on speed tape. RAD Alt & Mins on Altitude tape.	NO	NO		X			B	B
Shutdown	No Change								
Normal Procedures	See Airplane Flight Manual Supplement for review of all Normal Procedures	NO	YES			FTD		C	C
Abnormal Procedures	See Airplane Flight Manual Supplement for new or changed Abnormal Procedures	NO	YES			FTD		C	C
Emergency Procedures	See Airplane Flight Manual Supplement for new or changed Emergency Procedures	NO	YES			FTD		C	C

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: B300 / B300C with G1000									
BASE AIRCRAFT: B300 / B300C with Proline 21				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
21 Air Conditioning	No Change								
22 Auto-Flight	Collins autopilot replaced by Garmin GFC 700 autopilot with GMC 710 mode controller. RED Autopilot Disconnect on yoke now single stage switch for Trim, YD, RB, AP Rudder Boost using AP servo for Vmcg per Exemption 5599	YES	YES			FTD		C	C
22 Auto-Flight	Garmin ESP System software, default to ON Garmin USP System software AP coupled Go-Around only with ESP installed	YES	YES				FFS	C	D
23 Communications	Dual Garmin GIA 63W Communication Transceivers are installed Replaced Audio Control Panels with dual Garmin GMA 1347 audio panels outboard of each PFD. Emer. Freq. push button add on Center Pedestal RTU removed, GCU-477 provides function	NO	YES		X			B	B
24 Electrical Power	Individual Circuits & Circuit Breakers change with new labels and locations. (No circuit breaker source color code provide) Power Distribution for new systems (AFMS Sec.7) Standby battery powered items changed	NO	YES		X			B	B
25 Equipment / Furn.	Several New Avionics Racks behind instrument panel and in forward avionics bay	NO	NO	X				A	A
26 Fire Protection	No Change								
27 Flight Controls	Electric Pitch Trim speed schedule added	YES	NO		X			B	A
28 Fuel	No Change								
29 Hydraulic	No Change								
30 Ice / Rain	No Change								
31 Indicating/Record	Autofeather (AFX) annunciators removed.	NO	NO		X			B	A
32 Landing Gear	No Change								

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

DIFFERENCES TABLE				COMPLIANCE METHOD					
DIFFERENCE AIRCRAFT: B300 / B300C with G1000									
BASE AIRCRAFT: B300 / B300C with Proline 21				TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR
33 Lights	Pilot and Copilot dimming control added to the overhead panel for EFIS display system brightness control.	NO	NO	X				A	A
34 Navigation	Install dual Garmin GIA 63W GPS/VHF Navigation receivers GRS-77 AHRS source for Attitude data GDC-7400 ADC for Air Data. Transponder tuning & Ident moves to PFDs. GWX-68 WX radar installed GCU-477 controls Nav Display on MFD. GTS-TAS/TCAS or TCAS II system. GDU contains TAWS A or B ADF not integrated, ADF-60 on center pedestal. ESIS replaced with mechanical standby AI, Altimeter and Airspeed Indicator.	NO	YES			FTD		B	B
34 Navigation	SVS selectable on PFD Display & transition time. Formats differ for attitude scale, Reference Zero vs. Zero Pitch Line depiction and Flight Path Marker.	NO	YES				FFS	C	C
35 Oxygen	No Change								
36 Pneumatics	No Change								
37 Vacuum	No Change								
38 Waste / Water	No Change								
45 Maintenance Computer	No Change								
46 Information Systems	Optional datalink equipment available that provides XM data (GDL-59) or (GFDS)Garmin Flight Data Service International service (GDL-69). Also provided are the abilities to send and receive telephone calls and SMS text messaging	NO	YES	X				A	A
46 Information Systems	EFB , Electronic Charts, Airport Diagrams Selectable display format using GDU-1500 MFD. SAFETAXI not AMMD AC20-159 compliant.	NO	YES			FTD		B	B
49 APU	No Change								
52 Doors	No Change								
53 Fuselage	Added (2) GPS antennae	NO	NO	X				A	A

Hawker Beechcraft Corporation, Model 300
Flight Standardization Board Report

DIFFERENCES TABLE					<u>COMPLIANCE METHOD</u>					
DIFFERENCE AIRCRAFT: B300 / B300C with G1000										
BASE AIRCRAFT: B300 / B300C with Proline 21					TRAINING				CHKG/CURR	
SYSTEM	REMARKS	FLT CHAR	PROC CHNG	LVL A	LVL B	LVL C	LVL D	CHK	CURR	
54 Nacelles/Pylons	No Change									
55 Horizontal & Vertical Stab.	No Change									
56 Windows	No Change									
57 Wings	No Change									
61 Propellers	G1000 STC includes 4-Blade propeller airplanes only	NO	NO	X				A	A	
71 Powerplant	No Change									
72 Engine (turbine)	No Change									
73 Fuel Controls	No Change									
74 Engine Ignitions	No Change									
75 Engine Bleed Air	No Change									
76 Engine Controls	No Change									
77 Engine Indicating	Engine Indicators displayed on G1000 Multi-Function Display (MFD) in different format	NO	NO		X			B	B	
78 Exhaust	No Change									
79 Engine Oil	No Change									
80 Engine Starting	Engine indications on G1000 ITT gauge changes scale during start sequence	NO	NO		X			B	B	

APPENDIX 3 - AIRCRAFT SAMPLE TRAINING PROGRAM

RESERVED

**APPENDIX 4 - AIRCRAFT REGULATORY COMPLIANCE
CHECKLIST**

RESERVED