

Ce406r4b.txt

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION
WASHINGTON, D. C.

Revision: 4 b
Date: 06/30/97

M A S T E R M I N I M U M E Q U I P M E N T L I S T

CESSNA MODELS 406 AND F406

FEDERAL AVIATION ADMINISTRATION
AIRCRAFT EVALUATION GROUP
1201 WALNUT ST, SUITE 900
KANSAS CITY, MO 64106

TELEPHONE: (816) 426-3946
FAX: (816) 426-3084

FEDERAL AVIATION ADMINISTRATION
MASTER MINIMUM EQUIPMENT LIST
CESSNA MODELS 406 AND F406

Page: 1
Revision: 4 b
Date: 06/30/97

Ce406r4b.txt
Table of Contents

SYSTEM NO.	SYSTEM	PAGE
--	Table of Contents	I
--	Log of Revisions	II
--	Control Page	III
--	Highlights of Change	IV
--	Definitions	V, VI, VII, VIII
--	Definitions	IX, X, XI, XII
--	Preamble	XIII, XIV
--	Guidelines for (O) & (M) Procedures	XV, XVI
21	Air Conditioning	21-1, 2
22	Auto Flight	22-1
23	Communications	23-1, 2, 3
25	Equipment/Furnishings	25-1, 2
26	Fire Protection	26-1
27	Flight Controls	27-1
28	Fuel	28-1
29	Hydraulic Power	29-1
30	Ice and Rain Protection	30-1
31	Indicating/Recording Systems	31-1
33	Lights	33-1, 2
34	Navigation	34-1, 2, 3, 4
35	Oxygen	35-1
61	Propellers	61-1
71	Powerplant	71-1

FEDERAL AVIATION ADMINISTRATION Page: II
MASTER MINIMUM EQUIPMENT LIST Revision: 4 b
Date: 06/30/97
CESSNA MODELS 406 AND F406

Log of Revisions

REV. NO.	DATE	PAGE NUMBERS	INITIALS
ORIGINAL	12/03/86	N/A	
1	06/05/87	ADDS MODEL F406	
2	05/05/89	ALL PAGES	
3	06/22/89	HIGHLIGHTS OF REV., DEFINITIONS	
3	06/22/89	PREAMBLE	
4	09/10/90	HIGHLIGHTS OF REV., DEFINITIONS	
4	09/10/90	GUIDELINES	
4	09/10/90	21-1, 21-2, 22-1, 23-1, 25-1	
4	09/10/90	26-1, 28-1, 30-1, 31-1, 33-1	
4	09/10/90	33-2, 34-1, 61-1	
4a	08/13/92	HIGHLIGHTS OF REV.	
4a	08/13/92	21-1, 21-2, 23-1, 23-2, 25-1	
4a	08/13/92	31-1, 33-1, 33-2, 34-1, 34-2	
4a	08/13/92	34-3	
4b	06/30/97	HIGHLIGHTS OF REV., DEFINITIONS	
4b	06/30/97	GUIDELINES	
4b	06/30/97	21-1, 21-2, 22-1, 23-1, 23-2	
4b	06/30/97	23-3, 25-1, 25-2, 26-1, 27-1	

		Ce406r4b.txt	
4b	06/30/97	28-1, 29-1, 30-1, 31-1, 33-1	
4b	06/30/97	33-2, 34-1, 34-2, 34-3, 34-4	
4b	06/30/97	35-1, 61-1, 71-1	

FEDERAL AVIATION ADMINISTRATION
MASTER MINIMUM EQUIPMENT LIST
CESSNA MODELS 406 AND F406

Page: III
Revision: 4 b
Date: 06/30/97

Control Page

SYSTEM	PAGE	REV NO.	CURRENT DATE
Cover Page	-	4 b	06/30/97
Table of Contents	I	4 b	06/30/97
Log of Revisions	II	4 b	06/30/97
Control Page	III	4 b	06/30/97
Highlights of Change	IV	4 b	06/30/97
Definitions	V	6	01/31/95
	VI	6	01/31/95
	VII	6	01/31/95
	VIII	6	01/31/95
	IX	6	01/31/95
	X	6	01/31/95
	XI	6	01/31/95
	XII	6	01/31/95
Preamble	XIII	2	06/14/89
	XIV	2	06/14/89
Guidelines for (O) & (M) Procedures	XV	4 b	06/30/97
	XVI	4 b	06/30/97
21	21-1	4 b	06/30/97
	21-2	4 b	06/30/97
22	22-1	4 b	06/30/97

	Ce406r4b. txt			
23		23-1	4 b	06/30/97
		23-2	4 b	06/30/97
		23-3	4 b	06/30/97
25		25-1	4 b	06/30/97
		25-2	4 b	06/30/97
26		26-1	4 b	06/30/97
27		27-1	4 b	06/30/97
28		28-1	4 b	06/30/97
29		29-1	4 b	06/30/97
30		30-1	4 b	06/30/97
31		31-1	4 b	06/30/97
33		33-1	4 b	06/30/97
		33-2	4 b	06/30/97
34		34-1	4 b	06/30/97
		34-2	4 b	06/30/97
		34-3	4 b	06/30/97
		34-4	4 b	06/30/97
35		35-1	4 b	06/30/97
61		61-1	4 b	06/30/97
71		71-1	4 b	06/30/97

FEDERAL AVIATION ADMINISTRATION Page: IV
 MASTER MINIMUM EQUIPMENT LIST Revision: 4 b
 Date: 06/30/97
 CESSNA MODELS 406 AND F406

Highlights of Change

All asterisks in column 4 were removed in accordance with Policy Letter 61 designated as Global Change 8. See Definitions Section for placarding requirements.

- 23-4 Proviso was rewritten in accordance with Policy Letter 9 designated as Global Change 13.
- 23-7 Added relief for Boom Microphones in accordance with Policy Letter 58 designated as Global Change 14.
- 25-3 Reinstated relief for Approved Floatation Equipment.
- 25-5 Added relief for First Aid Kits in accordance with Policy Letter 73 designated as Global Change 17.
- 25-7 Added relief for Emergency Medical Equipment (EMS).
- 26-1 Reinstated relief for Portable Fire Extinguishers in accordance with Policy Letter 75 designated as Global Change 19.
- 31-1 Proviso was rewritten in accordance with Policy Letter 87 designated as Global Change 35.
- 34-5 Proviso was rewritten in accordance with Policy Letter 76 designated as Global Change 20.
- 34-15 Added relief for Traffic Alert Collision Avoidance System (TCAS I) in accordance with Policy Letter 80 designated as Global Change 30.

34-17 Added relief for Ground Proximity Warning System in accordance with Policy Letter 54 designated as Global Change 10.

FEDERAL AVIATION ADMINISTRATION

Page: V

MASTER MINIMUM EQUIPMENT LIST

Revision: 6

Date: 01/31/95

CESSNA MODELS 406 AND F406

Definitions

1. System Definitions.

System numbers are based on the Air Transport Association (ATA) Specification Number 100 and items are numbered sequentially.

- a. "Item" (Column 1) means the equipment, system, component, or function listed in the "Item" column.
- b. "Number Installed" (Column 2) is the number (quantity) of items normally installed in the aircraft. This number represents the aircraft configuration considered in developing this MMEL. Should the number be a variable (e.g., passenger cabin items) a number is not required.
- c. "Number Required for Dispatch" (Column 3) is the minimum number (quantity) of items required for operation provided the conditions specified in Column 4 are met.

NOTE: Where the MMEL shows a variable number required for dispatch, the MEL must reflect the actual number required for dispatch or an alternate means of configuration control approved by the Administrator.

- d. "Remarks or Exceptions" (Column 4) in this column includes a statement either prohibiting or permitting operation with a specific number of items inoperative, provisos (conditions and limitations) for such operation, and appropriate notes.
- e. A vertical bar (change bar) in the margin indicates a change, addition or deletion in the adjacent text for the current revision of that page only. The change bar is dropped at the next revision of that page.

2. "Airplane/Rotorcraft Flight Manual" (AFM/RFM) is the document required for type certification and approved by the responsible FAA Aircraft Certification Office. The FAA approved AFM/RFM for the specific aircraft is listed on the applicable Type

FEDERAL AVIATION ADMINISTRATION

Page: VI

MASTER MINIMUM EQUIPMENT LIST

Revision: 6

Date: 01/31/95

CESSNA MODELS 406 AND F406

Definitions

Certificate Data Sheet.

3. "As required by FAR" means that the listed item is subject to certain provisions (restrictive or permissive) expressed in the Federal Aviation Regulations operating rules. The number of items required by the FAR must be operative. When the listed item is not required by FAR it may be inoperative for time specified by repair category.

4. Each inoperative item must be placarded to inform and remind the crewmembers and maintenance personnel of the equipment condition.

NOTE: To the extent practical, placards should be located adjacent to the control or indicator for the item affected; however, unless otherwise specified, placard wording and location will be determined by the operator.

5. "-" symbol in Column 2 and/or Column 3 indicates a variable number (quantity) of the item installed.

6. "Deleted" in the remarks column after a sequence item indicates that the item was previously listed but is now required to be operative if installed in the aircraft.

7. "ER" refers to extended range operations of a two-engine airplane which has a type design approval for ER operations and complies with the provisions of Advisory Circular 120-42A.

8. "Federal Aviation Regulations" (FAR) means the applicable portions of the Federal Aviation Act and Federal Aviation Regulations.

9. "Flight Day" means a 24 hour period (from midnight to midnight) either Universal Coordinated Time (UCT) or local time, as established by the operator, during which at least one flight is initiated for the affected aircraft.

10. "Icing Conditions" means an atmospheric environment that may cause ice to form on the aircraft or in the engine(s).

11. Alphabetical symbol in Column 4 indicates a proviso (condition or limitation) that must be complied with for

Definitions

operation with the listed item inoperative.

12. "Inoperative" means a system and/or component malfunction to the extent that it does not accomplish its intended purpose and/or is not consistently functioning normally within its approved operating limit(s) or tolerance(s).

13. "Notes:" in Column 4 provides additional information for crewmember or maintenance consideration. Notes are used to identify applicable material which is intended to assist with compliance, but do not relieve the operator of the responsibility for compliance with all applicable requirements. Notes are not a part of the provisions.

14. Inoperative components of an inoperative system: Inoperative items which are components of a system which is inoperative are usually considered components directly associated with and having no other function than to support that system. (Warning/caution systems associated with the inoperative system must be operative unless relief is specifically authorized per the MMEL).

15. "(M)" symbol indicates a requirement for a specific maintenance procedure which must be accomplished prior to operation with the listed item inoperative. Normally these procedures are accomplished by maintenance personnel; however, other personnel may be qualified and authorized to perform certain functions. Procedures requiring specialized knowledge or skill, or requiring the use of tools or test equipment should be accomplished by maintenance personnel. The satisfactory accomplishment of all maintenance procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are required to be published as part of the operator's manual or MEL.

16. "(O)" symbol indicates a requirement for a specific operations procedure which must be accomplished in planning for and/or operating with the listed item inoperative. Normally these procedures are accomplished by the flight crew; however, other personnel may be qualified and authorized to perform certain functions. The satisfactory accomplishment of all procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are

Defi ni ti ons

required to be published as a part of the operator's manual or MEL.

NOTE: The (M) and (O) symbols are required in the operator's MEL unless otherwise authorized by the Administrator.

17. "Deactivated" and "Secured" means that the specified component must be put into an acceptable condition for safe flight. An acceptable method of securing or deactivating will be established by the operator.

18. "Visual Flight Rules" (VFR) is as defined in FAR Part 91. This precludes a pilot from filing an Instrument Flight Rules (IFR) flight plan.

19. "Visual Meteorological Conditions" (VMC) means the atmospheric environment is such that would allow a flight to proceed under the visual flight rules applicable to the flight. This does not preclude operating under Instrument Flight Rules.

20. "Visible Moisture" means an atmospheric environment containing water in any form that can be seen in natural or artificial light; for example, clouds, fog, rain, sleet, hail, or snow.

21. "Passenger Convenience Items" means those items related to passenger convenience, comfort or entertainment such as, but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps, etc.

22. Repair Intervals: All users of an MEL approved under FAR 121, 125, 129 and 135 must effect repairs of inoperative systems or components, deferred in accordance with the MEL, at or prior to the repair times established by the following letter designators:

Category A. Items in this category shall be repaired within the time interval specified in the remarks column of the operator's approved MEL.

Category B. Items in this category shall be repaired within three (3) consecutive calendar days (72 hours), excluding the day the malfunction was recorded in the aircraft maintenance

FEDERAL AVIATION ADMINISTRATION

Page: IX

MASTER MINIMUM EQUIPMENT LIST

Revision: 6

Date: 01/31/95

CESSNA MODELS 406 AND F406

Defi ni ti ons

record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the three day interval would begin at midnight the 26th and end at midnight the 29th.

Category C. Items in this category shall be repaired within ten (10) consecutive calendar days (240 hours), excluding the day the malfunction was recorded in the aircraft maintenance record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the 10 day interval would begin at midnight the 26th and end at midnight February 5th.

Category D. Items in this category shall be repaired within one hundred and twenty (120) consecutive calendar days (2880 hours), excluding the day the malfunction was recorded in the aircraft maintenance log and/or record.

The letter designators are inserted adjacent to Column 2.

23. Electronic fault alerting system - General

New generation aircraft display system fault indications to the flight crew by use of computerized display systems. Each aircraft manufacturer has incorporated individual design philosophies in determining the data that would be represented. The following are customized definitions (specific to each manufacturer) to help determine the level of messages affecting the aircraft's dispatch status. When preparing the MEL document, operators are to select the proper Definition No. 23 for their aircraft, if appropriate.

a. BOEING (B-757/767, B-747-400, B-777)

Boeing airplanes equipped with Engine Indicating and Crew Alerting Systems (EICAS), provide different priority levels of system messages (WARNING, CAUTION, ADVISORY, STATUS and MAINTENANCE). Any messages that affects airplane dispatch status will be displayed at a STATUS message level or higher. The absence of an EICAS STATUS or higher level (WARNING, CAUTION, ADVISORY) indicates that the system/component is operating within its approved operating limits or tolerances.

System conditions that result only in a maintenance level message, i.e. no correlation with a higher level EICAS message,

FEDERAL AVIATION ADMINISTRATION

Page: X

MASTER MINIMUM EQUIPMENT LIST

Revision: 6

Date: 01/31/95

CESSNA MODELS 406 AND F406

Definitions

do not affect dispatch and do not require action other than as addressed within an operators standard maintenance program.

b. DOUGLAS (MD-11)

Some Douglas aircraft are equipped with an alerting function which is a subsystem within the Electronic Instrument System (EIS). The alerting function provides various levels of system condition alerts (WARNING, CAUTION, ADVISORY, MAINTENANCE and STATUS).

Alerts that affect aircraft dispatch will include WARNING, CAUTION, STATUS or MAINTENANCE level. MAINTENANCE alerts are displayed on the status page of the EIS display panel under the maintenance heading.

A MAINTENANCE alert on the EIS indicates the presence of a system fault which can be identified by the Central Fault Display System (CFDS) interrogation. The systems are designed to be fault tolerant, however, for any MAINTENANCE alert, the MEL must be verified for dispatch purposes.

c. AIRBUS (A-300-600, A-310, A-320/319/321, A-330, A-340

Airbus aircraft equipped with Electronic Centralized Aircraft Monitoring (ECAM) provide different levels of system condition messages (WARNING, CAUTION, STATUS, and ADVISORY). A-320/319/321, A-330, and A-340 also provide MAINTENANCE status messages.

Any message that effects airplane dispatchability will normally be at the WARNING, CAUTION or STATUS level. MAINTENANCE messages (A-320/319/321, A-330, and A-340 only) are also indicated on ECAM Status Page below the white Maintenance label.

A MAINTENANCE status (Class II) message on ECAM indicates the presence of a system fault which can be identified by CFDS (A-320/319/321) or CMS (A-330/A-340) interrogation. The systems are designed to be fault tolerant, however for any MAINTENANCE status (Class II) message, the A-320/319/321 MEL must be verified for dispatch capability. For the A-330 and A-340, MAINTENANCE status messages do not affect dispatch.

d. FOKKER (FK-100)

FEDERAL AVIATION ADMINISTRATION

Page: XI

MASTER MINIMUM EQUIPMENT LIST

Revision: 6

Date: 01/31/95

CESSNA MODELS 406 AND F406

Definitions

Fokker aircraft are equipped with Multi Function Display System (MFDS) which provides electronic message referring to the different priority levels of system information (WARNING (red), CAUTION (amber), AWARENESS (cyan) AND STATUS (white)). Any messages that affects aircraft dispatch will be at the WARNING, CAUTION or AWARENESS level. In these cases the MEL must be verified for dispatch capability and maintenance may be required.

System conditions that only require maintenance are not presented on the flight deck. These maintenance indications/messages may be presented on the Maintenance & Test Panel (MAP) or the Centralized Fault Display Unit (CFDU) and by dedicated Built In Test Evaluation (BITE) of systems.

24. "Administrative control item" means an item listed by the

Ce406r4b.txt

operator in the MEL for tracking and informational purposes. It may be added to an operator's MEL by approval of the Principal Operations Inspector provided no relief is granted, or provided conditions and limitations are contained in an approved document (i.e. Structural Repair Manual, airworthiness directive, etc.). If relief other than that granted by an approved document is sought for an administrative control item, a request must be submitted to the Administrator. If the request results in review and approval by the FOEB, the item becomes an MMEL item rather than an administrative control item.

25. "****" symbol in Column 1 indicates an item which is not required by regulation but which may have been installed on some models of aircraft covered by this MMEL. This item may be included on the operator's MEL after the approving office has determined that the item has been installed on one or more of the operator's aircraft. The symbol, however, shall not be carried forward into the operator's MEL. It should be noted that neither this policy nor the use of this symbol provide authority to install or remove an item from an aircraft.

26. "Excess Items" means those items that have been installed that are redundant to the requirements of the FARs.

27. "Day of Discovery" is the calendar day an equipment/instrument malfunction was recorded in the aircraft

FEDERAL AVIATION ADMINISTRATION

Page: XII

MASTER MINIMUM EQUIPMENT LIST

Revision: 6

Date: 01/31/95

CESSNA MODELS 406 AND F406

Definitions

maintenance log and or record. This day is excluded from the calendar days or flight days specified in the MMEL for the repair of an inoperative item of equipment. This provision is applicable to all MMEL items, i.e., categories "A, B, C, and D."

FEDERAL AVIATION ADMINISTRATION Page: XIII
MASTER MINIMUM EQUIPMENT LIST Revision: 2
Date: 06/14/89
CESSNA MODELS 406 AND F406

Preamble
(Effective 6/14/89)

The following is applicable for authorized certificate holders operating under Federal Aviation Regulations (FAR) Parts 121, 125, 129, 135: The FAR require that all equipment installed on an aircraft in compliance with the Airworthiness Standards and the Operating Rules must be operative. However, the Rules also permit the publication of a Minimum Equipment List (MEL) where compliance with certain equipment requirements is not necessary in the interests of safety under all operating conditions. Experience has shown that with the various levels of redundancy designed into aircraft, operation of every system or installed component may not be necessary when the remaining operative equipment can provide an acceptable level of safety. A Master Minimum Equipment List (MMEL) is developed by the FAA, with participation by the aviation industry, to improve aircraft utilization and thereby provide more convenient and economic air transportation for the public. The FAA approved MMEL includes those items of equipment related to airworthiness and operating regulations and other items of equipment which the Administrator finds may be inoperative and yet maintain an acceptable level of safety by appropriate conditions and limitations; it does not contain obviously required items such as wings, flaps, and rudders. The MMEL is the basis for development of individual operator MELs which take into consideration the operator's particular aircraft equipment configuration and operational conditions. Operator MELs, for administrative control, may include items not contained in the MMEL; however, relief for administrative control items must be approved by the Administrator. An operator's MEL may differ in format from the MMEL, but cannot be less restrictive than the MMEL. The individual operator's MEL, when approved and authorized, permits operation of the aircraft with inoperative equipment.

Equipment not required by the operation being conducted and equipment in excess of FAR requirements are included in the MEL with appropriate conditions and limitations. The MEL must not deviate from the Aircraft Flight Manual Limitations, Emergency Procedures or with Airworthiness

Directives. It is important to remember that all equipment related to the airworthiness and the operating regulations of the aircraft not listed on the MMEL must be operative.

FEDERAL AVIATION ADMINISTRATION Page: XIV
MASTER MINIMUM EQUIPMENT LIST Revision: 2
Date: 06/14/89
CESSNA MODELS 406 AND F406

Preamble
(Effective 6/14/89)

Suitable conditions and limitations in the form of placards, maintenance procedures, crew operating procedures and other restrictions as necessary are specified in the MEL to ensure that an acceptable level of safety is maintained.

The MEL is intended to permit operation with inoperative items of equipment for a period of time until repairs can be accomplished. It is important that repairs be accomplished at the earliest opportunity. In order to maintain an acceptable level of safety and reliability the MMEL establishes limitations on the duration of and conditions for operation with inoperative equipment. The MEL provides for release of the aircraft for flight with inoperative equipment. When an item of equipment is discovered to be inoperative, it is reported by making an entry in the Aircraft Maintenance Record/Logbook as prescribed by FAR. The item is then either repaired or may be deferred per the MEL or other approved means acceptable to the Administrator prior to further operation. MEL conditions and limitations, do not relieve the operator from determining that the aircraft is in condition for safe operation with items of equipment inoperative.

When these requirements are met, an Airworthiness Release, Aircraft Maintenance Record/Logbook entry, or other approved documentation is issued as prescribed by FAR. Such documentation is required prior to operation with any item of equipment inoperative.

Operators are responsible for exercising the necessary operational control to ensure that an acceptable level of safety is maintained. When operating with multiple inoperative items, the interrelationships between those items and the effect on aircraft operation and crew workload will be considered.

Operators are to establish a controlled and sound repair program including the parts, personnel, facilities, procedures, and schedules to ensure timely repair.

WHEN USING THE MEL, COMPLIANCE WITH THE STATED INTENT OF THE PREAMBLE, DEFINITIONS, AND THE CONDITIONS AND LIMITATIONS SPECIFIED IN THE MEL IS REQUIRED.

Guidelines for (O) & (M) Procedures

The FOEB has identified a need for certain procedures to provide an adequate level of safety while providing relief for the following items. These procedures must be established by the operator. The following guidelines are to help establish these required procedures:

- 21-1 (M) Maintenance procedure to ensure shutoff valves are closed.
- 21-2 (M) Maintenance procedure to ensure shutoff valves are closed.
- 21-3 (M) Maintenance procedure to ensure shutoff valves are closed.
- 21-4 (M) Maintenance procedure to ensure shutoff valves are closed.
- 22-1 (M) Maintenance procedure to ensure no electrical or mechanical fault exists that will have an adverse effect on any flight control.
- 22-2 (M) Maintenance procedure to ensure no electrical or mechanical fault exists that will have an adverse effect on any flight control function.
- 23-4 (O) Operations procedure to ensure passengers are briefed.
- 27-1 (M) Maintenance procedure to ensure failure of electric trim will not interfere with operation of manual trim.
- 28-3 (O) Operations procedure to determine fuel quantity on board.
- 29-1 (M) Maintenance procedure to ensure hydraulic pump failure will not adversely affect engine operation or cause contamination or failure of the hydraulic system.
- 31-2 (O) Operations procedure to record elapsed flight time.
- 33-7 (O) Operations procedure to ensure passengers are appropriately briefed.

Guidelines for (O) & (M) Procedures

- 34-15 (M)Maintenance procedure to deactivate and secure the system.
- 34-16-1 (M)Maintenance procedure to deactivate and secure the system.
- 34-16-2 (O)Operations procedure to ensure TA and RA display is visible to the non-flying pilot and audio functions are operative on flying pilot side.
- 34-16-3 (O)Operations procedure to ensure non-flying pilot monitors pilot's display.
 - (O)Operations procedure to ensure TA ONLY mode is selected and all TA functions/elements are operative.
- 34-16-4 (O)Operations procedure to ensure all RA display/functions are operative.
- 34-17-1 (O)Operations procedure to ensure pilot awareness of loss of appropriate mode.
 - (O)Operations procedure to ensure pilot awareness of altitude vs terrain.
 - (O)Operations procedure to ensure pilot awareness of altitude vs terrain.
- 71-1 (M)Maintenance procedure to ensure cowl flaps are secured in the trail or full open position.

U. S. DEPARTMENT OF TRANSPORTATION

FEDERAL AVIATION ADMINISTRATION

MASTER MINIMUM EQUIPMENT LIST

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

21-1

1. | 2. NUMBER INSTALLED

SYSTEM & SEQUENCE NUMBERS	ITEM			3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
21	AIR CONDITIONING				
1.	Cabin Heat Source Selectors	C	2	0	(M)May be inoperative with the Selector Switch in the OFF position
2.	Automatic Cabin Air Temperature Control System	C	1	0	May be inoperative provided Manual Cabin Air Temperature Control System is operative. OR (M)May be inoperative provided: a) Bleed heat is not used and b) Cabin Heat Source Selector is in the OFF position.
3.	Manual Cabin Air Temperature Control System	C	1	0	May be inoperative provided Automatic Cabin Air Temperature Control System is operative. OR (M)May be inoperative provided: a) Bleed heat is not used and b) Cabin Heat Source Selector is in the OFF position.
4.	Air Duct Overheat Light	C	1	0	(M)May be inoperative provided: a) Bleed heat is not used and b) Cabin Heat Source Selector is in the OFF position.
5.	Fresh Air Blower	C	1	0	

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

21-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH
---------------------------	------	----	---------------------	---------------------------------

-----				4. REMARKS OR EXCEPTIONS
21	AIR CONDITIONING			
6.	Cabin/Cockpit Air Control			Deleted, Rev. 4
7.	Overhead Vent Fan	C	1	0
8.	Air Conditioner System	C	1	0

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

DATE: 06/30/97

PAGE:

22-1

SYSTEM & SEQUENCE NUMBERS	1. ITEM	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
22	AUTO FLIGHT			

1.	Autopilot	C	1	0	(M)As required by FAR.
2.	Yaw Damper	C	1	0	(M)

U. S. DEPARTMENT OF TRANSPORTATION

FEDERAL AVIATION ADMINISTRATION

MASTER MINIMUM EQUIPMENT LIST

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

23-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
23	COMMUNICATIONS				
1.	Communication	C	-	-	As required by FAR.

Systems (UHF, VHF, HF)					
2.	Audi o Ampl i fi er			Del eted, Rev. 4	
3.	Cockpi t Speakers	C	2	1	One speaker may be i noperati ve.
					OR
		C	2	0	May be i noperati ve provi ded an operati ve headset is used by the flight crew.
4.	Passenger Address System				
	1) Passenger Confi gurati on	B	1	0	(0)May be i noperati ve provi ded altern ate, normal and emergency procedures and/or operati ng restri cti ons are establi shed and used.
	2) Cargo Confi gurati on	D	1	0	
5.	Stati c Di scharge Wi cks	C	17	-	No more than one may be damaged or mi ssi ng on any one control surface.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b
DATE: 06/30/97

PAGE:
23-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
23	COMMUNICATIONS				
6.***	Cockpi t Voi ce Recorder (CVR) (If Flight Data Recorder Requ i red by	A	1	0	May be i noperati ve provi ded: a) Flight Data Recorder (FDR) operates normally, b) Repai rs are made wi thi n

Ce406r4b.txt

FAR)

three flight days.

*** Cockpit Voice Recorder (CVR) (If No Flight Data Recorder Required by FAR)

A

1

0

May be inoperative provided repairs are made within three flight days.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT: CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

23-3

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3. NUMBER REQUIRED FOR DISPATCH		
23	COMMUNICATIONS				
7.	Boom Microphone				
***	(CVR & FDR installations)				
1)	Cockpit Voice Recorder Equipped to Record Boom	A	-	0	May be inoperative provided: are made within three flight days.

	Mi crophone per FAR 135.151(d) or FAR 121.359(e)			
*** 2)	Cockpi t Voi ce Recorder Not Equi pped to Record Boom Mi crophone	D	-	0
	Boom Mi crophone (CVR i nstal lations onl y)			
1)	Cockpi t Voi ce Recorder Equi pped To Record Boom Mi crophone per FAR 121.359(e) or FAR 135.151(d)	A	-	0
				May be i noperati ve provi ded repairs are made wi thi n three fl ight days.
2)	Cockpi t Voi ce Recorder Not Equi pped to Record Boom Mi crophone	D	-	0

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MI NI MUM EQUI PMENT LI ST

FEDERAL AVI ATI ON ADMI NI STRATI ON

AIRCRAFT: CESSNA MODELS 406 AND F406

REVI SI ON NO: 4 b

PAGE:

DATE: 06/30/97

25-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
25	EQUI PMENT/FURNI SHI NGS				
1.	Cockpi t Shoul der Harness	C	2	1	Right si de may be i noperati ve provi ded seat remai ns unoccupi ed.
2.	Passenger Seats	C	-	0	All may be i noperati ve provi ded: a) Affected seat does not block emergency egress to the aisle or exit and b) Affected seat is blocked and placarded "DO NOT OCCUPY."

				NOTE 1: A seat with an inoperative seat belt or shoulder harness is considered to be inoperative.
				NOTE 2: A seat with an inoperative recline mechanism is considered to be inoperative if the seat back cannot be secured in the upright position.
3.	Approved Flotation Equipment	D	- 0	Any in excess of those required by FAR may be inoperative or missing.
4.	Emergency Locator Transmitter (ELT)	C	1 0	As required by FAR
		C	1 0	OR May be inoperative for published scheduled flights in scheduled air carrier service.
5.	First Aid Kits	D	- -	Any in excess of those required by FAR may be incomplete or missing provided required distributions are maintained.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

25-2

SYSTEM & SEQUENCE NUMBERS	1. ITEM	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
25	EQUIPMENT/FURNISHINGS			
6.	Passenger Convenience Items	-	-	Passenger convenience items, as expressed in this MMEL, are those related to passenger convenience, comfort or entertainment such as but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps, etc. Items addressed elsewhere in this document shall not be included. (M) and (O) procedures may be required in the air carrier's

Ce406r4b.txt

appropriate document.

7. *** Emergency Medical Equipment (EMS)

C

-

0

May be inoperative provided system is deactivated and secured. (M) or (O) procedures may be required and included in the air carrier's approved document.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT: CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

26-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3. NUMBER REQUIRED FOR DISPATCH		
26	FIRE PROTECTION				
1.	Portable Fire Extinguisher	D	-	-	Any in excess of those required by FAR may be inoperative or missing provided: a) Inoperative fire extinguisher is tagged inoperative, removed from the installed location, and placed out of sight so it can not be mistaken for a functional unit and b) Required distribution is maintained.
2.	Total Cabin Flood	C	1	0	

3. Fire Extinguishing System
 Engine Fire Extinguishing System

Deleted, Rev. 4

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
 CESSNA MODELS 406 AND F406

REVISION NO: 4 b
 DATE: 06/30/97

PAGE:
 27-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3. NUMBER REQUIRED FOR DISPATCH		
27	FLIGHT CONTROLS				
1.	Electric Elevator Trim System	C	1	0	(M)May be inoperative provided manual trim is operative and unaffected.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

28-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3. NUMBER REQUIRED FOR DISPATCH		
28 FUEL					
1.	Fuel Level Low Lights	C	2	0	
2.	Fuel Totalizer	C	1	0	
3.	Fuel Quantity Indicators	C	2	1	(0)One side may be inoperative provided a reliable means is established to determine that fuel quantity on board meets the regulatory requirements for the intended flight.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

29-1

SYSTEM & SEQUENCE NUMBERS	1. ITEM	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
		3. NUMBER REQUIRED FOR DISPATCH		
29 HYDRAULIC POWER				
1.	Engine Driven Pumps C	2	1	(M)One may be inoperative.
2.	Hydraulic Flow Low Lights C	2	1	One light may be inoperative provided Hydraulic Flow Light for the associated pump is operative and monitored.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

30-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3.	NUMBER REQUIRED FOR DISPATCH	
30	ICE AND RAIN PROTECTION				
1.	Pi tot Heaters	B	2	1	Left Pi tot Heater must be operative for IFR passenger carrying and for flight in known or forecast icing conditions. NOTE: Two heated pi tot tubes are required for these conditions if a second airspeed indicator is installed and operative.
2.	Surface Deicing System (Wing, Vertical and Horizontal Stabilizer)	C	1	0	May be inoperative provided aircraft is not operated into known or forecast icing conditions.
3.	Propeller Deice Systems (Manual or Automatic)	C	2	0	May be inoperative provided aircraft is not operated into known or forecast icing conditions.
4.	Windshield Heater	C	1	0	May be inoperative provided

Ce406r4b.txt

5.	Windshield Alcohol System	C	1	0	aircraft is not operated into known or forecast icing conditions.
6.	Stall Warning Heater	C	1	0	May be inoperative provided aircraft is not operated into known or forecast icing conditions.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

31-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3.	NUMBER REQUIRED FOR DISPATCH	
31	INDICATING/RECORDING SYSTEMS				
1.	Clock with sweep second hand, or electric digital clock	C	-	0	May be inoperative for VFR operations.
2.	Flight Hour Recorder	C	1	0	(0)
3.	Flight Data Recorder (FDR) (Recording Parameters Required by FAR)	A	-	0	May be inoperative provided: a) Cockpit Voice Recorder (CVR) operates normally, b) Airplane is not dispatched from a designated airport where repairs or replacements can be made and c) Repairs are made within three flight days.
***	Flight Data Recorder (FDR) (Recording Parameters not required by FAR)	C	-	0	

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

33-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3.	NUMBER REQUIRED FOR DISPATCH	
33 LIGHTS					
1.	Anti -collisi on Strobe Light System	B	1	0	May be inoperative for day operati ons.
2.	Posi ti on Lights	C	3	0	May be inoperative for day operati ons.
3.	Cockpi t/ Flight Deck/ Flight Compartment and Instrument Li ghti ng System	C	-	-	Indi vidual lights may be inoperative provided remaini ng lights are: a) Suffi cient to clearly illumi nate all required instruments, controls, and other devices for which it is provided, b) Posi ti oned so that direct rays are shielded from flight crewmembers eyes and c) Li ghti ng confi gurati on and intensi ty is acceptable to the flight crew.
4.	Landi ng Li ght	C	1	0	May be inoperative for day operati ons.
5.	Cabi n Li ght System	C	-	0	Indi vidual lights may be inoperative provided Li ghti ng

Ce406r4b.txt

6.	Oscillating Beacon Ground Recognition Lights	C	2	0	configuration is acceptable to the flight crew.
7.	Passenger Notice System (Fasten Seat Belt/No Smoking)	C	1	0	(0)May be inoperative provided appropriate verbal briefings are given to the passengers.
8.	Taxi Light	C	1	0	

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

33-2

SYSTEM & SEQUENCE NUMBERS	1. ITEM		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
33	LIGHTS					
9.	Wing Ice Lights	C	2	0		May be inoperative provided a portable lamp/light of adequate capacity for wing and/or control surface inspection is available for night operations in icing conditions.
10.	Wing Tip Recognition Lights	C	2	0		

U. S. DEPARTMENT OF TRANSPORTATION

FEDERAL AVIATION ADMINISTRATION

MASTER MINIMUM EQUIPMENT LIST

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

34-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3.	NUMBER REQUIRED FOR DISPATCH	
34	NAVIGATION				
1.	Aircraft Altitude *** Alerting System	C	1	0	
2.	Flight Director	C	1	0	
3.	Gyroscopic Rate of Turn/Slip Skid Indicators	B	2	0	Must be operative on left side for IFR, passenger carrying VFR over-the-top, and passenger carrying VFR night flights.
4.	Vertical Speed Indicators	B	2	0	Must be operative on left side for passenger carrying operations.
5.	ATC Transponders and Automatic Altitude Reporting Systems	D	-	-	Any in excess of those required by FAR may be inoperative.
6.	Navigation Equipment (VOR/ILS, Loran, Omega/VLF, GPS INS, Doppler, RNAV)	C	-	-	As required by FAR.
7.	Weather Radar/ Thunderstorm Detection Equipment	C	1	-	As required by FAR.
8.	Marker Beacon	C	1	0	May be inoperative provided approach procedure does not require its use.
9.	DME	C	-	0	As required by FAR.

10. ADF	C	-	0	As required by FAR.
11. RMI	C	-	0	
12. Altitude Encoder				Has been included in item 5.
13. Radar Altimeter	C	1	0	

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

DATE: 06/30/97

PAGE:

34-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34 NAVIGATION					
14. Nonstabilized Magnetic Compass	B	1	0		May be inoperative provided any combination of three gyro or INS (IRU) stabilized compass systems are operative.
					OR
	B	1	0		May be inoperative provided: a) Any combination of two gyro or INS stabilized compass systems are operative and b) Aircraft is operated with dual independent navigation capability and under positive radar control by ATC on the enroute portion of the flight.
					OR
	B	1	0		May be inoperative for flights that are entirely within areas of magnetic unreliability provided at least two stabilized directional gyro systems are installed, operative, and used in conjunction with approved free gyro navigation techniques.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

34-3

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
			-	0		
34	NAVIGATION					
15. ***	Traffic Alert Collision Avoidance System I (TCAS I)	C	-	0		(M)May be inoperative provided system is deactivated and secured.
16. ***	Traffic Alert Collision Avoidance System II (TCAS II)					
1)	TCAS System	C	-	0		(M)May be inoperative provided system is deactivated and secured.
2)	Combined TA and RA Dual Displays	C	2	1		(O)May be inoperative on the non-flying pilot side provided: a) TA and RA elements and audio functions are operative on flying pilot side, and b) TA and RA display indications are visible to the non-flying pilot.
3)	Resolution Advisory (RA) Display System(s)	C	2	1		(O)One may be inoperative on non-flying pilot side. OR
		C	-	0		(O)May be inoperative provided: a) All Traffic Alert (TA) display elements and voice command audio functions are operative, and b) TA only mode is selected by the crew.
4)	TA Display System(s)	C	-	0		(O)May be inoperative provided all installed RA display and audio functions are operative.

U. S. DEPARTMENT OF TRANSPORTATION

FEDERAL AVIATION ADMINISTRATION

MASTER MINIMUM EQUIPMENT LIST

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

34-4

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION					
17.	Ground Proximity *** Warning System					
	1) Modes 1-4	A	-	0	(0) May be inoperative provided: a) Alternate procedures are established, used and b) Repairs are made within two flight days.	
	2) Test Mode	A	1	0	May be inoperative provided: a) GPWS is considered inoperative and b) Repairs are made within two flight days.	
	3) Glide slope Deviation (Mode 5)	B	2	0		
***	4) Advisory Callouts	C	-	0	(0) May be inoperative provided alternate procedures are established and used.	
***	5) Windshear Mode	C	-	0	(0) May be inoperative provided alternate procedures are established and used.	

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA MODELS 406 AND F406

REVISION NO: 4 b

PAGE:

DATE: 06/30/97

35-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3.	NUMBER REQUIRED FOR DISPATCH	
35	OXYGEN				
1.	Oxygen System (Passengers)	C	1	-	As required by FAR.

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b
DATE: 06/30/97

PAGE:
61-1

SYSTEM & SEQUENCE NUMBERS	1. ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
61 PROPELLERS					
1. Propeller Synchrophaser	C	1	0		

U. S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:
CESSNA MODELS 406 AND F406

REVISION NO: 4 b
DATE: 06/30/97

PAGE:
71-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
71	POWERPLANT				
1.	Cowl Flap Controls C	2	2	1	(M)May be inoperative in the trail or fully open position provided the oil temperature is monitored.