

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

Revision: 5
Date: 09/30/2002

WASHINGTON, D.C.

M A S T E R M I N I M U M E Q U I P M E N T L I S T

PARTENAVIA P68 SERIES

FEDERAL AVIATION ADMINISTRATION
KANSAS CITY AIRCRAFT EVALUATION GROUP
DOT BUILDING, 901 LOCUST
ROOM 332
KANSAS CITY, MO 64106-2641

TELEPHONE: (816) 329-3233
FAX: (816) 329-3241

PARTENAVIA P68 SERIES

Table of Contents

SYSTEM NO.	SYSTEM	PAGE
--	Table of Contents	I
--	Log of Revisions	II
--	Control Page	III, IV
--	Highlights of Change	V, VI
--	Definitions	VII, VIII, IX, X
--	Definitions	XI, XII, XIII, XIV
--	Preamble	XV, XVI
--	Guidelines for (O) & (M) Procedures	XVII, XVIII
21	Air Conditioning	21-1
22	Auto Flight	22-1
23	Communications	23-1, 2, 3
24	Electrical Power	24-1
25	Equipment/Furnishings	25-1, 2
26	Fire Protection	26-1
27	Flight Controls	27-1
28	Fuel	28-1
30	Ice and Rain Protection	30-1
31	Indicating/Recording Systems	31-1
33	Lights	33-1, 2
34	Navigation	34-1, 2, 3, 4, 5
34	Navigation	34-6, 7, 8, 9
35	Oxygen	35-1
37	Vacuum/Pressure	37-1
61	Propellers	61-1
77	Engine Indicating	77-1

PARTENAVIA P68 SERIES

Log of Revisions

REV.NO.	DATE	PAGE NUMBERS	INITIALS
ORIGINAL	07/03/1986		
1	05/08/1989	ALL PAGES	
2	06/26/1989	HIGHLIGHTS OF REV., DEFINITIONS	
2	06/26/1989	PREAMBLE	
3	08/13/1992	HIGHLIGHTS OF REV., DEFINITIONS	
3	08/13/1992	GUIDELINES	
3	08/13/1992	21-1, 22-1, 23-1, 25-1, 25-2	
3	08/13/1992	30-1, 31-1, 33-1, 33-2, 34-1	
3	08/13/1992	34-2, 34-3, 61-1, 77-1	
4	03/29/1995	HIGHLIGHTS OF REV., DEFINITIONS	
4	03/29/1995	GUIDELINES	
4	03/29/1995	21-1, 22-1, 23-1, 23-2, 24-1	
4	03/29/1995	25-1, 25-2, 26-1, 27-1, 28-1	
4	03/29/1995	30-1, 31-1, 33-1, 33-2, 34-1	
4	03/29/1995	34-2, 34-3, 34-4, 35-1, 37-1	
4	03/29/1995	61-1, 77-1	
5	09/30/2002	HIGHLIGHTS OF REV., DEFINITIONS	
5	09/30/2002	GUIDELINES	
5	09/30/2002	21-1, 22-1, 23-1, 23-2, 23-3	
5	09/30/2002	24-1, 25-1, 25-2, 26-1, 27-1	
5	09/30/2002	28-1, 30-1, 31-1, 33-1, 33-2	
5	09/30/2002	34-1, 34-2, 34-3, 34-4, 34-5	
5	09/30/2002	34-6, 34-7, 34-8, 34-9, 35-1	
5	09/30/2002	37-1, 61-1, 77-1	

PARTENAVIA P68 SERIES

Control Page

SYSTEM	PAGE	REV NO.	CURRENT DATE
Cover Page	-	5	09/30/2002
Table of Contents	I	5	09/30/2002
Log of Revisions	II	5	09/30/2002
Control Page	III	5	09/30/2002
	IV	5	09/30/2002
Highlights of Change	V	5	09/30/2002
	VI	5	09/30/2002
Definitions	VII	6	01/31/1995
	VIII	6	01/31/1995
	IX	6	01/31/1995
	X	6	01/31/1995
	XI	6	01/31/1995
	XII	6	01/31/1995
	XIII	6	01/31/1995
	XIV	6	01/31/1995
Preamble	XV	2	06/14/1989
	XVI	2	06/14/1989
Guidelines for (O) & (M) Procedures	XVII	5	09/30/2002
	XVIII	5	09/30/2002
21	21-1	5	09/30/2002
22	22-1	5	09/30/2002
23	23-1	5	09/30/2002
	23-2	5	09/30/2002
	23-3	5	09/30/2002
24	24-1	5	09/30/2002
25	25-1	5	09/30/2002
	25-2	5	09/30/2002
26	26-1	5	09/30/2002
27	27-1	5	09/30/2002
28	28-1	5	09/30/2002
30	30-1	5	09/30/2002
31	31-1	5	09/30/2002
33	33-1	5	09/30/2002
	33-2	5	09/30/2002
34	34-1	5	09/30/2002
	34-2	5	09/30/2002
	34-3	5	09/30/2002
	34-4	5	09/30/2002
	34-5	5	09/30/2002
	34-6	5	09/30/2002

PARTENAVIA P68 SERIES

Control Page

SYSTEM	PAGE	REV NO.	CURRENT DATE
	34-7	5	09/30/2002
	34-8	5	09/30/2002
	34-9	5	09/30/2002
35	35-1	5	09/30/2002
37	37-1	5	09/30/2002
61	61-1	5	09/30/2002
77	77-1	5	09/30/2002

PARTENAVIA P68 SERIES

Highlights of Change

- ATA 22-1 Changed relief for Autopilot in accordance with Policy Letter 101 designated as Global Change 103.
- ATA 22-3 Added relief for Autopilot Disconnect in accordance with Policy Letter 93.
- ATA 23-1 Changed relief for Communications Equipment (UHF, VHF) in accordance with Policy Letter 95 designated as Global Change 111.
- ATA 23-5 Changed relief for Boom Microphones in accordance with Policy Letter 58 designated as Global Change 100.
- ATA 23-6 Changed relief for Passenger Address System in accordance with Policy Letter 9 designated as Global Change 109.
- ATA 23-7 Changed relief for High Frequency (HF) Communications System in accordance with Policy Letter 106 designated as Global Change 89.
- ATA 25-3 Changed relief for Passenger Seats in accordance with Policy Letter 79 designated as Global Change 96.
- ATA 25-4 Changed relief for Passenger Convenience Items in accordance with Policy Letter 33 designated as Global Change 99.
- ATA 25-5 Deleted the word "OR" for clarification and compliance with Policy Letter 31 and deleted relief for other than "As required by FAR".
- ATA 31-3 Changed relief for Flight Data Recorder System in accordance with Policy Letter 87 designated as Global Change 101.
- ATA 33-3 Deleted the word "OR" for clarification and compliance with Policy Letter 31 designated as Global Change 83, changed format in remarks column and changed category if strobes are installed.
- ATA 33-8 Deleted the word "OR" for clarification and compliance with Policy Letter 31 designated as Global Change 83.

PARTENAVIA P68 SERIES

Highlights of Change

- ATA 34-4 Changed relief for ATC Transponders and Automatic Altitude Reporting Systems in accordance with Policy Letter 76 designated as Global Change 110.
- ATA 34-8 Changed relief for Distant Measuring Equipment (DME) Systems in accordance with Policy Letter 3.
- ATA 34-14 Changed relief for Nonstablized Magnetic (Standby) Compass System in accordance with Policy Letter 10.
- ATA 34-15 Added relief for Altitude Alerting Systems in accordance with Policy Letter 39 designated as Global Change 95.
- ATA 34-16 Changed relief for TCAS I System in accordance with Policy Letter 32 designated as Global Change 81 and renumbered from 34-15 to 34-16.
- ATA 34-17 Changed relief for TCAS II System in accordance with Policy Letter 32 designated as Global Change 81.
- ATA 34-18 Changed relief for Ground Proximity Warning System in accordance with Policy Letter 54 designated as Global Change 107 and renumbered from 34-16 to 34-18.
- ATA 34-19 Added relief for Windshear Detection, Guidance, and Avoidance System in accordance with Policy Letter 67 designated as Global Change 88.
- ATA 34-20 Added relief for Flight Management System Navigation Databases in accordance with Policy Letter 98 designated as Global Change 71.
- ATA 34-21 Added relief for Navigation Management System Navigation Databases in accordance with Policy Letter 98 designated as Global Change 71.

PARTENAVIA P68 SERIES

Definitions

1. System Definitions.

System numbers are based on the Air Transport Association (ATA) Specification Number 100 and items are numbered sequentially.

- a. "Item" (Column 1) means the equipment, system, component, or function listed in the "Item" column.
- b. "Number Installed" (Column 2) is the number (quantity) of items normally installed in the aircraft. This number represents the aircraft configuration considered in developing this MMEL. Should the number be a variable (e.g., passenger cabin items) a number is not required.
- c. "Number Required for Dispatch" (Column 3) is the minimum number (quantity) of items required for operation provided the conditions specified in Column 4 are met.

NOTE: Where the MMEL shows a variable number required for dispatch, the MEL must reflect the actual number required for dispatch or an alternate means of configuration control approved by the Administrator.

- d. "Remarks or Exceptions" (Column 4) in this column includes a statement either prohibiting or permitting operation with a specific number of items inoperative, provisos (conditions and limitations) for such operation, and appropriate notes.
- e. A vertical bar (change bar) in the margin indicates a change, addition or deletion in the adjacent text for the current revision of that page only. The change bar is dropped at the next revision of that page.

2. "Airplane/Rotorcraft Flight Manual" (AFM/RFM) is the document required for type certification and approved by the responsible FAA Aircraft Certification Office. The FAA approved AFM/RFM for the specific aircraft is listed on the applicable Type

PARTENAVIA P68 SERIES

Definitions

Certificate Data Sheet.

3. "As required by FAR" means that the listed item is subject to certain provisions (restrictive or permissive) expressed in the Federal Aviation Regulations operating rules. The number of items required by the FAR must be operative. When the listed item is not required by FAR it may be inoperative for time specified by repair category.

4. Each inoperative item must be placarded to inform and remind the crewmembers and maintenance personnel of the equipment condition.

NOTE: To the extent practical, placards should be located adjacent to the control or indicator for the item affected; however, unless otherwise specified, placard wording and location will be determined by the operator.

5. "-" symbol in Column 2 and/or Column 3 indicates a variable number (quantity) of the item installed.

6. "Deleted" in the remarks column after a sequence item indicates that the item was previously listed but is now required to be operative if installed in the aircraft.

7. "ER" refers to extended range operations of a two-engine airplane which has a type design approval for ER operations and complies with the provisions of Advisory Circular 120-42A.

8. "Federal Aviation Regulations" (FAR) means the applicable portions of the Federal Aviation Act and Federal Aviation Regulations.

9. "Flight Day" means a 24 hour period (from midnight to midnight) either Universal Coordinated Time (UCT) or local time, as established by the operator, during which at least one flight is initiated for the affected aircraft.

10. "Icing Conditions" means an atmospheric environment that may cause ice to form on the aircraft or in the engine(s).

11. Alphabetical symbol in Column 4 indicates a proviso (condition or limitation) that must be complied with for

PARTENAVIA P68 SERIES

Definitions

operation with the listed item inoperative.

12. "Inoperative" means a system and/or component malfunction to the extent that it does not accomplish its intended purpose and/or is not consistently functioning normally within its approved operating limit(s) or tolerance(s).

13. "Notes:" in Column 4 provides additional information for crewmember or maintenance consideration. Notes are used to identify applicable material which is intended to assist with compliance, but do not relieve the operator of the responsibility for compliance with all applicable requirements. Notes are not a part of the provisos.

14. Inoperative components of an inoperative system:
Inoperative items which are components of a system which is inoperative are usually considered components directly associated with and having no other function than to support that system. (Warning/caution systems associated with the inoperative system must be operative unless relief is specifically authorized per the MMEL).

15. "(M)" symbol indicates a requirement for a specific maintenance procedure which must be accomplished prior to operation with the listed item inoperative. Normally these procedures are accomplished by maintenance personnel; however, other personnel may be qualified and authorized to perform certain functions. Procedures requiring specialized knowledge or skill, or requiring the use of tools or test equipment should be accomplished by maintenance personnel. The satisfactory accomplishment of all maintenance procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are required to be published as part of the operator's manual or MEL.

16. "(O)" symbol indicates a requirement for a specific operations procedure which must be accomplished in planning for and/or operating with the listed item inoperative. Normally these procedures are accomplished by the flight crew; however, other personnel may be qualified and authorized to perform certain functions. The satisfactory accomplishment of all procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are

PARTENAVIA P68 SERIES

Definitions

required to be published as a part of the operator's manual or MEL.

NOTE: The (M) and (O) symbols are required in the operator's MEL unless otherwise authorized by the Administrator.

17. "Deactivated" and "Secured" means that the specified component must be put into an acceptable condition for safe flight. An acceptable method of securing or deactivating will be established by the operator.

18. "Visual Flight Rules" (VFR) is as defined in FAR Part 91. This precludes a pilot from filing an Instrument Flight Rules (IFR) flight plan.

19. "Visual Meteorological Conditions" (VMC) means the atmospheric environment is such that would allow a flight to proceed under the visual flight rules applicable to the flight. This does not preclude operating under Instrument Flight Rules.

20. "Visible Moisture" means an atmospheric environment containing water in any form that can be seen in natural or artificial light; for example, clouds, fog, rain, sleet, hail, or snow.

21. "Passenger Convenience Items" means those items related to passenger convenience, comfort or entertainment such as, but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps, etc.

22. Repair Intervals: All users of an MEL approved under FAR 121, 125, 129 and 135 must effect repairs of inoperative systems or components, deferred in accordance with the MEL, at or prior to the repair times established by the following letter designators:

Category A. Items in this category shall be repaired within the time interval specified in the remarks column of the operator's approved MEL.

Category B. Items in this category shall be repaired within three (3) consecutive calendar days (72 hours), excluding the day the malfunction was recorded in the aircraft maintenance

PARTENAVIA P68 SERIES

Definitions

record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the three day interval would begin at midnight the 26th and end at midnight the 29th.

Category C. Items in this category shall be repaired within ten (10) consecutive calendar days (240 hours), excluding the day the malfunction was recorded in the aircraft maintenance record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the 10 day interval would begin at midnight the 26th and end at midnight February 5th.

Category D. Items in this category shall be repaired within one hundred and twenty (120) consecutive calendar days (2880 hours), excluding the day the malfunction was recorded in the aircraft maintenance log and/or record.

The letter designators are inserted adjacent to Column 2.

23. Electronic fault alerting system - General

New generation aircraft display system fault indications to the flight crew by use of computerized display systems. Each aircraft manufacturer has incorporated individual design philosophies in determining the data that would be represented. The following are customized definitions (specific to each manufacturer) to help determine the level of messages affecting the aircraft's dispatch status. When preparing the MEL document, operators are to select the proper Definition No. 23 for their aircraft, if appropriate.

a. BOEING (B-757/767, B-747-400, B-777)

Boeing airplanes equipped with Engine Indicating and Crew Alerting Systems (EICAS), provide different priority levels of system messages (WARNING, CAUTION, ADVISORY, STATUS and MAINTENANCE). Any messages that affects airplane dispatch status will be displayed at a STATUS message level or higher. The absence of an EICAS STATUS or higher level (WARNING, CAUTION, ADVISORY) indicates that the system/component is operating within its approved operating limits or tolerances.

System conditions that result only in a maintenance level message, i.e. no correlation with a higher level EICAS message,

PARTENAVIA P68 SERIES

Definitions

do not affect dispatch and do not require action other than as addressed within an operators standard maintenance program.

b. DOUGLAS (MD-11)

Some Douglas aircraft are equipped with an alerting function which is a subsystem within the Electronic Instrument System (EIS). The alerting function provides various levels of system condition alerts (WARNING, CAUTION, ADVISORY, MAINTENANCE and STATUS).

Alerts that affect aircraft dispatch will include WARNING, CAUTION, STATUS or MAINTENANCE level. MAINTENANCE alerts are displayed on the status page of the EIS display panel under the maintenance heading.

A MAINTENANCE alert on the EIS indicates the presence of a system fault which can be identified by the Central Fault Display System (CFDS) interrogation. The systems are designed to be fault tolerant, however, for any MAINTENANCE alert, the MEL must be verified for dispatch purposes.

c. AIRBUS (A-300-600, A-310, A-320/319/321, A-330, A-340)

Airbus aircraft equipped with Electronic Centralized Aircraft Monitoring (ECAM) provide different levels of system condition messages (WARNING, CAUTION, STATUS, and ADVISORY). A-320/319/321, A-330, and A-340 also provide MAINTENANCE status messages.

Any message that effects airplane dispatchability will normally be at the WARNING, CAUTION or STATUS level. MAINTENANCE messages (A-320/319/321, A-330, and A-340 only) are also indicated on ECAM Status Page below the white Maintenance label.

A MAINTENANCE status (Class II) message on ECAM indicates the presence of a system fault which can be identified by CFDS (A-320/319/321) or CMS (A-330/A-340) interrogation. The systems are designed to be fault tolerant, however for any MAINTENANCE status (Class II) message, the A-320/319/321 MEL must be verified for dispatch capability. For the A-330 and A-340, MAINTENANCE status messages do not affect dispatch.

d. FOKKER (FK-100)

PARTENAVIA P68 SERIES

Definitions

Fokker aircraft are equipped with Multi Function Display System (MFDS) which provides electronic message referring to the different priority levels of system information (WARNING (red), CAUTION (amber), AWARENESS (cyan) AND STATUS (white). Any messages that affects aircraft dispatch will be at the WARNING, CAUTION or AWARENESS level. In these cases the MEL must be verified for dispatch capability and maintenance may be required.

System conditions that only require maintenance are not presented on the flight deck. These maintenance indications/messages may be presented on the Maintenance & Test Panel (MAP) or the Centralized Fault Display Unit (CFDU) and by dedicated Built In Test Evaluation (BITE) of systems.

24. "Administrative control item" means an item listed by the operator in the MEL for tracking and informational purposes. It may be added to an operator's MEL by approval of the Principal Operations Inspector provided no relief is granted, or provided conditions and limitations are contained in an approved document (i.e. Structural Repair Manual, airworthiness directive, etc.). If relief other than that granted by an approved document is sought for an administrative control item, a request must be submitted to the Administrator. If the request results in review and approval by the FOEB, the item becomes an MMEL item rather than an administrative control item.

25. "****" symbol in Column 1 indicates an item which is not required by regulation but which may have been installed on some models of aircraft covered by this MMEL. This item may be included on the operator's MEL after the approving office has determined that the item has been installed on one or more of the operator's aircraft. The symbol, however, shall not be carried forward into the operator's MEL. It should be noted that neither this policy nor the use of this symbol provide authority to install or remove an item from an aircraft.

26. "Excess Items" means those items that have been installed that are redundant to the requirements of the FARs.

27. "Day of Discovery" is the calendar day an equipment/instrument malfunction was recorded in the aircraft

PARTENAVIA P68 SERIES

Definitions

maintenance log and or record. This day is excluded from the calendar days or flight days specified in the MMEL for the repair of an inoperative item of equipment. This provision is applicable to all MMEL items, i.e., categories "A, B, C, and D."

PARTENAVIA P68 SERIES

Preamble
(Effective 6/14/89)

The following is applicable for authorized certificate holders operating under Federal Aviation Regulations (FAR) Parts 121, 125, 129, 135: The FAR require that all equipment installed on an aircraft in compliance with the Airworthiness Standards and the Operating Rules must be operative. However, the Rules also permit the publication of a Minimum Equipment List (MEL) where compliance with certain equipment requirements is not necessary in the interests of safety under all operating conditions. Experience has shown that with the various levels of redundancy designed into aircraft, operation of every system or installed component may not be necessary when the remaining operative equipment can provide an acceptable level of safety. A Master Minimum Equipment List (MMEL) is developed by the FAA, with participation by the aviation industry, to improve aircraft utilization and thereby provide more convenient and economic air transportation for the public. The FAA approved MMEL includes those items of equipment related to airworthiness and operating regulations and other items of equipment which the Administrator finds may be inoperative and yet maintain an acceptable level of safety by appropriate conditions and limitations; it does not contain obviously required items such as wings, flaps, and rudders. The MMEL is the basis for development of individual operator MELs which take into consideration the operator's particular aircraft equipment configuration and operational conditions. Operator MELs, for administrative control, may include items not contained in the MMEL; however, relief for administrative control items must be approved by the Administrator. An operator's MEL may differ in format from the MMEL, but cannot be less restrictive than the MMEL. The individual operator's MEL, when approved and authorized, permits operation of the aircraft with inoperative equipment.

Equipment not required by the operation being conducted and equipment in excess of FAR requirements are included in the MEL with appropriate conditions and limitations. The MEL must not deviate from the Aircraft Flight Manual Limitations, Emergency Procedures or with Airworthiness Directives. It is important to remember that all equipment related to the airworthiness and the operating regulations of the aircraft not listed on the MMEL must be operative.

PARTENAVIA P68 SERIES

Preamble
(Effective 6/14/89)

Suitable conditions and limitations in the form of placards, maintenance procedures, crew operating procedures and other restrictions as necessary are specified in the MEL to ensure that an acceptable level of safety is maintained.

The MEL is intended to permit operation with inoperative items of equipment for a period of time until repairs can be accomplished. It is important that repairs be accomplished at the earliest opportunity. In order to maintain an acceptable level of safety and reliability the MMEL establishes limitations on the duration of and conditions for operation with inoperative equipment. The MEL provides for release of the aircraft for flight with inoperative equipment. When an item of equipment is discovered to be inoperative, it is reported by making an entry in the Aircraft Maintenance Record/Logbook as prescribed by FAR. The item is then either repaired or may be deferred per the MEL or other approved means acceptable to the Administrator prior to further operation. MEL conditions and limitations, do not relieve the operator from determining that the aircraft is in condition for safe operation with items of equipment inoperative.

When these requirements are met, an Airworthiness Release, Aircraft Maintenance Record/Logbook entry, or other approved documentation is issued as prescribed by FAR. Such documentation is required prior to operation with any item of equipment inoperative.

Operators are responsible for exercising the necessary operational control to ensure that an acceptable level of safety is maintained. When operating with multiple inoperative items, the interrelationships between those items and the effect on aircraft operation and crew workload will be considered.

Operators are to establish a controlled and sound repair program including the parts, personnel, facilities, procedures, and schedules to ensure timely repair.

WHEN USING THE MEL, COMPLIANCE WITH THE STATED INTENT OF THE PREAMBLE, DEFINITIONS, AND THE CONDITIONS AND LIMITATIONS SPECIFIED IN THE MEL IS REQUIRED.

PARTENAVIA P68 SERIES

Guidelines for (O) & (M) Procedures

The FOEB has identified a need for certain procedures to provide an adequate level of safety while providing relief for the following items. These procedures must be established by the operator. The following guidelines are to help establish these required procedures.

- 21-1 (M) Procedure to ensure no fuel leak or mechanical/electrical fault will cause a fire or additional damage.
- 22-1 (M) Procedure to ensure that no electrical or mechanical fault will have any adverse effect on any flight control functions.
- 22-2 (M) Procedure to ensure that no electrical or mechanical fault will have any adverse effect on any flight control functions.
- 23-6 (O) Procedure to ensure that the passengers receive the appropriate briefings.
- 23-7 (O) Procedure to verify SATCOM System operates normally.
- 28-1 (O) Procedure to determine the quantity of fuel on board.
- 31-2 (O) Procedure for recording aircraft flight time for maintenance purposes.
- 34-15 (O) Procedure to ensure pilot awareness of altitude changes/ assignments.
- 34-16 (M) Procedure to deactivate and secure system.
 - (O) Procedure to ensure TCAS is not required.
- 34-17 (M) Procedure to deactivate and secure the system.
 - (O) Procedure to ensure TCAS is not required.
- 34-17-2 (O) Procedure to ensure TA ONLY mode is selected and enroute or approach procedures do not require its use.

PARTENAVIA P68 SERIES

Guidelines for (O) & (M) Procedures

- 34-17-3 (O) Procedures to ensure all RA display and audio functions are operative and enroute or approach procedures do not require its use.
- 34-18 (O) Procedure to ensure alternate procedures are established and used.
- 1) (O) Procedure to ensure alternate procedures are established and used.
 - 4) (O) Procedure to ensure alternate procedures are established and used for inoperative callout(s).
 - 5) (O) Procedure to ensure alternate procedures are established and used for inoperative windshear mode.
- 34-19-1 (O) Procedure to ensure that alternate procedures are established and used and that the Windshear Detection and Avoidance System operates normally.
- (O) Procedure to ensure that alternate procedures are established and that takeoff and landings are not conducted in known or forecast windshear conditions.
- 34-19-2 (O) Procedure to ensure that alternate procedures are established and used and that the Windshear Warning and Guidance System operates normally.
- (O) Procedure to ensure that alternate procedures are established and that takeoff and landings are not conducted in known or forecast windshear conditions.
- 34-20 (O) Procedure to verify status and suitability of navigation facilities used to define route of flight.
- 34-21 (O) Procedure to verify status and suitability of navigation facilities used to define route of flight.
- 37-1 (M) Procedure to assure that no unsafe conditions exist which could affect the engine operation or systems function.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

21-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
21	AIR CONDITIONING				
1.	Combustion Heater	C	1	0	(M)
2.	Heater Ventilation Blower	C	1	0	May be inoperative provided: a) Combustion heater is not operated on the ground, and b) Combustion heater is turned off prior to landing.
3.	Cabin Ventilating Blower	C	1	0	
4.	Air Conditioner	C	1	0	

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

22-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
				3. NUMBER REQUIRED FOR DISPATCH	
22	AUTO FLIGHT				
1.	Autopilot	C	-	0	(M) May be inoperative provided operations do not require its use.
2.	Yaw Damper	C	1	0	(M)
3.	Autopilot Disconnect	C	-	-	One may be inoperative provided the autopilot is not utilized at less than initial approach altitude.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

23-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3. NUMBER REQUIRED FOR DISPATCH		
23	COMMUNICATIONS				
1.	Communications Systems (UHF, VHF)	D	-	-	Any in excess of those required by FAR may be inoperative provided it is not powered by the Emergency Power Supply and not required for emergency procedures.
2.	Cockpit Speaker	C	1	0	May be inoperative provided two operative headsets are available to the flight crew.
3.	Audio Amplifier	C	1	0	May be inoperative provided two operative headsets are available to the flight crew.
4.	Cockpit Voice Recorder (CVR) (If FDR Required by FAR)	A	1	0	May be inoperative provided: a) Flight Data Recorder is operating normally, and b) Repairs are made within three flight days.
	Cockpit Voice Recorder (CVR) (If No FDR Required by FAR)	A	1	0	May be inoperative provided repairs are made within three flight days.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

23-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
23	COMMUNICATIONS				
5.	Boom Microphones (With Cockpit Voice Recorder (CVR) and with Flight Data Recorder (FDR) Installed)				
	1) Cockpit Voice Recorder Equipped to Record Boom Microphones per FAR 135.151(d).	A	- 0		May be inoperative provided: a) Flight Data Recorder (FDR) operates normally, and b) Repairs are made within three flight days.
***	2) Cockpit Voice Recorder not Equipped to Record Boom Microphone (Cockpit Voice Recorder (CVR) without Flight Data Recorder (FDR) Installed)	D	- 0		Any in excess of those required by FAR may be inoperative.
	1) Cockpit Voice Recorder Equipped to Record Boom Microphones per FAR 135.151(d)	A	- 0		May be inoperative provided repairs are made within three flight days.
***	2) Cockpit Voice Recorder Not Equipped to Record Boom Microphone	D	- 0		Any in excess of those required by FAR may be inoperative.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

PARTENAVIA P68 SERIES

REVISION NO: 5

DATE: 09/30/2002

PAGE:

23-3

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
23	COMMUNICATIONS				
6.	Passenger Address *** (PA) System				
1)	Passenger Configuration	B	1	0	(O) May be inoperative provided alternate, normal and emergency procedures, and/or operating restrictions are established and used. NOTE: Any station that operates normally may be used.
2)	Cargo Configuration	D	1	0	
7.	High Frequency (HF) *** Communication System	D	-	-	Any in excess of those required by FAR may be inoperative.
		C	-	-	(O) May be inoperative while conducting operations that require two LRCS provided: a) SATCOM (High or Low Gain) Data Link system operates normally, and b) SATCOM Data Link communication operates normally over the intended route of flight.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

24-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
24	ELECTRICAL POWER				
1.	Volt/Ammeter	B	1	0	May be inoperative provided: a) "Alternator Off" warning lights are operative, and b) "Low Voltage" warning light is operative.
2.	Low Voltage Warning Light	B	1	0	May be inoperative provided: a) "Volt/Ammeter" is operative and monitored. b) "Alternator Off" warning lights are operative.
3.	Alternator Off Lights	B	2	1	One may be inoperative provided: a) "Volt/Ammeter" is operative and monitored, and b) "Low Voltage" warning light is operative.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

25-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
25	EQUIPMENT/FURNISHINGS				
1.	Approved Flotation Equipment	C	-	-	As required by FAR.
2.	Cockpit Shoulder Harness	B	2	1	Right side may be inoperative for single pilot operations provided seat remains unoccupied.
3.	Passenger Seat(s)	C	-	-	May be inoperative provided: a) Seat does not block an Emergency Exit, b) The affected seat(s) are blocked and placarded "DO NOT OCCUPY".
					NOTE: A seat with an inoperative seat belt is considered inoperative.
	1) Recline Mechanism	C	-	-	May be inoperative and seat occupied provided seat is secured in the up-right position.
4.	Passenger Convenience Item(s)		-	-	Passenger convenience items, as expressed in this MMEL are those related to passenger convenience, comfort or entertainment such as, but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps. Items addressed elsewhere in this document shall not be included. (M) and (O) procedures may be required and included in the air carrier's appropriate document.
					NOTE: Exterior lavatory door ash trays are not considered convenience items.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

25-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
25	EQUIPMENT/FURNISHINGS				
5.	Emergency Locator Transmitter	C	1	0	As required by FAR.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

26-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
26	FIRE PROTECTION				
1.	Portable Fire Extinguishers	D	-	-	Any in excess of those required by FAR may be inoperative or missing provided: a) The inoperative fire extinguisher is tagged inoperative, removed from the installed location, and placed so that it can not be mistaken for a functional unit, and b) Required distribution is maintained.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

PARTENAVIA P68 SERIES

REVISION NO: 5

DATE: 09/30/2002

PAGE:

27-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
27	FLIGHT CONTROLS				
1.	Trim Tab Position Indicators (Rudder, Stabilator)	C	-	0	May be inoperative provided: a) Tab is visually checked for full range of operation. b) Tab operation is not affected, and c) Tab is positioned to neutral prior to each departure and neutral position is verified by visual inspection.
2.	Electric Stabilator Trim	C	1	0	May be inoperative provided manual trim is operative and unaffected.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

28-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
28	FUEL				
1.	Fuel Quantity Indicator (Dual Indicating)	C	1	1	(O)One side may be inoperative provided a reliable means is established to determine that fuel quantity on board meets the regulatory requirements for the intended flight.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

30-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
30	ICE AND RAIN PROTECTION				
1.	Pitot Heater	B	2	0	Left unit must be operative for IFR passenger carrying and for flight in known or forecast icing conditions. Two heated pitot tubes are required for these conditions if a second airspeed indicator is installed and operative.
2.	Surface Deicing System (Wing, Vertical, and Horizontal Stabilizer)	C	1	0	May be inoperative provided aircraft is not operated in known or forecast icing conditions.
3.	Propeller Anti-ice System	C	2	0	May be inoperative provided the aircraft is not operated in known or forecast icing conditions.
4.	Stall Detector Heater	C	1	0	May be inoperative provided the aircraft is not operated in known or forecast icing conditions.
5.	Alcohol Windshield Deice	C	1	0	May be inoperative provided the aircraft is not operated in known or forecast icing conditions.

NOTE:

AIRCRAFT OPERATING LIMITATIONS PROHIBIT FLIGHT INTO ICING CONDITIONS.
(Items 2 through 5)

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

31-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
			3.	NUMBER REQUIRED FOR DISPATCH	
31	INDICATING/RECORDING SYSTEMS				
1.	Clock with sweep second hand, or electric digital indicator	C	1	0	May be inoperative for VFR.
2.	Flight Hour Recorder	C	1	0	(0)
3.	Flight Data Recorder (FDR) System	C	-	1	Any in excess of those required by FAR may be inoperative.
		A	-	0	May be inoperative provided: <ul style="list-style-type: none"> a) Cockpit Voice Recorder (CVR) operates normally, b) Airplane is not dispatched from a designated airport as listed in the operator's MEL unless: <ul style="list-style-type: none"> 1) The FDR failure occurs after pushback but prior to takeoff, or 2) The FDR repair was attempted but was not successful. c) In those cases where repair is attempted but not successful, the aircraft may be dispatched on a flight or series of flights until the next designated airport where repair must be accomplished prior to dispatch, and d) Repairs are made within three flight days.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

33-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
33	LIGHTS				
1.	Cockpit & Instrument Lighting System	C	-	-	Individual lights may be inoperative provided remaining lights are: a) Sufficient to clearly illuminate all required instruments, controls, and other devices for which it is provided, b) Positioned so that direct rays are shielded from flight crewmembers eyes, and c) Lighting configuration and intensity is acceptable to flight crew.
2.	Cabin Lights	C	-	-	May be inoperative provided lighting configuration is acceptable to the flight crew.
3.	Anticollision Light System	B	1	0	May be inoperative provided airplane is not operated at night.
		C	1	0	May be inoperative provided strobe lights are installed and operate normally.
					NOTE: The strobe light system must be approved and certificated as an Anticollision Light System if used in place of a rotating beacon.
4.	Landing Lights	C	2	0	May be inoperative for day operations.
5.	Position Lights	C	3	0	May be inoperative for day operations.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

33-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
33	LIGHTS				
6.	Wing Ice Light	C	1	0	May be inoperative provided a portable lamp/light of adequate capacity for wing and/or control surface inspection is available for night operations in icing conditions.
7.	Taxi Light	C	1	0	May be inoperative for day operations.
8.	Strobe Light *** System	C	1	0	May be inoperative: a) For day operations. b) For night operations provided system is not the only approved anticollision light system.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
1.	Altimeter, adjustable for barometric pressure	B	2	1	May be inoperative on right side for day VMC. NOTE: Where a servoed electric altimeter is installed, a functioning pneumatic indicator is required.
2.	Airspeed Indicator	C	2	1	May be inoperative on right side for day VMC. NOTE: Where a servoed electric airspeed is installed, a functioning pneumatic indicator is required.
3.	Gyroscopic Pitch and Bank Indicator System	B	2	1	May be inoperative on right side for day VMC.
4.	ATC Transponders and Automatic Altitude Reporting Systems	C	-	0	May be inoperative provided: a) Enroute operations do not require its use, and b) Prior to flight, approval is obtained from ATC facilities having jurisdiction over the planned route of flight.
		D	-	1	Any in excess of those required by FAR may be inoperative.
5.	Navigation Equipment (VOR/ILS, Loran, Omega/VLF, INS, Doppler, GPS, RNAV)	C	-	-	As required by FAR.
6.	Weather Radar/ Thunderstorm Detection Equipment	C	1	0	As required by FAR.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
7.	Marker Beacon	C	1	0	May be inoperative provided approach procedure does not require its use.
8.	Distant Measuring Equipment (DME) Systems	D	-	-	Any in excess of those required by FAR may be inoperative.
9.	ADF	C	1	0	As required by FAR.
10.	RMI	C	1	0	
11.	Altitude Encoder				Combined with ATC Transponders, Revision 4.
12.	Radar Altimeter	C	1	0	NOTE:May affect GPWS.
13.	Vertical Speed Indicator	B	1	0	Must be operative on left side for IFR passenger carrying operations.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-3

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
14.	Nonstabilized Magnetic (Standby) Compass	B	1	0	May be inoperative provided any combination of three gyro or INS (IRU) stabilized compass systems are operative.
		B	1	0	May be inoperative provided: a) Any combination of two gyro or INS stabilized compass systems are operative, and b) Aircraft is operated with dual independent navigation capability and under positive radar control by ATC on the en route portion of the flight.
		B	1	0	May be inoperative for flights that are entirely within areas of magnetic unreliability provided at least two Stabilized Directional Gyro Systems are installed, operate normally, and used in conjunction with approved Free Gyro Techniques.
15.	Altitude Alerting *** System	A	-	0	(O) May be inoperative provided: a) Autopilot with altitude hold is operative, b) Enroute operations do not require its use, and c) Repairs are made within three flight days.
		C	-	0	May be inoperative provided it is not required by FAR.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-4

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
16.	Traffic Alert and *** Collision Avoidance System (TCAS I)	B	-	0	(M) (O) May be inoperative provided: a) System is deactivated and secured, and b) Enroute or approach procedures do not require its use.
		C	-	0	(M) (O) May be inoperative provided: a) Not required by FAR, b) System is deactivated and secured, and c) Enroute or approach procedures do not require its use.
17.	Traffic Alert and *** Collision Avoidance System (TCAS II)	B	-	0	(M) May be inoperative provided: a) System is deactivated and secured, and b) Enroute or approach procedures do not require its use.
		C	-	0	(M) (O) May be inoperative provided: a) Not required by FAR, b) System is deactivated and secured, and c) Enroute or approach procedures do not require its use.
1)	Combined Traffic Alert (TA) and Resolution Advisory (RA) Dual Display	C	2	1	May be inoperative on the non-flying pilot side provided: a) TA and RA visual display is operative on the flying pilot side, and b) TA and RA audio function is operative on flying pilot side.

(CON'T.)

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-5

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
	(CON'T.)				
17.	Traffic Alert and *** Collision Avoidance System (TCAS II)				
2)	Resolution Advisory (RA) Display System(s)	C	2	1	May be inoperative on non-flying pilot side.
		C	-	0	(O) May be inoperative provided: a) Traffic Alert (TA) visual display and audio functions are operative, b) TA only mode is selected by the crew, and c) Enroute or approach procedures do not require its use.
3)	Traffic Alert Display System(s)	C	-	0	(O) May be inoperative provided: a) RA visual display and audio functions are operative, and b) Enroute or approach procedures do not require its use.
18.	Ground Proximity *** Warning System (GPWS)	A	-	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within two flight days.
		C	-	0	(O) May be inoperative provided: a) It is not required by FAR, and b) Alternate procedures are established and used.
	(CON'T.)				

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-6

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
	(CON'T.)				
18.	Ground Proximity *** Warning System (GPWS)				
	1) Modes 1-4	A	- 0	(0)	May be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within two flight days.
		C	- 0	(0)	May be inoperative provided: a) It is not required by FAR, and b) Alternate procedures are established and used.
	2) Test Mode	A	1 0		May be inoperative provided: a) GPWS is considered inoperative, and b) Repairs are made within two flight days.
		C	- 0		May be inoperative provided: a) It is not required by FAR, and b) GPWS is considered inoperative.
	3) Glideslope Deviation (Mode 5)	B	2 0		
		C	2 0		May be inoperative provided it is not required by FAR.
	(CON'T.)				

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-7

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
	(CON'T.)				
18.	Ground Proximity *** Warning System (GPWS)				
	4) Advisory Callouts ***	C	- 0		(0) May be inoperative provided alternate procedures are established and used.
	5) Windshear Mode	C	- 0		(0) May be inoperative provided: a) Alternate procedures are established and used, and b) Windshear Detection and Avoidance System operates normally.
		C	- 0		(0) May be inoperative provided: a) Alternate procedures are established and used, and b) Takeoffs and landings are not conducted in known or forecast windshear conditions.
	6) TAWS ***	C	- 0		

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-8

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
19.	Windshear Detection, *** Guidance, and Avoidance System				
1)	Windshear Warning and Flight Guidance System	C	- 0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Windshear Detection and Avoidance System operates normally.	
		C	- 0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Takeoffs and landings are not conducted in known or forecast windshear conditions.	
2)	Windshear Detection and Avoidance System	C	- 0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Windshear Warning and Guidance System operates normally.	
		C	- 0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Takeoffs and landings not conducted in known or forecast windshear conditions.	

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

34-9

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
20. ***	Flight Management System Navigation Databases	C	-	-	(0) May be out of currency provided: a) Current Aeronautical Charts are used to verify Navigation Fixes prior to dispatch, b) Procedures are established and used to verify status and suitability of Navigation Facilities used to define route of flight, and c) Approach Navigation Radios are manually tuned and identified.
21. ***	Navigation Management System Navigation Databases	C	-	-	(0) May be out of currency provided: a) Current Aeronautical Charts are used to verify Navigation Fixes prior to dispatch, b) Procedures are established and used to verify status and suitability of Navigation Facilities used to define route of flight, and c) Approach Navigation Radios are manually tuned and identified.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

35-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
35	OXYGEN				
1.	Oxygen System (Passengers)	C	-	-	As required by FAR.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

37-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
37	VACUUM/PRESSURE				
1.	Vacuum Pump	C	2	1	(M) One may be inoperative for day VFR flights.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

61-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
61	PROPELLERS				
1.	Propeller Synchrophaser/ Synchronizer	C	1	0	

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 5

PAGE:

PARTENAVIA P68 SERIES

DATE: 09/30/2002

77-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
77	ENGINE INDICATING				
1.	Economy Mixture Indicators (EGT) (Except AP68TP)	C	1	0	