

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION
WASHINGTON, D.C.

Revision: 11
Date: 09/15/2003

M A S T E R M I N I M U M E Q U I P M E N T L I S T

SIKORSKY HELICOPTER
S-61L, S-61N

Federal Aviation Administration
FORT WORTH, TX 76193-0270

TELEPHONE: (817) 222-5270
FAX (817) 222-5295

SIKORSKY HELICOPTER
S-61L, S-61N

Table of Contents

SYSTEM NO.	SYSTEM	PAGE
--	Table of Contents	I
--	Log of Revisions	II
--	Control Page	III
--	Highlights of Change	IV
--	Definitions	V, VI, VII, VIII
--	Definitions	IX, X, XI, XII
--	Preamble	XIII, XIV
--	Guidelines for (O) & (M) Procedures	XV
21	Air Conditioning	21-1
23	Communications	23-1, 2
24	Electrical Power	24-1
25	Equipment/Furnishings	25-1
26	Fire Protection	26-1
28	Fuel	28-1, 2
30	Ice and Rain Protection	30-1
31	Indicating/Recording Systems	31-1
32	Landing Gear	32-1
33	Lights	33-1, 2
34	Navigation	34-1, 2
52	Doors	52-1
65	Rotors	65-1
73	Engine Fuel & Control	73-1
77	Engine Indicating	77-1
79	Engine Oil	79-1

SIKORSKY HELICOPTER
S-61L, S-61N

Log of Revisions

REV.NO.	DATE	PAGE NUMBERS	INITIALS
8	1/22/72	Complete revision	
9	9/16/88	All pages (4 column format)	
10	11/14/1989	ALL PAGES	
10a	08/30/1994	HIGHLIGHTS OF REV., DEFINITIONS	
10a	08/30/1994	PREAMBLE	
10a	08/30/1994	21-1, 23-1, 24-1, 25-1, 26-1	
10a	08/30/1994	28-1, 30-1, 31-1, 33-1, 34-1	
10a	08/30/1994	34-2, 52-1, 65-1, 73-1, 77-1	
10a	08/30/1994	79-1	
11	09/15/2003	HIGHLIGHTS OF REV., DEFINITIONS	
11	09/15/2003	GUIDELINES	
11	09/15/2003	23-2, 24-1, 25-1, 28-2, 30-1	
11	09/15/2003	32-1, 33-1, 33-2, 34-1, 34-2	
11	09/15/2003	65-1	

SIKORSKY HELICOPTER
S-61L, S-61N

Control Page

SYSTEM	PAGE	REV NO.	CURRENT DATE
Cover Page	-	11	09/15/2003
Table of Contents	I	11	09/15/2003
Log of Revisions	II	11	09/15/2003
Control Page	III	11	09/15/2003
Highlights of Change	IV	11	09/15/2003
Definitions	V	6	01/31/1995
	VI	6	01/31/1995
	VII	6	01/31/1995
	VIII	6	01/31/1995
	IX	6	01/31/1995
	X	6	01/31/1995
	XI	6	01/31/1995
	XII	6	01/31/1995
Preamble	XIII	2	06/14/1989
	XIV	2	06/14/1989
Guidelines for (O) & (M) Procedures	XV	11	09/15/2003
21	21-1	10 a	08/30/1994
23	23-1	10 a	08/30/1994
	23-2	11	09/15/2003
24	24-1	11	09/15/2003
25	25-1	11	09/15/2003
26	26-1	10 a	08/30/1994
28	28-1	10 a	08/30/1994
	28-2	11	09/15/2003
30	30-1	11	09/15/2003
31	31-1	10 a	08/30/1994
32	32-1	11	09/15/2003
33	33-1	11	09/15/2003
	33-2	11	09/15/2003
34	34-1	11	09/15/2003
	34-2	11	09/15/2003
52	52-1	10 a	08/30/1994
65	65-1	11	09/15/2003
73	73-1	10 a	08/30/1994
77	77-1	10 a	08/30/1994
79	79-1	10 a	08/30/1994

SIKORSKY HELICOPTER
S-61L, S-61N

Highlights of Change

REVISION 11

1. Revised fax number on cover page.
2. ATA 23 item 5 Provided relief for Hoist Operator ICS.
3. ATA 24 item 5 Provided relief for Alternate Battery.
4. ATA 25 item 7 Provided relief for Sonic Locator.
5. ATA 28 item 3 Provided relief for Emergency Fuel Jettison System.
6. ATA 28 item 4 Provided relief for Pressure Refueling System.
7. ATA 30 item 5 Provided relief for Windshield Heaters.
8. ATA 32 item 1 Provided relief for Landing Gear Retraction System.
9. ATA 32 item 2 Provided relief for Landing Gear Warning System.
10. ATA 33 item 9 Provided relief for High Visibility Pulse Light System.
11. ATA 34 item 18 Provided relief for Traffic Alert/Advisory Systems.
12. ATA 34 item 19 Provided relief for Supplemental Navigation Displays.
13. ATA 65 item 1 Deleted relief for Triple Tachometer.
14. ATA 65 item 3 Provided relief for Cockpit BIM (CBIM) System.

SIKORSKY HELICOPTER
S-61L, S-61N

Definitions

1. System Definitions.

System numbers are based on the Air Transport Association (ATA) Specification Number 100 and items are numbered sequentially.

- a. "Item" (Column 1) means the equipment, system, component, or function listed in the "Item" column.
- b. "Number Installed" (Column 2) is the number (quantity) of items normally installed in the aircraft. This number represents the aircraft configuration considered in developing this MMEL. Should the number be a variable (e.g., passenger cabin items) a number is not required.
- c. "Number Required for Dispatch" (Column 3) is the minimum number (quantity) of items required for operation provided the conditions specified in Column 4 are met.

NOTE: Where the MMEL shows a variable number required for dispatch, the MEL must reflect the actual number required for dispatch or an alternate means of configuration control approved by the Administrator.

- d. "Remarks or Exceptions" (Column 4) in this column includes a statement either prohibiting or permitting operation with a specific number of items inoperative, provisos (conditions and limitations) for such operation, and appropriate notes.
- e. A vertical bar (change bar) in the margin indicates a change, addition or deletion in the adjacent text for the current revision of that page only. The change bar is dropped at the next revision of that page.

2. "Airplane/Rotorcraft Flight Manual" (AFM/RFM) is the document required for type certification and approved by the responsible FAA Aircraft Certification Office. The FAA approved AFM/RFM for the specific aircraft is listed on the applicable Type

SIKORSKY HELICOPTER
S-61L, S-61N

Definitions

Certificate Data Sheet.

3. "As required by FAR" means that the listed item is subject to certain provisions (restrictive or permissive) expressed in the Federal Aviation Regulations operating rules. The number of items required by the FAR must be operative. When the listed item is not required by FAR it may be inoperative for time specified by repair category.

4. Each inoperative item must be placarded to inform and remind the crewmembers and maintenance personnel of the equipment condition.

NOTE: To the extent practical, placards should be located adjacent to the control or indicator for the item affected; however, unless otherwise specified, placard wording and location will be determined by the operator.

5. "-" symbol in Column 2 and/or Column 3 indicates a variable number (quantity) of the item installed.

6. "Deleted" in the remarks column after a sequence item indicates that the item was previously listed but is now required to be operative if installed in the aircraft.

7. "ER" refers to extended range operations of a two-engine airplane which has a type design approval for ER operations and complies with the provisions of Advisory Circular 120-42A. |

8. "Federal Aviation Regulations" (FAR) means the applicable portions of the Federal Aviation Act and Federal Aviation Regulations.

9. "Flight Day" means a 24 hour period (from midnight to midnight) either Universal Coordinated Time (UCT) or local time, as established by the operator, during which at least one flight is initiated for the affected aircraft.

10. "Icing Conditions" means an atmospheric environment that may cause ice to form on the aircraft or in the engine(s).

11. Alphabetical symbol in Column 4 indicates a proviso (condition or limitation) that must be complied with for

SIKORSKY HELICOPTER
S-61L, S-61N

Definitions

operation with the listed item inoperative.

12. "Inoperative" means a system and/or component malfunction to the extent that it does not accomplish its intended purpose and/or is not consistently functioning normally within its approved operating limit(s) or tolerance(s).

13. "Notes:" in Column 4 provides additional information for crewmember or maintenance consideration. Notes are used to identify applicable material which is intended to assist with compliance, but do not relieve the operator of the responsibility for compliance with all applicable requirements. Notes are not a part of the provisos.

14. Inoperative components of an inoperative system: Inoperative items which are components of a system which is inoperative are usually considered components directly associated with and having no other function than to support that system. (Warning/caution systems associated with the inoperative system must be operative unless relief is specifically authorized per the MMEL).

15. "(M)" symbol indicates a requirement for a specific maintenance procedure which must be accomplished prior to operation with the listed item inoperative. Normally these procedures are accomplished by maintenance personnel; however, other personnel may be qualified and authorized to perform certain functions. Procedures requiring specialized knowledge or skill, or requiring the use of tools or test equipment should be accomplished by maintenance personnel. The satisfactory accomplishment of all maintenance procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are required to be published as part of the operator's manual or MEL.

16. "(O)" symbol indicates a requirement for a specific operations procedure which must be accomplished in planning for and/or operating with the listed item inoperative. Normally these procedures are accomplished by the flight crew; however, other personnel may be qualified and authorized to perform certain functions. The satisfactory accomplishment of all procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are

SIKORSKY HELICOPTER
S-61L, S-61N

Definitions

required to be published as a part of the operator's manual or MEL.

NOTE: The (M) and (O) symbols are required in the operator's MEL unless otherwise authorized by the Administrator.

17. "Deactivated" and "Secured" means that the specified component must be put into an acceptable condition for safe flight. An acceptable method of securing or deactivating will be established by the operator.

18. "Visual Flight Rules" (VFR) is as defined in FAR Part 91. This precludes a pilot from filing an Instrument Flight Rules (IFR) flight plan.

19. "Visual Meteorological Conditions" (VMC) means the atmospheric environment is such that would allow a flight to proceed under the visual flight rules applicable to the flight. This does not preclude operating under Instrument Flight Rules.

20. "Visible Moisture" means an atmospheric environment containing water in any form that can be seen in natural or artificial light; for example, clouds, fog, rain, sleet, hail, or snow.

21. "Passenger Convenience Items" means those items related to passenger convenience, comfort or entertainment such as, but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps, etc.

22. Repair Intervals: All users of an MEL approved under FAR 121, 125, 129 and 135 must effect repairs of inoperative systems or components, deferred in accordance with the MEL, at or prior to the repair times established by the following letter designators:

Category A. Items in this category shall be repaired within the time interval specified in the remarks column of the operator's approved MEL.

Category B. Items in this category shall be repaired within three (3) consecutive calendar days (72 hours), excluding the day the malfunction was recorded in the aircraft maintenance

SIKORSKY HELICOPTER
S-61L, S-61N

Definitions

record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the three day interval would begin at midnight the 26th and end at midnight the 29th.

Category C. Items in this category shall be repaired within ten (10) consecutive calendar days (240 hours), excluding the day the malfunction was recorded in the aircraft maintenance record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the 10 day interval would begin at midnight the 26th and end at midnight February 5th.

Category D. Items in this category shall be repaired within one hundred and twenty (120) consecutive calendar days (2880 hours), excluding the day the malfunction was recorded in the aircraft maintenance log and/or record.

The letter designators are inserted adjacent to Column 2.

23. Electronic fault alerting system - General

New generation aircraft display system fault indications to the flight crew by use of computerized display systems. Each aircraft manufacturer has incorporated individual design philosophies in determining the data that would be represented. The following are customized definitions (specific to each manufacturer) to help determine the level of messages affecting the aircraft's dispatch status. When preparing the MEL document, operators are to select the proper Definition No. 23 for their aircraft, if appropriate.

a. BOEING (B-757/767, B-747-400, B-777)

Boeing airplanes equipped with Engine Indicating and Crew Alerting Systems (EICAS), provide different priority levels of system messages (WARNING, CAUTION, ADVISORY, STATUS and MAINTENANCE). Any messages that affects airplane dispatch status will be displayed at a STATUS message level or higher. The absence of an EICAS STATUS or higher level (WARNING, CAUTION, ADVISORY) indicates that the system/component is operating within its approved operating limits or tolerances.

System conditions that result only in a maintenance level message, i.e. no correlation with a higher level EICAS message,

SIKORSKY HELICOPTER
S-61L, S-61N

Definitions

do not affect dispatch and do not require action other than as addressed within an operators standard maintenance program.

b. DOUGLAS (MD-11)

Some Douglas aircraft are equipped with an alerting function which is a subsystem within the Electronic Instrument System (EIS). The alerting function provides various levels of system condition alerts (WARNING, CAUTION, ADVISORY, MAINTENANCE and STATUS).

Alerts that affect aircraft dispatch will include WARNING, CAUTION, STATUS or MAINTENANCE level. MAINTENANCE alerts are displayed on the status page of the EIS display panel under the maintenance heading.

A MAINTENANCE alert on the EIS indicates the presence of a system fault which can be identified by the Central Fault Display System (CFDS) interrogation. The systems are designed to be fault tolerant, however, for any MAINTENANCE alert, the MEL must be verified for dispatch purposes.

c. AIRBUS (A-300-600, A-310, A-320/319/321, A-330, A-340)

Airbus aircraft equipped with Electronic Centralized Aircraft Monitoring (ECAM) provide different levels of system condition messages (WARNING, CAUTION, STATUS, and ADVISORY). A-320/319/321, A-330, and A-340 also provide MAINTENANCE status messages.

Any message that effects airplane dispatchability will normally be at the WARNING, CAUTION or STATUS level. MAINTENANCE messages (A-320/319/321, A-330, and A-340 only) are also indicated on ECAM Status Page below the white Maintenance label.

A MAINTENANCE status (Class II) message on ECAM indicates the presence of a system fault which can be identified by CFDS (A-320/319/321) or CMS (A-330/A-340) interrogation. The systems are designed to be fault tolerant, however for any MAINTENANCE status (Class II) message, the A-320/319/321 MEL must be verified for dispatch capability. For the A-330 and A-340, MAINTENANCE status messages do not affect dispatch.

d. FOKKER (FK-100)

SIKORSKY HELICOPTER
S-61L, S-61N

Definitions

Fokker aircraft are equipped with Multi Function Display System (MFDS) which provides electronic message referring to the different priority levels of system information (WARNING (red), CAUTION (amber), AWARENESS (cyan) AND STATUS (white). Any messages that affects aircraft dispatch will be at the WARNING, CAUTION or AWARENESS level. In these cases the MEL must be verified for dispatch capability and maintenance may be required.

System conditions that only require maintenance are not presented on the flight deck. These maintenance indications/messages may be presented on the Maintenance & Test Panel (MAP) or the Centralized Fault Display Unit (CFDU) and by dedicated Built In Test Evaluation (BITE) of systems.

24. "Administrative control item" means an item listed by the operator in the MEL for tracking and informational purposes. It may be added to an operator's MEL by approval of the Principal Operations Inspector provided no relief is granted, or provided conditions and limitations are contained in an approved document (i.e. Structural Repair Manual, airworthiness directive, etc.). If relief other than that granted by an approved document is sought for an administrative control item, a request must be submitted to the Administrator. If the request results in review and approval by the FOEB, the item becomes an MMEL item rather than an administrative control item.

25. "****" symbol in Column 1 indicates an item which is not required by regulation but which may have been installed on some models of aircraft covered by this MMEL. This item may be included on the operator's MEL after the approving office has determined that the item has been installed on one or more of the operator's aircraft. The symbol, however, shall not be carried forward into the operator's MEL. It should be noted that neither this policy nor the use of this symbol provide authority to install or remove an item from an aircraft.

26. "Excess Items" means those items that have been installed that are redundant to the requirements of the FARs.

27. "Day of Discovery" is the calendar day an equipment/instrument malfunction was recorded in the aircraft

SIKORSKY HELICOPTER

S-61L, S-61N

Definitions

maintenance log and or record. This day is excluded from the calendar days or flight days specified in the MMEL for the repair of an inoperative item of equipment. This provision is applicable to all MMEL items, i.e., categories "A, B, C, and D."

SIKORSKY HELICOPTER
S-61L, S-61N

Preamble
(Effective 6/14/89)

The following is applicable for authorized certificate holders operating under Federal Aviation Regulations (FAR) Parts 121, 125, 129, 135: The FAR require that all equipment installed on an aircraft in compliance with the Airworthiness Standards and the Operating Rules must be operative. However, the Rules also permit the publication of a Minimum Equipment List (MEL) where compliance with certain equipment requirements is not necessary in the interests of safety under all operating conditions. Experience has shown that with the various levels of redundancy designed into aircraft, operation of every system or installed component may not be necessary when the remaining operative equipment can provide an acceptable level of safety. A Master Minimum Equipment List (MMEL) is developed by the FAA, with participation by the aviation industry, to improve aircraft utilization and thereby provide more convenient and economic air transportation for the public. The FAA approved MMEL includes those items of equipment related to airworthiness and operating regulations and other items of equipment which the Administrator finds may be inoperative and yet maintain an acceptable level of safety by appropriate conditions and limitations; it does not contain obviously required items such as wings, flaps, and rudders. The MMEL is the basis for development of individual operator MELs which take into consideration the operator's particular aircraft equipment configuration and operational conditions. Operator MELs, for administrative control, may include items not contained in the MMEL; however, relief for administrative control items must be approved by the Administrator. An operator's MEL may differ in format from the MMEL, but cannot be less restrictive than the MMEL. The individual operator's MEL, when approved and authorized, permits operation of the aircraft with inoperative equipment.

Equipment not required by the operation being conducted and equipment in excess of FAR requirements are included in the MEL with appropriate conditions and limitations. The MEL must not deviate from the Aircraft Flight Manual Limitations, Emergency Procedures or with Airworthiness Directives. It is important to remember that all equipment related to the airworthiness and the operating regulations of the aircraft not listed on the MMEL must be operative.

SIKORSKY HELICOPTER
S-61L, S-61N

Preamble
(Effective 6/14/89)

Suitable conditions and limitations in the form of placards, maintenance procedures, crew operating procedures and other restrictions as necessary are specified in the MEL to ensure that an acceptable level of safety is maintained.

The MEL is intended to permit operation with inoperative items of equipment for a period of time until repairs can be accomplished. It is important that repairs be accomplished at the earliest opportunity. In order to maintain an acceptable level of safety and reliability the MMEL establishes limitations on the duration of and conditions for operation with inoperative equipment. The MEL provides for release of the aircraft for flight with inoperative equipment. When an item of equipment is discovered to be inoperative, it is reported by making an entry in the Aircraft Maintenance Record/Logbook as prescribed by FAR. The item is then either repaired or may be deferred per the MEL or other approved means acceptable to the Administrator prior to further operation. MEL conditions and limitations, do not relieve the operator from determining that the aircraft is in condition for safe operation with items of equipment inoperative.

When these requirements are met, an Airworthiness Release, Aircraft Maintenance Record/Logbook entry, or other approved documentation is issued as prescribed by FAR. Such documentation is required prior to operation with any item of equipment inoperative.

Operators are responsible for exercising the necessary operational control to ensure that an acceptable level of safety is maintained. When operating with multiple inoperative items, the interrelationships between those items and the effect on aircraft operation and crew workload will be considered.

Operators are to establish a controlled and sound repair program including the parts, personnel, facilities, procedures, and schedules to ensure timely repair.

WHEN USING THE MEL, COMPLIANCE WITH THE STATED INTENT OF THE PREAMBLE, DEFINITIONS, AND THE CONDITIONS AND LIMITATIONS SPECIFIED IN THE MEL IS REQUIRED.

SIKORSKY HELICOPTER

S-61L, S-61N

Guidelines for (O) & (M) Procedures

The FOEB has identified a need for certain procedures to provide an adequate level of safety while providing relief for some items. Those procedures must be established by the operator. The following guidelines specify the objectives of the required procedures:

- 21-3 (M) Procedure to deactivate and secure system.
- 23-2a (O) Alternate procedure to notify passengers.
- 24-5 (M) Procedure for securing or removing the Alternate Battery.
- 28-2 (O) Alternate fuel management procedure.
- 28-3 (M) Procedure for deactivating and securing the Emergency Fuel Jettison System.
- 32-1 (M) Procedure for securing the Landing Gear Retraction System.
- 32-2 (M) Procedure for securing the Landing Gear Warning System.
- 33-8b (O) Alternate procedure to notify passengers.
- 34-18 (M) Procedure for deactivating and securing the Traffic Alert/Advisory Systems.
- 65-3 (O) Procedure for visual check of the BIM System.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

21-1

SYSTEM & SEQUENCE NUMBERS	ITEM	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
		1.	3. NUMBER REQUIRED FOR DISPATCH	
21	AIR CONDITIONING			
21	AIR CONDITIONING			
1.	Blower, Fresh Air (Aux. Vent)	C	-	0
2.	Blower, (Cabin Heater)	C	1	0
				May be inoperative for VFR flight provided: a. Heater is not required, b. Equivalent air flow is insured by other means, and c. Cockpit windshield and window frosting or fogging conditions are not present.
3.	Air Conditioning System	C	-	0
				(M) May be inoperative provided system is deactivated and secured.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

23-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
23	COMMUNICATIONS				
1.	Communication Systems (FM, HF, UHF, VHF, etc.)	C	-	0	As required by FAR.
2.	Cabin Public Address System	A	-	0	(O)May be inoperative provided: a) Alternate normal and emergency procedures and/or operating restrictions are established and utilized for passenger notification, and b) Aircraft may continue flight or a series of flights for a maximum of 15 hours, but shall not depart airport where repairs or replacements can be made. OR c) For nonpassenger carrying operations.
		C			
3.	Cockpit Voice Recorder (CVR) System				
	1) When FDR is not required	A	1	0	May be inoperative provided repairs are made within three flight days.
	2) When FDR is required	B	1	0	May be inoperative provided Flight Data Recorder is installed and operative.
4.	Flight Data Recorder (FDR)	B	1	0	May be inoperative provided Cockpit Voice Recorder is installed and operative.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

23-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
23	COMMUNICATIONS				
5.	Hoist Operator	C	-	0	May be inoperative provided hoist
***	ICS				operations are not conducted.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

24-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
24	ELECTRICAL POWER				
1.	Voltmeter, A.C.	C	-	0	
2.	Inverter	B	1	0	May be inoperative provided: a. Ext. A.C. power is utilized for starting and shutdown, and b. A.C. generators are kept on line at en-route stops.
3.	Transformer Rectifier Unit	B	-	1	
5. ***	Alternate Battery	C	-	0	(M) May be inoperative provided: a. Battery is disconnected and secured, and b. Battery remains installed. OR c. If battery is removed and appropriate ballast is installed OR d. If battery is removed, weight and balance is revised.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

25-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
25	EQUIPMENT/FURNISHINGS				
25	EQUIPMENT/FURNISHINGS				
1.	Passenger Seat Belts	C	-	0	One required for each occupied seat. If belt is inoperative or missing, seat must be blocked and placarded.
2.	Emergency Locator Transmitter (ELT)	C	-	0	
3.	Passenger Convenience Item(s)		-	0	Passenger convenience items, as expressed in this MMEL, are those related to passenger convenience, comfort, or entertainment such as, but not limited to, galley equipment, ash trays, stereo equipment, overhead reading lamps, etc. Items addressed elsewhere in this document shall not be included. (M) and (O) procedures may be required and included in the air carrier's appropriate document.
4.	Cargo Suspension System	C	-	0	
5.	Hoist System	C	-	0	
6.	EMS Equipment	C	-	0	May be inoperative provided system is deactivated and secured. (M) and (O) procedures may be required and included in the air carrier's appropriate document.
7.	Sonic Locator	C	-	0	

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

26-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
				3. NUMBER REQUIRED FOR DISPATCH	
26	FIRE PROTECTION				
26	FIRE PROTECTION				
1.	Heater Overheat Light	C	1	0	May be inoperative provided heater is not operated.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

28-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
28	FUEL				
28	FUEL				
1.	Fuel Boost Pumps	C	4	0	May be inoperative provided RFM limitations are complied with.
2.	Fuel Quantity Indicators				
1)	Forward and Aft Tank Indicators	B	2	1	(O)One may be inoperative for VFR provided: <ul style="list-style-type: none"> a. At each subsequent refueling, respective tank is filled to next higher fuel level with pressure refueling or to full tank when pressure refueling is not available, b. No fuel leaks are evident, c. A fuel management procedure (monitoring of fuel flow vs flight time) is established to assure pilot of quantity of fuel remaining at all times, d. Maximum allowable takeoff gross weight is reduced by 200 lbs, and e. Aircraft shall not depart on originating flight of a day's schedule.
2)	Center Tank Indicator	C	-	0	(O)May be inoperative provided a fuel management procedure (monitoring of fuel flow vs flight time) is established to assure pilot of quantity of fuel remaining at all times.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

28-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
28	FUEL				
3. ***	Emergency Fuel Jettison System (STC SR09218RC)	C	-	0	(M) May be inoperative provided system is deactivated and secured.
4. ***	Pressure Refueling System	C	-	0	May be inoperative if pressure refueling is not required.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

30-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
30	ICE AND RAIN PROTECTION					
1.	Windshield Wipers	C	2	0		May be inoperative provided operations are not conducted in precipitation during the takeoff and landing phases.
2.	Pitot Heaters	B	2	0		May be inoperative for VFR flight unless precipitation or icing conditions are known or forecast.
3.	Engine Bellmouth Anti-Icing System	C	2	0		May be inoperative for VFR provided: a) RFM OAT limitations for inoperative Engine Bellmouth Anti-Icing System are observed, and b) Precipitation or icing conditions are not known or forecast.
4.	Engine Inlet Guide Vane Anti-Icing System	C	2	0		May be inoperative for VFR provided: a) OAT is not below 50 degrees F (10 degrees C), and b) Appropriate "anti-icing on" performance charts are utilized.
5.	Windshield Heaters ***	C	-	-		May be inoperative provided: a) Blower (Item 21-2) is operative, and b) Defogging vents are not obstructed.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

31-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1. 2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
31	INDICATING/RECORDING SYSTEMS				
1.	Clock Displaying Hours, Minutes, and Seconds with Sweep- Second Pointer or Digital Presentation	C	-	1	Operative clock must be located on the instrument panel in a position that makes it plainly visible to, and usable by, any pilot at the pilot's station.
		C	-	0	May be inoperative for VFR provided Elapsed Timer is installed and operative.
2.	Elapsed Timer	C	-	0	May be inoperative provided Clock is operative.
3.	Hour Meter	C	-	0	
4.	Aircraft/Engine Monitoring System	C	-	0	
5.	Cockpit Voice Recorder				MOVED TO ATA CHAPTER 23
6.	Flight Data Recorder				MOVED TO ATA CHAPTER 23

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

32-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
32	LANDING GEAR				
1.	Landing Gear Retraction System (S-61N Model only)	C	1	0	(M) May be inoperative provided: a. Gear is secured down and locked, and b. Control lever is covered and placarded.
2.	Landing Gear Warning System (S-61N Model only)	C	1	0	(M) May be inoperative provided: a. Gear is secured down and locked, and b. Control lever is covered and placarded.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

33-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
33	LIGHTS				

1.	Cockpit Dome Light	C	1	0	May be inoperative provided both Pilot Map Lights are operative.
2.	Flight Instrument Light System	B	2	0	May be inoperative for day VFR.
3.	Engine Instrument Light System	B	1	0	May be inoperative for day VFR.
4.	Pilot Map Lights	C	2	1	One may be inoperative provided Cockpit Dome Light is operative.
5.	Navigation Lights	C	3	0	May be inoperative for day.
6.	Anti-Collision Lights	B	2	0	May be inoperative provided: a) For day VFR. OR b) One light is operative, c) One bulb is operative in other light, and d) Aircraft shall not depart airport where repairs or replacements can be made.
7.	Landing Lights	C	2	0	May be inoperative provided: a) For day VFR. OR b) One light is operative, and c) Aircraft shall not depart airport where repairs or replacements can be made.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

33-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
33	LIGHTS				

8.	Passenger Notice System (Fasten Seat Belt-No Smoking)	B	1	0	(O)May be inoperative provided: a) Passengers are not carried. OR b) Alternate procedures are used for passenger notification. OR c) Cabin Public Address System is installed and operative.
----	---	---	---	---	---

9.	High Visibility *** Pulse Light System	C	-	0	
----	--	---	---	---	--

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

34-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1. 2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
34	NAVIGATION				
1.	Air Speed Indicators				Deleted
2.	Altimeters				Deleted
3.	Attitude Gyro Indicators				Deleted
4.	Directional Gyro Indicators				Deleted
5.	Vertical Speed Indicators	B	2	1	One may be inoperative for VFR.
6.	Gyroscopic Rate of Turn Indicator	B	2	1	One may be inoperative provided Third Attitude Indicator is installed and operative.
7.	Slip and Skid Indicator	B	2	1	One may be inoperative for VFR.
8.	Third Attitude Indicator	B	-	0	May be inoperative for VFR provided both Gyroscopic Rate of Turn Indicators are operative.
9.	Navigation Systems (VOR, ILS, ADF, Long Range, etc.)	C	-	0	As required by FAR.
10.	Marker Beacon	C	-	0	May be inoperative provided approach is not predicated on its use.
11.	ATC Transponder	C	-	0	As required by FAR.
12.	Flight Director	C	-	0	

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

34-2

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION				
13.	Radio Altimeter System	C	-	0	As required by FAR.
14.	Weather Radar System	C	-	0	As required by FAR.
15.	Thunderstorm Detection System	C	-	0	As required by FAR.
16.	Altitude Encoding System	C	-	0	As required by FAR.
17.	DME	C	-	0	May be inoperative provided navigation is not predicated on its use.
18.	Traffic Alert/ *** Advisory Systems (i.e., TCAS, TCAD, TAS, etc.)	C	-	0	(M) May be inoperative provided system is deactivated and secured.
19.	Supplemental *** Navigation Displays (Moving Map, Radar Graphic, etc.)	C	-	0	May be inoperative provided navigation is not predicated on its use.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

52-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
52	DOORS				

1.	Door Warning Light System	C	1	0	May be inoperative provided it is determined by visual check that the doors are closed and locked.
----	---------------------------	---	---	---	--

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 11

PAGE:

DATE: 09/15/2003

65-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
65	ROTORS				
1.	Triple Tachometer				DELETED REVISION NO. 11
2.	Automatic Flight Control System (AFCS)	C	1	0	May be inoperative for VFR.
3.	Cockpit BIM (CBIM) *** System	B	-	0	(O) May be inoperative provided a visual check is made of the Visual BIM (VBIM) System in accordance with the RFM.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

73-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
73	ENGINE FUEL & CONTROL				

73	ENGINE FUEL & CONTROL				
----	-----------------------	--	--	--	--

1.	Low Fuel Pressure Indicator Lights	C	2	0	May be inoperative provided: a) Aircraft is operated below 5,000' pressure altitude, and b) Respective engine fuel boost system is operative and selected "ON."
----	------------------------------------	---	---	---	---

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

77-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
77	ENGINE INDICATING				

77	ENGINE INDICATING				
----	-------------------	--	--	--	--

1.	Gas Generator Tachometer System(Ng)	B	2	1	One may be inoperative provided: a. Engine start is not required, and b. Aircraft shall not depart airport where repairs or replacements can be made.
2.	Fuel Flow/ Monitoring System	B	-	0	

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

SIKORSKY HELICOPTER
S-61L, S-61N

REVISION NO: 10 a

PAGE:

DATE: 08/30/1994

79-1

SYSTEM & SEQUENCE NUMBERS	ITEM	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
79	ENGINE OIL				
1.	Pressure Warning Lights	C	2	0	

