



U.S. Department of Transportation
Federal Aviation Administration
Washington, DC

Master Minimum Equipment List (MMEL)

Revision: 7
Date: 03/12/2021

Bombardier Challenger **BD-100-1A10** **(Models CL-300 & CL-350)**

**** FOR 14 CFR PARTS 91, 125, and 135 OPERATIONS ONLY ****

Michael A. Nash, Chair
Flight Operations Evaluation Board (FOEB)

Federal Aviation Administration (FAA)
Long Beach Aircraft Evaluation Group (LGB-AEG)
3960 Paramount Blvd, Suite 100
Lakewood, CA 90712-4137

Telephone: (562) 627-5317
Fax: (562) 627-5210

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. I

AIRCRAFT:
 BD-100-1A10

TABLE OF CONTENTS AND CONTROL PAGE

SYSTEM NO.	SYSTEM	PAGE NO.	REV NO.	DATE
--	Cover Page	--	7	03/12/2021
--	Table of Contents and Control Page	I	7	03/12/2021
--	Highlights of Change	II thru III	7	03/12/2021
--	Definitions	IV	7	03/12/2021
--	Preamble	V	7	03/12/2021
Section One	Line Replaceable Unit (LRU) Component Relief	1-1	7	03/12/2021
21	Air Conditioning	21-1 thru 19	7	03/12/2021
22	Autoflight	22-1 thru 2	7	03/12/2021
23	Communications	23-1 thru 6	7	03/12/2021
24	Electrical Power	24-1 thru 3	7	03/12/2021
25	Equipment/Furnishings	25-1 thru 13	7	03/12/2021
26	Fire Protection	26-1 thru 2	7	03/12/2021
27	Flight Controls	27-1 thru 2	7	03/12/2021
28	Fuel	28-1 thru 4	7	03/12/2021
29	Hydraulic Power	29-1 thru 3	7	03/12/2021
30	Ice and Rain Protection	30-1 thru 7	7	03/12/2021
31	Indicating/Recording Systems	31-1 thru 10	7	03/12/2021
32	Landing Gear	32-1 thru 2	7	03/12/2021
33	Lights	33-1 thru 7	7	03/12/2021
34	Navigation	34-1 thru 12	7	03/12/2021
35	Oxygen	35-1 thru 2	7	03/12/2021
36	Pneumatic	36-1 thru 35	7	03/12/2021
38	Water/Waste	38-1	6	07/30/2018
45	Central Maintenance System	45-1	7	03/12/2021
46	Information Systems	46-1 thru 2	7	03/12/2021
49	Airborne Auxiliary Power	49-1	7	03/12/2021
52	Doors	52-1 thru 2	7	03/12/2021
73	Engine Fuel and Control	73-1	7	03/12/2021
74	Ignition	74-1	7	03/12/2021
76	Engine Control	76-1	Original	11/18/2003
77	Engine Indicating	77-1	1	11/26/2004
78	Engine Exhaust	78-1	7	03/12/2021
79	Engine Oil	79-1	7	03/12/2021
80	Starting	80-1	Original	11/18/2003
Section Two	Crew Alerting System (CAS) Message Relief	2-1	7	03/12/2021
--	Statement Page	2-2	6	07/30/2018
--	CAS Messages	2-3 thru 5	7	03/12/2021

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. II

AIRCRAFT:
 BD-100-1A10

HIGHLIGHTS OF CHANGE

The following changes are the Highlights of Changes for **Revision 7**.

PAGE NO.	EXPLANATION OF CHANGE
General	Minor editorial corrections and formatting changes were made throughout the document, indicated with change bars. These editorial corrections may be adopted in Minimum Equipment Lists (MEL) at the operator's discretion.
22-11-02	Relief condition for restriction of steep approach is added.
23-41-01	Missing note added as per the MMEL Policy Letter (PL) 9, Revision 12.
23-72-01	Added relief per FAA Policy Letter (PL) 9, Revision 12.
24-20-02	Removed "O" requirement.
24-31-01	Revised proviso "d" for clarity.
25-11-01	Modified proviso.
25-14-06	Updated relief to comply with Policy Letter (PL) 104, Revision 7.
25-14-08	Revised proviso for clarity and modified the NOTE.
25-14-09	New MMEL item introduced.
25-21-01	Changed "upright position" to "full upright position" in sub-item 1. Added "****" to sub-item 4.
25-61-01	Updated relief to comply with Policy Letter 120, Revision 3, GC.
25-62-03	Changed proviso.
26-11-01	Changed Note.
26-14-01	Relief condition for restriction of steep approach and Short field operations are added.
27-41-01	Amended Note.
29-12-02	Relief condition for restriction of steep approach and Short field operations are added.
30-10-06	Modified to include performance limitations from AFM.
31-31-02	New MMEL item introduced.
32-30-01	Changed Item name and modified proviso. Relief condition for restriction of steep approach and Short field operations are added.

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. III

AIRCRAFT:
 BD-100-1A10

HIGHLIGHTS OF CHANGE

PAGE NO.	EXPLANATION OF CHANGE
33-41-02	Modified proviso.
33-43-01	Modified proviso.
33-45-02	Updated relief to comply with Policy Letter 72, Rev 4 GC.
34-10-01	Updated relief.
34-30-01	New MMEL item introduced.
34-42-01	Glideslope Deviation (Mode 5) relief "B" is brought back after it was removed unintentionally.
34-43-01	Updated sub-item 1 to say "Combined Traffic Alert".
34-44-01	"Approach minimums or operating procedures do not" changed to "operating procedures are not". Relief condition for restriction of steep approach is added.
34-55-01	Re-instate dispatch with both GPS inoperative.
34-56-01	Updated relief to comply with Policy Letter 105, Revision 3, GC.
36-10-02	Updated proviso for sub-item 2, L/H Bleed Pressure Indication System.
45-45-01	Added "M" procedure to proviso.
46-10-01	New line item for Database Applications is added.
46-20-01	New MMEL item introduced.
49-11-01	Relief condition for restriction of steep approach is added.
52-70-01	Added "O" to proviso and modified proviso wording for clarity.
73-30-02	Changed "Quantity Gauging" to "Quantity Gaging".
74-21-01	Modified "Note" for clarity.
78-30-01	Relief condition for restriction of steep approach is added.

REVISION NO. 7
DATE: 03/12/2021

PAGE NO. IV

AIRCRAFT:
BD-100-1A10

DEFINITIONS

Insert definitions from Policy Letter PL 25 as revised.

REVISION NO. 7
DATE: 03/12/2021

PAGE NO. V

AIRCRAFT:
BD-100-1A10

PREAMBLE

Insert Preamble from Policy Letter PL-34, Rev 4 for 125 & 135 certificated holders, or PL-36, Rev 3 for Part 91 operators.

SECTION ONE

LINE REPLACEABLE UNIT (LRU) COMPONENT RELIEF

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
00-01	Integrated Air System Controller (IASC) (Cont'd) 2) Aircraft with SB 100-21-05, Aircraft 20101 and Subs a) IASC 1 Channel B b) IASC 2 Channel B	C	1	0	(O) May be inoperative provided: a) IASC 2 Channel B is operative, b) Left Bleed Loop is considered inoperative (36-20-01), c) Left High Pressure Valve is considered inoperative (30-10-01), and d) Operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	
		C	1	0	(O) May be inoperative provided: a) IASC 1 Channel B is operative, b) Trim Air System is considered inoperative (21-61-03), c) Right Bleed Loop is considered inoperative (36-20-01), d) Right High Pressure Valve is considered inoperative (30-10-01), and e) Operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
23-02	Avionics Cooling Valve	C	1	0	(M) May be inoperative provided: a) Valve is secured CLOSED, b) Avionics cooling fan is verified operative before each flight, and c) One Avionics Ventilation Temperature Sensor Element on each side is verified operative once each flight-day.	
23-03	Avionics Ventilated Temperature Sensors					
1)	L/H Avionics Ventilated Temperature Sensor Elements	C	2	1		
		C	2	0	(M) Any or all may be inoperative provided: a) One R/H Avionics Ventilated Temperature Sensor Element is verified operative once each flight-day, b) Avionics Cooling Valve is verified operative before each flight, and c) Avionics cooling fan is verified operative before each flight.	
2)	R/H Avionics Ventilated Temperature Sensor Elements	C	2	1		
		C	2	0	(M) Any or all may be inoperative provided: a) One L/H Avionics Ventilated Temperature Sensor Element is verified operative once each flight-day, b) Avionics Cooling Valve is verified operative before each flight, and c) Avionics cooling fan is verified operative before each flight.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
31-02	Safety Valves	C	2	0	(O) Any or all may be inoperative provided: a) PRESSURIZATION EMER DEPRESS switch is selected ON, and b) Operations are conducted unpressurized at or below 9000 ft. MSL.	
31-03	PRESSURIZATION MANUAL "ON" Switch Light (light function only)	C	1	0		
31-04	PRESSURIZATION EMER DEPRESS "ON" Switch Light (light function only)	C	1	0		
31-05	PRESSURIZATION DITCHING "ON" Switch Light (light function only)	C	1	0		
51-01	Flow Control Valves (FCV)					
	1) Aircraft 20003 to 20100 <u>without</u> SB 100-21-05	B	2	1	(M)(O) Left may be inoperative provided: a) Valve is secured CLOSED, b) Trim Air System is operative, c) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, d) Trim Air Inlet Temperature Sensor is operative, e) Right Bleed Loop is operative, f) Operational status of L/H Environmental Control Bleed Pressure Indication System is verified before each flight, g) Ram Air Valve is verified operative, h) Operations are conducted at or below FL 250, and i) Operations are conducted within one hour from a suitable airport.	

(Continued)

REVISION NO. 7

PAGE NO. 21-5

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
51-01	Flow Control Valves (FCV) (Cont'd) 1) Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)	B	2	1	(M)(O) Right may be inoperative provided: a) Valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, c) Pack Inlet Temperature Sensor is operative, d) Left Bleed Loop is operative, e) Operational status of R/H Environmental Control Bleed Pressure Indication System is verified before each flight, f) Ram Air Valve is verified operative, g) Operations are conducted at or below FL 250, and h) Operations are conducted within one hour from a suitable airport.	
		C	2	0	(M)(O) Any or all may be inoperative provided: a) Affected valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) Ram Air Valve is selected OPEN, d) PRESSURIZATION EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
51-01	Flow Control Valves (FCV) (Cont'd)					
	2) (Aircraft 20003 to 20100 <u>with</u> SB 100-21-05) Aircraft 20101 and subs	C	2	1	(M)(O) Left may be inoperative provided: a) Valve is secured CLOSED, b) Trim Air System is operative, c) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, d) Trim Air Inlet Temperature Sensor is operative, e) Right Bleed Loop is operative, f) Operational status of L/H Environmental Control Bleed Pressure Indication System is verified before each flight, g) Ram Air Valve is verified operative, h) Operations are conducted at or below FL 250, and i) Operations are conducted within one hour from a suitable airport.	
		C	2	1	(M)(O) Right may be inoperative provided: a) Valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, c) Pack Inlet Temperature Sensor is operative, d) Left Bleed Loop is operative, e) Operational status of R/H Environmental Control Bleed Pressure Indication System is verified before each flight, f) Ram Air Valve is verified operative, g) Operations are conducted at or below FL 250, and h) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
51-01	Flow Control Valves (FCV) (Cont'd)					
	2) (Aircraft 20003 to 20100 <u>with</u> SB 100-21-05) Aircraft 20101 and subs (Cont'd)	C	2	0	(M)(O) Any or all may be inoperative provided: a) Affected valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) Ram Air Valve is selected OPEN, d) PRESSURIZATION EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL.	
52-01	Compressor Discharge Temperature Sensor (CDTS)	C	1	0	May be inoperative provided left and right Flow Control Valves are considered inoperative (21-51-01).	
1)	Compressor Discharge Temperature Sensor Elements	C	2	1	(O) May be inoperative provided operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	
52-02	Pack Temperature Sensor (PTS)	C	1	0	(O) May be inoperative provided operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	
52-03	Pack Discharge Temperature Sensor (PDTS)	C	1	0	May be inoperative provided left and right Flow Control Valves are considered inoperative (21-51-01).	
1)	Pack Discharge Temperature Sensor Elements	C	2	1	(O) May be inoperative provided operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 21-8

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
52-04	Air Conditioning Pack	C	1	0	(O) May be inoperative provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	
53-01	Ram Air Valve (RAV)	C	1	0	(M)(O) May be inoperative provided: a) Valve is secured OPEN, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	
53-02	Ram Air Regulating Valve (RARV) 1) Aircraft 20006 to 20033 <u>without</u> SB 100-21-01	C	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) Ram Air Valve is verified operative, c) Operations are conducted at or below FL 250, and d) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
53-02	Ram Air Regulating Valve (RARV) (Cont'd) 1) Aircraft 20006 to 20033 <u>without</u> SB 100-21-01 (Cont'd) 2) Aircraft 20006 to 20033 <u>with</u> SB 100-21-01, 20001 to 20005, 20034 and subsequent.	C	1	0	(O) May be inoperative provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	
		C	1	0	(M)(O) May be inoperative provided: a) Valve is secured in DISPATCH position, b) Ram Air Valve is verified operative, c) Operations are conducted at or below FL 250, and d) Operations are conducted within one hour from a suitable airport.	
		C	1	0	(O) May be inoperative provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	

REVISION NO. 7

PAGE NO. 21-10

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
60-01	AIR COND/BLEED RAM AIR "ON" Switch Light (light function only)	C	1	0		
60-02	AIR COND/BLEED MAN TEMP "ON" Switch Light (light function only)	C	1	0		
61-01	Cockpit/Cabin Ventilated Temperature Sensors	C	2	0	(O) Any or all may be inoperative provided cockpit and cabin temperatures are controlled manually.	
1)	Cockpit/Cabin Ventilated Temperature Sensor Elements	C	4	2	(O) One sensor element per sensor may be inoperative provided operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	
61-02	Duct Temperature Sensors (DTS)					
	1) Aircraft 20003 to 20100 <u>without</u> SB 100-21-05	B	2	0	Any or all may be inoperative provided Trim Air System is considered inoperative (21-61-03).	
	a) Duct Temperature Sensor Elements	B	4	2	(O) One sensor element per sensor may be inoperative provided operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	
	2) (Aircraft 20003 to 20100 with SB 100-21-05) Aircraft 20101 and subs	C	2	0	Any or all may be inoperative provided Trim Air System is considered inoperative (21-61-03).	
	a) Duct Temperature Sensor Elements	C	4	2	(O) One sensor element per sensor may be inoperative provided operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 21-11

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-03	Trim Air System 1) Aircraft 20003 to 20100 <u>without</u> SB 100-21-05	B	1	0	(M)(O) May be inoperative provided: a) Right Flow Control Valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to PACK ONLY, c) Pre-cooler Cross Over Valve is operative, d) Left Flow Control Valve is operative, e) Pack Inlet Temperature Sensor is operative, f) Left Bleed Loop is operative, g) Ram Air Valve is verified operative, h) R BLEED is selected OFF, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
		C	1	0	(O) May be inoperative provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-03	Trim Air System (Cont'd)					
	2) (Aircraft 20003 to 20100 <u>with</u> SB 100-21-05) Aircraft 20101 and subs	C	1	0	(M)(O) May be inoperative provided: a) Right Flow Control Valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to PACK ONLY, c) Pre-cooler Cross Over Valve is operative, d) Left Flow Control Valve is operative, e) Pack Inlet Temperature Sensor is operative, f) Left Bleed Loop is operative, g) Ram Air Valve is verified operative, h) R BLEED is selected OFF, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
		C	1	0	(O) May be inoperative provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 21-13

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-04	Pre-cooler Cross Over Valve (PCV)	C	1	0	(M)(O) May be inoperative provided: a) Valve is secured OPEN, b) Trim Air System is operative, c) Ram Air Valve is verified operative, d) Operations are conducted at or below FL 250, and e) Operations are conducted within one hour from a suitable airport.	
		C	1	0	(O) May be inoperative provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-05	Pack Inlet Temperature Sensor (PITS)					
	1) Aircraft 20003 to 20100 <u>without</u> SB 100-21-05	B	1	0	(M)(O) May be inoperative provided: a) L/H Bleed Valve is secured CLOSED, b) XBLEED valve is selected CLOSED, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Right Bleed Loop is operative, f) Right Flow Control Valve is operative, g) Trim Air System is operative, h) Trim Air Inlet Temperature Sensor is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 250, and l) Operations are conducted within one hour from a suitable airport.	
		C	1	0	(M)(O) May be inoperative provided: a) L/H Bleed Valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) Ram Air Valve is selected OPEN, d) PRESSURIZATION EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-05	Pack Inlet Temperature Sensor (PITS) (Cont'd)					
	1) Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
	a) Pack Inlet Temperature Sensor Elements	C	2	1	(O) May be inoperative provided operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	
	2) (Aircraft 20003 to 20100 <u>with</u> SB 100-21-05) Aircraft 20101 and subs	C	1	0	(M)(O) May be inoperative provided: a) L/H Bleed Valve is secured CLOSED, b) XBLEED valve is selected CLOSED, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Right Bleed Loop is operative, f) Right Flow Control Valve is operative, g) Trim Air System is operative, h) Trim Air Inlet Temperature Sensor is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 250, and l) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7

PAGE NO. 21-16

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-05	Pack Inlet Temperature Sensor (PITS) (Cont'd)					
	2) (Aircraft 20003 to 20100 with SB 100-21-05) Aircraft 20101 and subs (Cont'd)					
		C	1	0	(M)(O) May be inoperative provided: a) L/H Bleed Valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) Ram Air Valve is selected OPEN, d) PRESSURIZATION EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL.	
	a) Pack Inlet Temperature Sensor Elements	C	2	1	(O) May be inoperative provided operational status of Pre-cooler Cross Over Valve is verified once each flight-day.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-06	Trim Air Inlet Temperature Sensor (HATS) 1) Aircraft 20003 to 20100 <u>without</u> SB 100-21-05	B	1	0	(M)(O) May be inoperative provided: a) R/H Bleed Valve is secured CLOSED, b) XBLEED valve is selected CLOSED, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Left Bleed Loop is operative, f) Left Flow Control Valve is operative, g) Pack Inlet Temperature Sensor is operative, h) APU bleed is used for engines start only, i) Ram Air Valve is verified operative, j) Operations are conducted at or below FL 250, and k) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-06	Trim Air Inlet Temperature Sensor (HATS) (Cont'd)					
	1) Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)	C	1	0	(M)(O) May be inoperative provided: a) R/H Bleed Valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) Ram Air Valve is selected OPEN, d) PRESSURIZATION EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL.	
	2) (Aircraft 20003 to 20100 <u>with</u> SB 100-21-05) Aircraft 20101 and subs	C	1	0	(M)(O) May be inoperative provided: a) R/H Bleed Valve is secured CLOSED, b) XBLEED valve is selected CLOSED, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Left Bleed Loop is operative, f) Left Flow Control Valve is operative, g) Pack Inlet Temperature Sensor is operative, h) APU bleed is used for engines start only, i) Ram Air Valve is verified operative, j) Operations are conducted at or below FL 250, and k) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 21-19

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
61-06	Trim Air Inlet Temperature Sensor (HATS) (Cont'd) 2) (Aircraft 20003 to 20100 <u>with</u> SB 100-21-05) Aircraft 20101 and subs (Cont'd)	C	1	0	(M)(O) May be inoperative provided: a) R/H Bleed Valve is secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) Ram Air Valve is selected OPEN, d) PRESSURIZATION EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL.	
61-07	Temperature Control Valve (TCV)	C	1	0	May be inoperative provided L/H and R/H Flow Control Valves are considered inoperative (21-51-01).	
61-08	Baggage Compartment Heaters	C	2	0	(M)(O) Any or all may be inoperative provided affected heater is deactivated.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 22-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

22. Autoflight

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Autopilot System	B	1	0	Except where enroute operations or approach procedures require its use, may be inoperative provided Altitude Alerting System is operative. NOTE 1: Autopilot is required for RVSM Operations. NOTE 2: Relief for inoperative individual flight guidance operational modes is provided by MMEL Item 22-10-02 Flight Directors.	
10-02	Flight Directors	B	2	1	(O) Except where enroute operations or approach procedures require its use, may be inoperative provided Autopilot System is considered inoperative (22-10-01).	
		B	2	0	Except where enroute operations or approach procedures require its use, may be inoperative provided: <ul style="list-style-type: none"> a) Autopilot System is considered inoperative (22-10-01), b) TO/GA Switches are considered inoperative (22-11-02), and c) Operations are conducted in accordance with AFM Supplement. 	

(Continued)

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

22. Autoflight

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Flight Directors (Cont'd)					
	1) Flight Director Modes	C	-	-	Except when enroute operations or approach procedures require its use, individual flight director modes may be inoperative provided Altitude Alerting System is operative.	
					NOTE 1: Flight director altitude hold mode is required for RVSM Operations.	
					NOTE 2: Any flight director mode which operates normally may be used.	
11-01	Autopilot/Flight Director Sync Switches	C	2	0	Any or all may be inoperative in Non-SYNC mode.	
		B	2	0	Any or all may be inoperative in SYNC mode provided:	
					a) Autopilot is disengaged and considered inoperative (22-10-01),	
					b) Flight Directors are selected off and considered inoperative (22-10-02), and	
					c) TO/GA switches (22-11-02) are considered inoperative.	
11-02	Take-Off/Go-Around (TO/GA) Switches	C	2	1	(O) May be inoperative provided alternate procedures are established and used.	
		C	2	0	(O) Any or all may be inoperative provided:	
					a) Operations are conducted in accordance with AFM Supplement, Supplement 2 – Supplemental information for the MMEL (Flight Directors inoperative), and	
					b) Operations with Steep Approach are not conducted.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 23-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
11-01	VHF Communication Systems	D	-	2	VHF 3 may be inoperative.	
11-02	HF Communication Systems	D	-	-	(M) Any in excess of those required by 14 CFR may be inoperative.	
		C	-	1	(M)(O) May be inoperative while conducting operations that require two LRCS provided: a) Aircraft SATVOICE system operates normally, b) SATVOICE services are available as a LRCS over the intended route of flight, c) The ICAO Flight Plan is updated (as required) to notify ATC of the communications equipment status of the aircraft, and d) Alternate procedures are established and used.	
13-01 ***	Satellite Communication (SATCOM) System	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	1	0	May be inoperative provided routine procedures do not require its use.	
20-01 ***	Datalink System (Includes CPDLC and ADS-C functions)	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	1	0	May be inoperative provided 14 CFR do not require its use.	
(Continued)						

REVISION NO. 7

PAGE NO. 23-2

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
20-01 ***	Datalink System (Includes CPDLC and ADS-C functions) (Cont'd)					
1)	Controller Pilot Data Link Communications (CPDLC) (Aircraft 20003 to 20500 <u>with</u> SB 100-23-22, or SB 100-23-21, or Aircraft 20501 and subs <u>with</u> SB 350-23-010, or SB 350-23-011)	C	2	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	2	0	May be inoperative provided 14 CFR do not require its use.	
a)	CPDLC In-Coming Message Visual Alerting (CDU and EICAS)	C	2	0	May be inoperative provided In-Coming Message Aural Alerting (chime) is operative.	
		D	2	0	May be inoperative provided operating regulations and routine operations do not require the use of CPDLC.	
2) ***	Automatic Dependent Surveillance Contract (ADS-C)	C	2	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	2	0	May be inoperative provided 14 CFR do not require its use.	

REVISION NO. 7

PAGE NO. 23-3

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
22-01 ***	Selective Call System (SELCAL)	C	-	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	-	0	May be inoperative provided procedures do not require its use.	
1)	Channels	C	-	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	-	0	May be inoperative provided procedures do not require its use.	
41-01	Passenger Address System (PA)					
1)	Passenger Configuration	C	1	0	(O) May be inoperative provided alternate, normal and emergency procedures, and/or operating restrictions are established and used.	
					NOTE: Any station function(s) that operate normally may be used.	
a)	Lavatory Speaker	C	-	0	(O) May be inoperative provided alternate procedures are established and used.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
41-02	Alerting System (Chime/Light)					
1)	Flight Deck Call Light	B	1	0	May be inoperative provided the flight deck chime is operative.	
					NOTE: Any visual alerting system function(s) that operates normally may be used.	
2)	Flight Attendant/ Cabin Call Light	D	-	0	(O) May be inoperative provided: a) Affected call light is not used for lavatory smoke detector alerting, and b) Alternate procedures are established and used.	
3)	Flight Attendant/ Cabin Chime	D	-	0	(O) May be inoperative provided: a) Affected chime is not used for lavatory smoke detector alerting, and b) Alternate procedures are established and used.	
51-01	Hand Held Microphones	C	2	1	May be inoperative provided associated Boom Microphone is operative and used.	
		C	2	0	Any or all may be inoperative provided: a) Boom Microphones are operative and used, and b) Spare Boom Microphone is available in flight compartment.	
51-02	Flight Compartment Speakers	C	2	0	Any or all may be inoperative provided: a) All flightcrew members on flight deck duty utilize headsets, and b) Spare headset is readily available.	
51-03	Boom Microphones	A	-	0	May be inoperative provided: a) Associated Hand Held Microphone is operative and used, and b) Repairs are made within 3 flight-days.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
51-04	Headsets	D	-	-	Any in excess of those required for each flightcrew member on flight deck duty may be inoperative.	
51-06	Cabin/Lavatory Speakers	C	-	0	May be inoperative provided: a) Passenger Address System (23-41-01) is considered inoperative, b) Flight Attendant/Cabin Chime is considered inoperative (23-41-02, sub item 3), and c) Pre-recorded Announcement System is considered inoperative (23-70-01).	
1)	Lavatory Speaker	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
51-07	Control Wheel TX/INPH Switches	A	2	1	(O) May be inoperative in non-transmit mode provided: a) Boom Microphone on affected side is considered inoperative (23-51-03), b) Crew interphone using O2 mask and hot mike is verified operative before each flight, and c) Repairs are made within 3 flight-days. NOTE: Pilot with inoperative TX/INPH Switch will not be able to transmit when wearing the O2 mask.	
51-08 ***	Cockpit Speaker Mute System					
1)	Cockpit Speaker Mute Pushbutton	C	1	0	May be inoperative in the mute state provided Flight Compartment Speakers (23-51-02) are considered inoperative.	
		D	1	0	(O) May be inoperative provided the system is not failed in the mute state.	
2)	Cockpit Speaker Mute Annunciators	D	2	0		

AIRCRAFT:
BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
70-01 ***	Pre-Recorded Announcement System (Airshow Custom Passenger Briefings)	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	1	0	May be inoperative provided routine procedures do not require its use.	
71-01	Cockpit Voice Recorder (CVR) System Including the Recorder Independent Power Supply (RIPS)					
1)	If CVR and FDR are installed	A	1	0	May be inoperative provided: a) Flight Data Recorder (FDR) operates normally, and b) Repairs are made within 3 flight-days.	
a)	Recorder Independent Power Supply (RIPS) (20292 and Subs Post SB 100-23-20)	C	1	0	(M) May be inoperative provided RIPS is removed.	
2)	Operators other than a holder of an air carrier or commercial operator certificate	A	1	0	May be inoperative provided repairs are made as required by 14 CFR.	
a)	Recorder Independent Power Supply (RIPS) (20292 and Subs Post SB 100-23-20)	C	1	0	(M) May be inoperative provided RIPS is removed.	
72-01	Crewmember Interphone System(s)					
1)	Flight Deck to Ground Function	C	-	0	(M) May be inoperative provided alternate procedures are established and used.	
		D	-	0	May be inoperative provided procedures do not require its use.	

REVISION NO. 7

PAGE NO. 24-1

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

24. Electrical Power

Sequence No.	Item	1	2	3	4	Change Bar
20-01	APU Generator Channel	C	1	0	(M) May be inoperative provided: a) APU generator is disabled, and b) Engine Driven Generator Channels are operative.	
20-02	ELECTRICAL APU GEN "ON" Switch Light (light function only)	C	1	0		
30-01	ELECTRICAL L/R BATT "OFF" Switch Light (light function only)	C	2	0		
30-02	ELECTRICAL STBY INST "OFF" Switch Light (light function only)	C	1	0		
31-01	Engine Driven Generator Channels	B	2	1	(M)(O) May be inoperative provided: a) Affected generator is disabled, b) APU is operative, c) APU Generator Channel is operative and used throughout flight, d) Flight planning must consider additional fuel burn for the APU, and e) Operations are conducted at or below FL 300.	
31-02	ELECTRICAL L/R GEN "OFF" Switch Light (light function only)	C	2	0		
31-03 ***	Hydraulic Motor Driven Generator (HMDG) System	D	1	0	(M) May be inoperative provided system is deactivated.	

REVISION NO. 7

PAGE NO. 24-2

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

24. Electrical Power

Sequence No.	Item	1	2	3	4	Change Bar
41-01	External Power System	C	1	0		
41-02	ELECTRICAL EXT PWR "AVAIL/ON" Switch Light (Pedestal) (Light Function Only)	C	1	0		
41-03	EXTERNAL POWER "AVAIL/IN USE" Indicator (Service Panel)	C	1	0		
41-04	Ground Service Power System	C	1	0	(O) May be inoperative provided ground service contactor is verified open.	
41-05	GND SERVICE "ON" Switch Light (Service Panel) (Light Function Only)	C	1	0		
50-01	Bus Tie Contactors	B	2	1	May be inoperative CLOSED.	
50-02	ELECTRICAL BUS TIE "-" Switch Light (Light Function Only)	C	1	0		
64-01	Auxiliary Buses					
1)	Left Auxiliary Bus	C	1	0		
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 24-3

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

24. Electrical Power

Sequence No.	Item	1	2	3	4	Change Bar
64-01	Auxiliary Buses (Cont'd)					
2)	Right Auxiliary Bus	B	1	0	(O) May be inoperative provided: a) Passenger Address System is considered inoperative (23-41-01), b) Alerting System is considered inoperative (23-41-02), c) Pre-recorded Announcement System is considered inoperative (23-70-01), d) Windshield & Side Window Heating System right Side Window Heating Channel is considered inoperative (30-41-01), e) Cabin Lighting System is considered inoperative (33-20-01), f) Water System is considered inoperative (38-00-01), and g) Lavatory Waste System is considered inoperative (38-30-01).	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 25-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
11-01	Pilot Seats					
1)	Headrests	C	2	0	Any or all may be inoperative or missing provided seat is acceptable to the affected crewmember.	
2)	Lumbar Supports	C	2	0	Any or all may be inoperative in the lowest position provided seat is acceptable to the affected crewmember.	
3)	Arm Rests	C	4	0	(M) Any or all may be inoperative or missing provided: a) Affected armrest is secured in upright position or removed, b) Egress is not impaired, and c) Seat is acceptable to the affected crewmember.	
4)	Seat Adjustments	C	-	-	Vertical, recline, and fore/aft adjustment may be inoperative provided seat is secured in a position to meet individual pilot requirements.	
11-02 ***	Belted Toilet Seat	D	1	0	Seat belt may be inoperative provided the seat is not occupied during taxi, takeoff and landing.	
11-03 ***	Forward Pull Out In Flight Seat	D	1	0	(M) May be inoperative provided it is secured in the STOWED position or removed.	
13-01 ***	Pilots Heated Mats	C	2	0	(M) Any or all may be inoperative provided affected mat is deactivated.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 25-2

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
14-01	Cockpit Sun Visors					
1)	Sun Visors (Headliner)	C	2	0	Any or all may be inoperative provided affected sun visor does not obstruct either pilot's field of view for take-off and landing.	
		C	2	0	(O) Any or all may be inoperative (missing) provided: a) Affected sun visor is removed, b) Affected sun visor is disposed in a secure stowage location, and c) It is acceptable to flightcrew for intended flight conditions.	
2)	Glare Shield Retractable Visors	C	2	0	(M) Any or all may be inoperative or missing provided: a) Affected visor is secured in the retracted position or removed, and b) It is acceptable to flightcrew for intended flight conditions.	
14-02	Control Wheel Chart Holders	C	2	0		
14-03 ***	Cockpit Writing Tables	D	2	0	Any or all may be inoperative (missing) provided affected table does not impede associated crewmember to perform his duties.	
14-04	Lavatory Entry Area Ashtray	A	1	0	May be inoperative or missing for a period of 10 calendar days.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 25-3

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
14-05	Galley Waste Receptacles Access Doors/Covers	C	-	-	(M)(O) May be inoperative provided: a) The container is empty and the access is secured to prevent waste introduction into the compartment, and b) Procedures are established to ensure that the sufficient galley waste receptacles are available to accommodate all waste that may be generated on a flight.	
14-06	Storage Bins/Cabin, Galley, and Lavatory Storage Compartments/ Closets	C	-	-	(M) May be inoperative provided: a) Procedures are established to secure affected bin, compartment, or closet in closed position, b) Affected bin, compartment, or closet is prominently placarded "DO NOT USE", c) Any emergency equipment located in affected bin, compartment, or closet is considered inoperative, and d) Affected bin, compartment, or closet is not used for storage of any items except for those permanently affixed. NOTE 1: For overhead bins, if no partitions are installed, the entire overhead bin is considered inoperative. NOTE 2: Proviso is not intended to preclude crewmember inspections.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 25-4

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
14-06	Storage Bins/Cabin, Galley, and Lavatory Storage Compartments/ Closets (Cont'd)	C	-	-	(M)(O) May be inoperative provided: a) For non-retractable doors affected door is removed, b) For retractable doors, affected door is removed or secured in retracted (fully open) position, c) Affected bin, compartment, or closet is prominently placarded DO NOT USE, d) Affected bin, compartment, or closet is not used for storage of any items except those permanently affixed, e) Procedures are established and used to alert crewmembers and passengers of inoperative bins, compartments, or closets, and f) Passengers are briefed that affected bin, compartment, or closet is not used. NOTE 1: For overhead bins, if no partitions are installed, the entire overhead bin is considered inoperative. NOTE 2: Any emergency equipment located in affected bin, compartment, or closet (permanently affixed) is available for use.	
(Continued)						

REVISION NO. 7

PAGE NO. 25-5

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
14-06	Storage Bins/Cabin, Galley, and Lavatory Storage Compartments/ Closets (Cont'd)	C	-	-	May be inoperative in closed position provided: <ol style="list-style-type: none"> a) Affected bin, compartment, or closet is prominently placarded "DO NOT USE", b) Any emergency equipment located in affected bin, compartment, or closet is considered inoperative, and c) Location placarding for any emergency equipment stored in affected bin, compartment, or closet is removed or obscured. NOTE: Use of this proviso may be dependent upon an operator's aircraft security program, as appropriate.	
1)	Storage Compartment Key Locks	D	-	0	(M) May be inoperative in the unlocked position provided doors can be secured by other means.	
14-07	Passenger Seat Life Vest Storage Compartment Panels					
1)	If Life vests required by Regulations	C	-	-	May be inoperative (missing) provided: <ol style="list-style-type: none"> a) Associated life vest is relocated and accessible for affected passenger, and b) Affected passenger is briefed about life vest location. 	

(Continued)

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
14-07	Passenger Seat Life Vest Storage Compartment Panels (Cont'd)					
1)	If Life vests required by Regulations (Cont'd)	C	-	-	May be inoperative (missing) provided: a) Associated life vest is removed, and b) Affected Passenger Seat is considered inoperative (25-21-01).	
2)	If Life vests not required by Regulations	D	-	-	May be inoperative (missing) provided associated life vest is removed.	
14-08	Lavatory Door	C	1	0	(M) May be inoperative provided door is secured closed and placarded DO NOT ENTER. NOTE: This proviso does not preclude inspections by crewmembers.	
14-09	Interior Baggage Door	C	1	0	(M) May be inoperative OPEN provided: a) Baggage compartment remains empty except for fly away kits and/or ballast, and b) Baggage restraints are operative and used if fly away kits or ballast are retained. NOTE: Operator MELs should define which items are approved for inclusion in fly away kits, and which material can be used as ballast.	
		C	1	0	(M) May be inoperative CLOSED and used for storage provided: a) Door is secured closed, and b) Baggage restraints are operative and used.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
21-01	Passenger Seats	D	-	-	May be inoperative provided: <ol style="list-style-type: none"> a) Seat does not restrict access to any emergency exit, egress route, or main aisle, and b) The affected seat(s) is blocked and placarded "DO NOT OCCUPY". NOTE 1: A seat(s) with an inoperative seat belt or shoulder harness is considered inoperative. NOTE 2: Affected seat(s) may include the seat(s) behind and/or adjacent outboard seats.	
1)	Recline Mechanism	D	-	-	(M) May be inoperative and seat(s) occupied provided seat(s) is secured in the full upright position.	
2) ***	Lazyboy Leg Rest Mechanism	D	-	-	(M) May be inoperative and seat(s) occupied provided leg rest(s) is secured in stowed position.	
3) ***	Track/Swivel Mechanism	D	-	-	(M) May be inoperative and seat(s) occupied provided: <ol style="list-style-type: none"> a) Affected forward facing seat is secured in fully aft, fully outboard, forward facing position, and b) Affected aft facing seat is secured in fully forward, fully outboard, aft facing position. 	
4) ***	Armrest	D	-	-	May be inoperative or missing and seat occupied provided it does not restrict access to any emergency exit, egress route, or main aisle.	
5) ***	Seat Belt Air Bag Restraint Systems					
	Seat Belt Air Bags Required by 14 CFR	D	-	-	May be inoperative provided affected seat is blocked and placarded "DO NOT OCCUPY".	
	Seat Belt Air Bags Not Required by 14 CFR	D	-	-	(M) May be inoperative or disconnected provided seat belt operates normally.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
21-02 ***	Observer Seat					
1) ***	Flight Deck Observer Seat (including associated equipment)	A	-	0	(O) May be inoperative provided: <ol style="list-style-type: none"> a) A passenger seat in the passenger cabin is made available to an FAA inspector for the performance of official duties, b) Affected seat is verified retracted prior to each flight, and c) Repairs are made within 2 flight-days. May be inoperative provided: <ol style="list-style-type: none"> a) Required minimum safety equipment (safety belt and oxygen) is available to the FAA inspector for the performance of official duties, b) Seat is acceptable to the FAA inspector for the performance of official duties, and c) Repairs are made within 2 flight-days. NOTE 1: These provisos are intended to provide for occupancy of the above seats by an FAA inspector when the minimum safety equipment (oxygen and safety belt) is functional and the inspector determines the conditions to be acceptable.	
					NOTE 2: The pilot-in-command will determine if the minimum safety equipment is functional for other persons authorized to occupy any observer seat(s).	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
21-02 ***	Observer Seat (Cont'd)					
2) ***	Passenger/Observer Seat (including 3-rd Audio System)	A	1	0	(M) May be inoperative provided: a) Seat does not block or restrict access to an emergency exit, b) Seat does not restrict any passenger from access to the main aisle, c) Seat is not used and is blocked and placarded "DO NOT OCCUPY", d) Other passenger seat is made available to a Regulatory Authorities inspector (if required) for the performance of official duties, and e) Repairs are made within 2 flight-days.	
***	a) Recline Mechanism	C	1	0	(M) May be inoperative and seat occupied provided seat is secured in the upright position.	
***	b) Lazyboy Leg Rest Mechanism	D	1	0	(M) May be inoperative and seat occupied provided leg rest is secured in stowed position.	
***	c) Track/Swivel Mechanism	D	1	0	(M) May be inoperative and seat occupied provided: a) Affected forward facing seat is secured in fully aft, fully outboard, forward facing position, and b) Affected aft facing seat is secured in fully forward, fully outboard, aft facing position.	
3) ***	Observer Seat not required by 14 CFR (including associated equipment)	D	-	0	NOTE: The pilot-in-command will determine if the minimum safety equipment is functional for other persons authorized to occupy any observer seat(s).	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 25-10

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
50-01	Cargo Restraint System	C	1	0	May be inoperative provided cargo compartment remains empty.	
1)	Baggage Net	C	1	0	May be inoperative provided Baggage Shelf is installed, operative and used to restrain all available baggage.	
2) ***	Baggage Shelf	D	1	0	May be inoperative provided shelf is not used. NOTE: An inoperative restraining net renders shelf inoperative.	
61-01 ***	Emergency Locator Transmitter (ELT)					
1)	Survival Type ELTs	D	-	-	Any in excess of those required by 14 CFR may be inoperative or missing.	
2)	Fixed ELTs	A	-	0	(M) May be inoperative provided: a) System is deactivated, and b) Repairs are made within 90 days.	
		A	-	0	May be missing provided: a) Placard stating "ELT not installed" is placed in view of the pilot, and b) Repairs are made within 90 days.	
		D	-	-	(M) Any in excess of those required by 14 CFR may be inoperative provided system is deactivated.	
		D	-	-	Any in excess of those required by 14 CFR may be missing.	

(Continued)

REVISION NO. 7

PAGE NO. 25-11

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
61-01 ***	Emergency Locator Transmitter (ELT) (Cont'd)					
3) ***	Remote ELT Switch	D	-	0	(M) May be inoperative provided: a) Remote ELT Switch is deactivated, and b) ELT Switch is placed in the ARMED mode.	
4) ***	ELT Indicator Light	D	-	0		
5) ***	ELT Aural Alarm	D	-	0		
62-01	Emergency Medical Equipment					
1)	Automatic External Defibrillator (AED) and/or Associated Equipment	A	-	0	(O) May be incomplete, missing or inoperative provided: a) AED is resealed in a manner that will identify it as a unit that cannot be mistaken for a fully serviceable unit, and b) Repairs or replacements are made within 1 flight.	
(Continued)						

REVISION NO. 7

PAGE NO. 25-12

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
62-01 ***	Emergency Medical Equipment (Cont'd)	D	-	-	Any in excess of those required by 14 CFR may be incomplete, missing, or inoperative.	
2)	Emergency Medical Kit (EMK) and/or Associated Equipment	A	-	0	(O) May be incomplete, missing or inoperative provided: a) EMK is resealed in a manner that will identify it as a unit that cannot be mistaken for a fully serviceable unit, and b) Repairs or replacements are made within 1 flight.	
3)	First Aid Kit (FAK) and/or Associated Equipment	A	-	-	(O) If more than one is required by 14 CFR, only one of the required first aid kits may be incomplete, missing or inoperative provided: a) FAK is resealed in a manner that will identify it as a unit that cannot be mistaken for a fully serviceable unit, and b) Repairs or replacements are made within 1 flight.	
		D	-	-	Any in excess of those required by CFR may be incomplete, missing, or inoperative.	
62-02	Flotation Equipment (Crew and Passengers)	D	-	-	As required by Regulations.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 25-13

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
62-03	Flashlights/Flashlight Holders					
1)	Flashlights	C	-	0	Any in excess of those required by 14 CFR may be inoperative or missing.	
2)	Holders	C	-	0	May be inoperative (missing) provided alternate stowage provisions are provided.	
70-01 ***	Non-Essential Equipment Furnishings (NEF)	-	-	0	May be inoperative, damaged or missing provided that the item(s) is deferred in accordance with the operator's NEF deferral program. The NEF program, procedures and processes are outlined in the operator's (insert name) Manual. (M) and (O) procedures, if required, must be available to the flightcrew and included in the operator's appropriate document. NOTE: Exterior lavatory door ashtrays are not considered NEF items.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

26. Fire Protection

Sequence No.	Item	1	2	3	4	Change Bar
11-01	FIREX System	B	1	1	System redundancy may be degraded as indicated by "FIRE SYS FAULT" advisory message provided operations are conducted within one hour from a suitable airport. NOTE: At time of repair, any FIREX system failure causing FIRE SYS FAULT advisory message to display must be corrected.	
11-02	FIREX Control Unit ARINC Communication	B	1	0	(O) May be inoperative provided FIRE DET test is performed before each flight.	
13-01	APU Fire Detection Subsystem	B	1	0	May be inoperative provided APU is considered inoperative (49-11-01).	
		B	1	0	(M) May be inoperative for ground operations only provided: a) APU access panel is opened, b) APU is continuously visually monitored, and c) APU is shut down before taxi.	
14-01	Main Landing Gear Bay Overheat Detection Subsystem	B	1	0	May be inoperative provided: a) Landing gear is left extended for a minimum of 5 minutes after takeoff, b) Takeoff performance is in accordance with the AFM Supplement (Flight with Landing Gear Down), c) Takeoff is not conducted in icing conditions, and d) Short Field Operations (Supplement 11) are not conducted. NOTE: In case of engine failure after V ₁ , performance is the prime consideration and the landing gear should be retracted normally until performance penalty with gear down is not a problem.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 26-2

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

26. Fire Protection

Sequence No.	Item	1	2	3	4	Change Bar
15-01	Baggage Compartment Smoke Detection Subsystem	C	1	0	(O) May be inoperative provided procedures are established and used to ensure the associated compartment remains empty, or is verified to contain only empty cargo handling equipment, ballast and/or fly away kits. NOTE: Operator MELs should define which items are approved for inclusion in the fly away kits, and which materials can be used as ballast.	
21-01	APU Fire Extinguishing Subsystem	B	1	0	May be inoperative provided APU is considered inoperative (49-11-01). (M) May be inoperative for ground operations only provided: a) APU access panel is opened, b) APU is continuously visually monitored, and c) APU is shut down before taxi.	
23-01	Portable Fire Extinguishers	D	-	-	Any in excess of those required by Regulations may be inoperative (missing) provided: a) Inoperative fire extinguisher is tagged inoperative, removed from installed location, and placed out of sight so it can not be mistaken for functional unit, and b) Required distribution is maintained.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

27. Flight Controls

Sequence No.	Item	1	2	3	4	Change Bar
10-01	EICAS Aileron Control Surface Position Indications	C	2	0	(O) Any or all may be inoperative provided affected control surface is visually checked for full, free and correct movement before each flight.	
20-01	EICAS Rudder Control Surface Position Indication	C	1	0	(O) May be inoperative provided: a) Rudder Pedal Adjustment Systems are operative, and b) Control surface is visually checked for full, free and correct movement before each flight.	
20-02	Rudder Pedal Adjustment Systems	C	2	0	(M) Any or all may be inoperative provided: a) Actuators are deactivated, b) EICAS Rudder Control Surface Position Indication is operative, c) Pedals position is acceptable to the affected crewmember, and d) Rudder and brake pedals are checked for full and unrestricted movement at both pilot stations.	
32-01	Stick Shakers	A	2	1	(M)(O) May be inoperative provided: a) Affected shaker is deactivated, b) Aural warnings are verified operative, and c) Repairs are made after 1 flight.	
32-02	STALL PUSHER "OFF" Switch Light (light function only)	C	1	0		

REVISION NO. 7

PAGE NO. 27-2

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

27. Flight Controls

Sequence No.	Item	1	2	3	4	Change Bar
41-01	Pitch Trim System	C	1	1	(O) System redundancy may be degraded as indicated by "STAB TRIM FAULT" advisory message provided pilot and copilot manual trim switches are verified operative before each flight. NOTE: At time of repair, any pitch trim system failure causing STAB TRIM FAULT advisory message to display must be corrected.	
60-01	Spoiler System					
1)	Ground Lift Dumping AUTO Function	C	1	0	(O) May be inoperative provided: a) GND SPOILERS rotary selector switch is selected to MANUAL ARM before each takeoff and landing, and b) GND SPOILERS rotary selector switch is selected to OFF after each landing.	
61-01	ROLL SPOILERS "OFF" Switch Light (light function only)	C	1	0		

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
21-03	L & R Fuel Boost Pumps Auto Function					
	L Fuel Boost Pump AUTO Function	C	1	0	May be inoperative provided FUEL L PUMP rotary selector switch is selected to ON before left engine start and selected to OFF when engine started.	
	R Fuel Boost Pump AUTO Function	C	1	0	May be inoperative provided: a) FUEL R PUMP rotary selector switch is selected to ON before right engine start and selected to OFF when engine started, and b) FUEL R PUMP rotary selector switch is selected to ON before APU start and selected to OFF when right engine started or APU shut down.	
22-01	XFER Valve	C	1	0	(M)(O) May be inoperative provided: a) Valve is deactivated CLOSED, b) Gravity XFLOW Valve is verified operative, and c) Operations are conducted within one hour from a suitable airport.	
22-02	FUEL XFER “-“ Switch Light (light function only)	C	1	0		
22-03	FUEL GRAVITY XFLOW “-“ Switch Light (light function only)	C	1	0		
22-04	Gravity XFLOW Valve	C	1	0	(M) May be inoperative provided: a) Valve is deactivated CLOSED, b) XFER Valve is verified operative, and c) Operations are conducted within one hour from a suitable airport.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
23-01	Pressure Refueling System (Refuel/Defuel Control Panel)	C	1	0	(O) May be inoperative provided gravity refueling procedure is used.	
1)	Automatic Mode	C	1	0	(O) May be inoperative provided Manual Mode is operative.	
2)	Manual Mode	C	1	0	(O) May be inoperative provided Automatic Mode is operative.	
3)	Fuel Quantity Display Indications (Left and Right)	C	2	0	(O) Any or all may be inoperative provided Manual Mode is operative and used.	
23-02	Refuel/Defuel Valves	C	2	0	(M) Any or all may be inoperative provided: a) Valves are deactivated, b) Affected valve is verified CLOSED, and c) Gravity refueling procedure is used.	
23-03	Pressure Relief Valves	C	2	0	(M) Any or all may be inoperative provided: a) Affected valve is verified CLOSED, and b) Pressure Refueling System Manual Mode is operative and used.	
		C	2	0	(M) Any or all may be inoperative provided: a) Affected valve is verified CLOSED, and b) Gravity refueling procedure is used for affected tank.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 28-4

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
23-04	Refuel/Defuel Adapter Cap	C	1	0	(M) May be inoperative (missing) provided: a) Refuel/defuel adapter is visually checked for contamination before each pressure refueling, b) Check valve is verified CLOSED after each pressure refueling, and c) Refuel/Defuel Valves are verified CLOSED after each pressure refueling.	
40-01	EICAS Bulk Fuel Temperature Indication System	C	1	0	(M) May be inoperative provided fuel temperature is verified to be within limits before each flight.	
41-01	High Level Sensors	C	2	0	(O) Any or all may be inoperative provided: a) Pressure Refueling System Manual Mode is operative and used, and b) Maximum allowed fuel quantity in each tank is limited to 5500 lbs (2500 kg).	
		C	2	0	Any or all may be inoperative provided gravity refueling procedure is used for the affected tank. NOTE: Refer to AFM fuel limitations for the maximum usable fuel load when using gravity refueling.	
41-02	Fuel Quantity Gaging Computer Channels	C	2	1	May be inoperative provided Fuel Used Readout is operative.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

29. Hydraulic Power

Sequence No.	Item	1	2	3	4	Change Bar
11-01	HYDRAULIC L/R SOV "CLOSED" Switch Light (light function only)	C	2	0		
12-01	L & R DC Motor Pumps (DCMP)					
1)	AUTO Function (Aircraft 20003 to 20190 <u>without</u> SB 100-29-011)	C	2	0		
2)	AUTO Function (Aircraft 20003 to 20190 <u>with</u> SB 100-29-011) Aircraft 20191 and subs.	C	2	0	(O) Any or all may be inoperative provided affected pump HYDRAULIC L/R PUMP rotary selector switch is selected to ON before each take-off and approach.	
12-02	Power Transfer System	C	1	0	(M)(O) May be inoperative provided: a) Power transfer unit selector valve is deactivated CLOSED, b) Takeoff performance is in accordance with the AFM Supplement 2 – Supplemental information for the MMEL (Flight with Landing Gear Down), and c) Steep approach (Supplement 10) or Short Field Operations (Supplement 11) are not conducted.	
1)	AUTO Function	C	1	0	NOTE: Only take-off and climb performance penalties for Landing Gear Down apply. May be inoperative provided: a) HYDRAULIC PTU rotary selector switch is selected to ON before each take off and selected to OFF during each climb, and b) HYDRAULIC PTU rotary selector switch is selected to ON before each approach and selected to OFF after each landing.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 29-2

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

29. Hydraulic Power

Sequence No.	Item	1	2	3	4	Change Bar
31-01	EICAS L & R Hydraulic Pressure Readouts	C	2	0	(O) Any or all may be inoperative provided DCMP Low Pressure Switch and EDP Low Pressure Switch on affected side are verified operative.	
31-02	L & R Hydraulic Pump Low Pressure Switches					
1)	DCMP Low Pressure Switches	C	2	0	(O) Any or all may be inoperative provided: a) EDP Low Pressure Switch on affected side is operative, b) Affected hydraulic pump is verified operative before each flight, and c) EICAS Hydraulic Pressure Readout and Hydraulic Reservoir Quantity Readout in affected system are operative and monitored during flight.	
2)	EDP Low Pressure Switches	C	2	0	(O) Any or all may be inoperative provided: a) DCMP Low Pressure Switch on affected side is operative, b) Affected hydraulic pump is verified operative before each flight, and c) EICAS Hydraulic Pressure Readout and Hydraulic Reservoir Quantity Readout in affected system are operative and monitored during flight.	
NOTE: When aircraft is dispatched with right EDP Low Pressure Switch inoperative, flaps will operate at low rate.						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

29. Hydraulic Power

Sequence No.	Item	1	2	3	4	Change Bar
32-01	EICAS Hydraulic Reservoir Quantity Readouts					
1)	L & R	C	2	0	(M) Any or all may be inoperative provided: <ul style="list-style-type: none"> a) Hydraulic Reservoir Quantity Gauge in affected system is operative, b) Quantity in associated reservoir is verified adequate on respective Hydraulic Reservoir Quantity Gauge before each flight, and c) Hydraulic Pump Low Pressure Switches (EDP and DCMP) on affected side are operative. 	
2)	AUX	C	1	0	(M) May be inoperative provided: <ul style="list-style-type: none"> a) AUX Hydraulic Reservoir Quantity Gauge is operative, and b) Quantity in auxiliary system reservoir is verified adequate on AUX Hydraulic Reservoir Quantity Gauge before each flight. 	
32-02	Hydraulic Reservoir Quantity Gauges					
1)	L & R	C	2	0	Any or all may be inoperative provided EICAS Hydraulic Reservoir Quantity Readout in affected system is operative.	
2)	AUX	C	1	0	May be inoperative provided AUX EICAS Hydraulic Reservoir Quantity Readout is operative.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 30-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
10-01	High Pressure Valves (HPV)	C	2	0	(M) Any or all may be inoperative provided: a) Affected valve is secured CLOSED, b) ANTI-ICE WING switch is selected OFF, c) Operations are not conducted in known or forecast icing conditions, and d) One Ice Detection System is operative.	
10-02	Anti-Ice Bleed Pressure Indication Systems	C	2	0	Any or all may be inoperative provided: a) ANTI-ICE WING switch is selected OFF, b) Operations are not conducted in known or forecast icing conditions, and c) One Ice Detection System is operative.	
10-03	Wing Anti-Ice Valves (WAIV)	C	2	0	(M) Any or all may be inoperative provided: a) Affected valve is secured CLOSED, b) ANTI-ICE WING switch is selected OFF, c) Operations are not conducted in known or forecast icing conditions, and d) One Ice Detection System is operative.	
10-04	Wing Isolation Valve (CBW)	C	1	0	May be inoperative provided: a) ANTI-ICE WING switch is selected OFF, b) Operations are not conducted in known or forecast icing conditions, and c) One Ice Detection System is operative.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
10-05	ANTI-ICE WING "ON" Switch Light (light function only)	C	1	0		
10-06	Engine Anti-Ice Valves	C	2	1	May be inoperative CLOSED provided: a) Operations are not conducted in known or forecast icing conditions, and b) One Ice Detection System is operative.	
		C	2	1	(O) May be inoperative OPEN provided: a) Affected engine ITT margin is checked before each take-off, b) Operations are conducted in accordance with AFM Performance data for engine anti-ice ON, and c) Operations are prohibited with Outside Air Temperature (OAT) above 10 °C.	
10-07	Engine Anti-Ice TT2 Probe Heaters	C	2	1	May be inoperative provided: a) Operations are not conducted in known or forecast icing conditions, and b) One Ice Detection System is operative.	
10-08	Engine Anti-Ice Low Pressure Switches	C	2	1	May be inoperative provided: a) Operations are conducted in accordance with AFM Performance data for engine anti-ice ON, b) Operations are not conducted in known or forecast icing conditions, and c) One Ice Detection System is operative.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
10-09	ANTI-ICE ENG L & R "ON" Switch Lights (light function only)	C	2	0		
11-01	Wing Anti-Ice Temperature Sensors	C	4	0	Any or all may be inoperative provided: a) ANTI-ICE WING switch is selected OFF, b) Operations are not conducted in known or forecast icing conditions, and c) One Ice Detection System is operative.	
1)	Outboard Wing Anti-Ice Temperature Sensor Elements	C	4	2	(M) One sensor element per sensor may be inoperative provided Anti-Ice Bleed Pressure Indication Systems operational status is verified before each flight.	
31-01	Air Data Probe Heating System					
1)	Pitot/Static Probe & Base Heaters	B	4	2	(M) Except where enroute operations require its use, same side Probe and/or Base Heaters may be inoperative provided: a) Affected heater is deactivated, b) Standby Pitot Probe Heater is operative, c) Operations are not conducted in visible moisture (including standing water and slush) in any form, d) Operations are not conducted in known or forecast icing conditions, e) One Ice Detection System is operative, and f) Operations are conducted in Day VMC conditions only.	

(Continued)

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 30-4

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
31-01	Air Data Probe Heating System (Cont'd)					
2)	Standby Pitot Probe Heater	B	1	0	(M) May be inoperative provided: a) Heater is deactivated, b) Pitot/Static Probe & Base Heaters are operative, c) Operations are not conducted in visible moisture (including standing water and slush) in any form, d) Operations are not conducted in known or forecast icing conditions, e) One Ice Detection System is operative, and f) Operations are conducted in Day VMC conditions only.	
3)	Static Port Heaters	B	2	1	(M) Except where enroute operations require its use, may be inoperative provided: a) Affected heater is deactivated, b) Operations are not conducted in visible moisture (including standing water and slush) in any form, c) Operations are not conducted in known or forecast icing conditions, d) One Ice Detection System is operative, and e) Operations are conducted in Day VMC conditions only.	
(Continued)						

REVISION NO. 7

PAGE NO. 30-5

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
31-01	Air Data Probe Heating System (Cont'd)					
4)	AOA Sensor Vane & Case Heaters	B	4	2	(M) Same side Vane and/or Case Heaters may be inoperative provided: a) Affected heater is deactivated, b) Operations are not conducted in visible moisture (including standing water and slush) in any form, c) Operations are not conducted in known or forecast icing conditions, d) One Ice Detection System is operative, and e) Operations are conducted in Day VMC conditions only.	
5)	TAT Sensor Heater	B	1	0	(M) May be inoperative provided: a) Heater is deactivated, b) Operations are not conducted in visible moisture (including standing water and slush) in any form, c) Operations are not conducted in known or forecast icing conditions, d) One Ice Detection System is operative, and e) Operations are conducted in Day VMC conditions only.	
31-02	ANTI-ICE L/R PROBES "OFF" Switch Light (light function only)	C	2	0		

REVISION NO. 7

PAGE NO. 30-6

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
40-01	Drain Mast Heaters	C	2	0	(M) Any or all may be inoperative provided: a) Heaters are deactivated, b) Water System is considered inoperative (38-00-01), c) Galley ice drawers remain empty, and d) Lavatory sink and galley drip tray (sink) are placarded "INOPERATIVE-DO NOT USE".	
41-01	Windshield & Side Window Heating System					
1)	Windshield Heating Channels	C	2	1	(M) May be inoperative provided: a) Affected channel is deactivated, b) Operations are not conducted in known or forecast icing conditions, and c) One Ice Detection System is operative.	
		C	2	0	(M) Any or all may be inoperative provided: a) Affected channel is deactivated, b) Side Window Heating Channels are operative, c) Operations are not conducted in known or forecast icing conditions, and d) One Ice Detection System is operative.	
2)	Side Window Heating Channels	C	2	1	(M) Right may be inoperative provided: a) Channel is deactivated, and b) One Windshield Heating Channel is operative.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 30-7

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
80-01	Ice Detection Systems	C	2	1	(M) May be inoperative provided: a) Affected detector is deactivated, and b) Anti-ice systems are turned ON when icing conditions exist as defined in AFM.	
		C	2	0	(M) Any or all may be inoperative for other than night operations provided: a) Affected detector is deactivated and, b) Anti-ice systems are turned ON when icing conditions exist as defined in AFM.	
		C	2	0	(M) Any or all may be inoperative for night operations provided: a) Affected detector is deactivated and, b) Anti-ice systems are turned ON when SAT is between +10 °C and -40 °C.	

REVISION NO. 7

PAGE NO. 31-1

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
21-01	Clock				Deleted, Revision 6.	
1)	Universal Time Co-ordination Display (UTC)	C	1	0		
2)	Flight Time (FT)	C	1	0		
3)	Chronometer (CHR)	C	1	0	(O) May be inoperative provided alternate procedures are established and used to determine elapsed time.	
4)	LCD Display Segments/Mode (Annuns.)	C	-	-	Individual segments or annunciations may be inoperative provided flightcrew can readily determine mode of operation.	
31-01 ***	Flight Data Recorder (FDR)					
1)	Holder of an air carrier or commercial operator certificate	C	-	-	Any in excess of those required by 14 CFR may be inoperative.	

(Continued)

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
31-01 ***	Flight Data Recorder (FDR) (Cont'd)					
		A	-	0	May be inoperative provided: <ol style="list-style-type: none"> a) Cockpit Voice Recorder (CVR) operates normally, b) Airplane is not dispatched from a designated airport as listed in the operator's MEL unless: <ol style="list-style-type: none"> 1. The FDR failure occurs after pushback but prior to takeoff, or 2. The FDR repair was attempted but was not successful, c) In those cases where repair is attempted but not successful, the aircraft may be dispatched on a flight or series of flights until the next designated airport where repair must be accomplished prior to dispatch, and d) Repairs are made within 3 flight-days. 	
	a) FDR Recording Parameters required by 14 CFR	A	-	-	May be inoperative provided: <ol style="list-style-type: none"> a) Cockpit Voice Recorder (CVR) operates normally, and b) Repairs are made within 20 calendar-days. 	
	b) FDR Recording Parameters not required by 14 CFR	A	-	-	May be inoperative provided repairs are made prior to the completion of the next heavy maintenance visit.	
2)	Operators other than a holder of an air carrier or commercial operator certificate	C	-	1	Any in excess of those required by 14 CFR may be inoperative.	
		A	-	0	May be inoperative provided repairs are made as required by 14 CFR.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
31-02 ***	Quick Access Recorder (QAR)	C	1	0	(M)(O) May be inoperative for Flight Data Monitoring (FDM) purposes, provided approved alternate procedures, if appropriate to the FDM program, are established and used.	
		D	1	0	May be inoperative provided procedures do not require its use.	
41-01	Cursor Control Panel (CCP) (Aircraft with Single CCP) (Aircraft 20000 to 20124)					
1)	L/R Toggle Switch	C	1	0	May be inoperative with CCP control active for right MFD provided right MFD is operative.	
		C	1	0	May be inoperative with CCP control active for left MFD.	
2)	Joystick	C	1	0	May be inoperative provided: a) Electronic Checklist is considered inoperative (31-60-01), and b) Maintenance Diagnostic Computer is considered inoperative (45-45-01).	
3)	CKLST Pushbutton	C	1	0	May be inoperative provided Electronic Checklist is considered inoperative (31-60-01).	
4)	SKIP Pushbutton	C	1	0		
(Continued)						

REVISION NO. 7

PAGE NO. 31-4

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
41-01	Cursor Control Panel (CCP) (Aircraft with Single CCP) (Aircraft 20000 to 20124) (Cont'd)					
5)	FRMT Pushbutton	C	1	0	May be inoperative provided Maintenance Diagnostic Computer is considered inoperative (45-45-01). NOTE: Plan Map will not be available unless PLAN pushbutton is installed and operative.	
6)	TFC Pushbutton	C	1	0	May be inoperative provided Maintenance Diagnostic Computer is considered inoperative (45-45-01).	
7)	TR/WX Pushbutton	C	1	0	May be inoperative provided Maintenance Diagnostic Computer is considered inoperative (45-45-01).	
8)	ENTER Pushbutton	C	1	0	May be inoperative provided: a) Electronic Checklist is considered inoperative (31-60-01), and b) Maintenance Diagnostic Computer is considered inoperative (45-45-01).	
9) ***	AUTO Pushbutton	D	1	0		
10) ***	PLAN Pushbutton	D	1	0		
11) ***	SHLDR Pushbutton	D	1	0		
12) ***	SIDE Pushbutton	D	1	0		

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
41-02	Cursor Control Panel (CCP) (Aircraft with dual CCP) (Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 and up)	C	2	1	(O) Right side may be inoperative.	
1)	Joystick	C	2	1		
		C	2	0	May be inoperative provided: a) Maintenance Diagnostic Computer (45-45-01) is considered inoperative, b) Electronic Checklist (31-60-01) is considered inoperative, c) Graphical Weather function (46-10-01) is considered inoperative, and d) Electronic Charts (46-10-01) are considered inoperative.	
2)	JSTK Pushbuttons	C	2	0		
3)	MEM Pushbuttons	D	6	0		
4)	CHART Pushbuttons	C	2	1		
		C	2	0	May be inoperative provided Electronic Charts (46-10-01) are considered inoperative.	
5)	ZOOM Pushbuttons	C	2	1		
		C	2	0	May be inoperative provided: a) Graphical Weather function (46-10-01) is considered inoperative, and b) Electronic Charts (46-10-01) are considered inoperative.	
(Continued)						

REVISION NO. 7

PAGE NO. 31-6

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
41-02	Cursor Control Panel (CCP) (Aircraft with dual CCP) (Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 and up) (Cont'd)					
6)	Orient Pushbuttons (located under the CHART pushbutton)	C	2	1		
		C	2	0	May be inoperative provided: a) Graphical Weather function (46-10-01) is considered inoperative, and b) Electronic Charts (46-10-01) are considered inoperative.	
7)	LWR FRMT Pushbuttons	C	2	0		
8)	UPR MENU Pushbuttons	C	2	1		
9)	LWR MENU Pushbuttons	C	2	1		
10)	ESC Pushbuttons	C	2	0		
11)	PUSH SELECT Pushbuttons (Menu)	C	2	1		
12)	MENU ADV knobs	C	2	1		
13)	DATA Knobs (Menu)	C	2	1		
14)	TFC Pushbuttons	C	2	0		
15)	TR/WX Pushbuttons	C	2	0		

(Continued)

REVISION NO. 7

PAGE NO. 31-7

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
41-02	Cursor Control Panel (CCP) (Aircraft with dual CCP) (Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 and up) (Cont'd)					
16)	ELEC Pushbuttons	C	2	0		
17)	FLT Pushbuttons	C	2	0	NOTE: The Flight Control System (FCS) diagnostics page will not be accessible.	
18)	HYD Pushbutton	C	2	0		
19)	A/ICE Pushbutton	C	2	0	May be inoperative provided the Maintenance Diagnostic Computer (45-45-01) is considered inoperative. NOTE: The Flight Control System (FCS) diagnostics page will not be accessible.	
20)	ECS Pushbutton	C	2	0	May be inoperative provided the Maintenance Diagnostic Computer (45-45-01) is considered inoperative. NOTE: The Flight Control System (FCS) diagnostics page will not be accessible.	
21)	FUEL Pushbutton	C	2	0	May be inoperative provided Maintenance Diagnostic Computer (45-45-01) is considered inoperative.	
22)	CAS Pushbutton	C	2	1	Right side may be inoperative.	
(Continued)						

REVISION NO. 7

PAGE NO. 31-8

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
41-02	Cursor Control Panel (CCP) (Aircraft with dual CCP) (Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 and up) (Cont'd)					
23)	CKLST Pushbutton	C	2	0	May be inoperative provided Electronic Checklist (31-60-01) is considered inoperative.	
24)	SKIP Pushbutton	C	2	0	May be inoperative provided Electronic Checklist (31-60-01) is considered inoperative.	
		D	2	1		
25)	ENTER Pushbutton	C	2	1		
		C	2	0	May be inoperative provided: a) Maintenance Diagnostic Computer (45-45-01) is considered inoperative, b) Electronic Checklist (31-60-01) is considered inoperative, c) Graphical Weather function (46-10-01) is considered inoperative, and d) Electronic Charts (46-10-01) are considered inoperative.	
					NOTE: Flightcrew will lose the ability to select waypoint with joysticks.	
26)	SUMRY Pushbutton	C	2	0	May be inoperative provided the Right MFD is operative.	
		D	2	1		
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 31-9

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
41-02	Cursor Control Panel (CCP) (Aircraft with dual CCP) (Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 and up) (Cont'd)					
27)	STAT Pushbutton	C	2	1		
		C	2	0	May be inoperative provided both FSU (46-10-01) are considered inoperative.	
52-01	BRT/DIM System	C	1	0	May be inoperative provided lighting brightness is acceptable to flightcrew for all intended flight conditions.	
60-01	Electronic Checklist	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
60-02 ***	Digital Voice Checklist	D	1	0	May be inoperative provided normal procedures do not require its use.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 31-10

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
61-01	Adaptive Flight Displays (AFD)					
1)	Aircraft with Single Cursor Control Panel	B	4	3	(O) Right MFD may be inoperative provided: <ul style="list-style-type: none"> a) Cursor Control Panel L/R Toggle Switch is operative to select CCP control to left MFD, b) Two Control Display Units are installed and operative, c) Unaffected displays reversion capabilities are verified operative before each flight, and d) Radio tuning reversion capabilities are verified operative before each flight. NOTE: If right side radio tuning is required, the RIGHT DISPLAYS reversion switch must be selected to PFD REV or the TUNE reversion switch must be selected to CDU ONLY.	
2)	Aircraft with Dual Cursor Control Panel (Aircraft 20125 and subsequent)	B	4	3	(O) Right MFD may be inoperative provided: <ul style="list-style-type: none"> a) Left Cursor Control Panel is operative to control left MFD, b) Two Control Display Units are installed and operative, c) Unaffected displays reversion capabilities are verified operative before each flight, and d) Radio tuning reversion capabilities are verified operative before each flight. NOTE: If right side radio tuning is required, the RIGHT DISPLAYS reversion switch must be selected to PFD REV or the TUNE reversion switch must be selected to CDU ONLY.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 32-2

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

32. Landing Gear

Sequence No.	Item	1	2	3	4	Change Bar
60-01	Nose Landing Gear Doors System	A	1	1	(M) May be inoperative as indicated by NOSE GEAR DOOR caution message provided: a) Nose Landing Gear Door mechanism is visually inspected and does not have any disconnected part, wear, excessive corrosion or cracks, b) Airspeed is limited to 250 KIAS, c) Operations are conducted at or below FL 180, and d) Repairs are made within 3 flight-days.	
					NOTE: For missing Nose Gear Door Seal, refer to the Configuration Deviation List (CDL).	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Cockpit and Instrument Lighting Systems					
1)	Reading, Stowage Lights, and Panels' Backlighting	C	-	-	Individual lights may be inoperative provided: <ol style="list-style-type: none"> a) Remaining Lighting System lights are sufficient to clearly illuminate all instruments, controls and other devices for which they are provided, b) Remaining Lighting System lights are positioned so that direct rays are shielded from flightcrew members' eyes, and c) Lighting configuration and intensity is acceptable to flightcrew. 	
2)	Dome Light LEDs	C	-	-	NOTE: Individual button/switch lights and/or annunciations/indications are excluded from this relief. May be inoperative provided lighting from remaining LEDs is acceptable to flightcrew.	
20-01	Cabin Lighting System (Overhead & Sidewall)	C	-	-	Individual lighting sources may be inoperative provided cabin lighting is sufficient for crewmembers to perform their duties.	
20-02 ***	Floor Accent Lighting System	D	-	0		
21-01	Airstair Lights	D	-	0		

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
23-01	Passenger Notice System (No Smoking/Fasten Seat Belt)	C	1	0	(M) May be inoperative provided: a) Associated passenger seat or lavatory is not occupied from which a passenger notice system (No Smoking/Fasten Seat Belt), is not readily legible, and b) Associated seat or lavatory is blocked and placarded – DO NOT OCCUPY. NOTE: These conditions are not intended to prohibit lavatory use or inspections by crewmembers.	
		C	1	0	(O) May be inoperative and associated passenger seat or lavatory may be occupied provided: a) PA system operates normally, and b) PA system is used to notify passengers and cabin crew when associated sign(s) are placed on or off.	
		C	-	-	(O) May be inoperative provided alternate procedures are established and used to notify cabin occupants.	
		C	1	0	May be inoperative provided no passengers are carried.	
1)	Aural Tone Function	C	1	0	(O) May be inoperative provided alternative procedures are established and used.	
31-01	Service Lighting					
1)	Aft Compartment Lights	D	2	0		
2)	Cargo Loading Light	D	1	0		
3)	Service Panel Lights	D	4	0		

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
41-01	Landing Lights					
1)	Belly Fairing Lights	C	2	1	May be inoperative for night operations provided Nose Light is operative.	
		C	2	1	May be inoperative for night operations provided Taxi Light is operative.	
		C	2	0	Any or all may be inoperative for night operations provided: a) Nose Light is operative, and b) Taxi Light is operative.	
		C	2	0	Any or all may be inoperative for other than night operations.	
***	LoPresti Boom Beam HID Landing Light (STC #ST02893AT)	C	2	0	May be inoperative for other than night operations.	
***	LoPresti Boom Beam HID Landing Light Ballasts (STC #ST02893AT)	C	6	3	May be inoperative provided all factory installed taxi lights are operative.	
***	LoPresti Boom Beam HID Landing Lighting Ballasts with LoPresti Boom Beam Taxi Lights Installed (STC #ST02893AT)	C	6	0	May be inoperative provided both Landing Lights are operative.	
a) ***	Belly Fairing Lights Pulse Function	D	2	0		

(Continued)

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
41-01	Landing Lights (Cont'd)					
2)	Nose Light	C	1	0	May be inoperative for night operations provided: a) One Belly Fairing Light is operative, and b) Taxi light is operative.	
		C	1	0	May be inoperative for night operations provided Belly Fairing Lights are operative.	
		C	1	0	May be inoperative for other than night operations.	
41-02	Taxi Light	C	1	0	May be inoperative for night operations provided: a) Nose Landing Light is operative, and b) One Belly Fairing Landing Light is operative.	
		C	1	0	May be inoperative for night operations provided Belly Fairing Landing Lights are operative.	
		C	1	0	May be inoperative for other than night operations.	
***	LoPresti Boom Beam HID Taxi Light (STC #ST02893AT)	C	2	1		
		C	2	0	May be inoperative for night operations provided Belly Fairing Landing Lights are operative.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 33-5

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
42-01	Navigation Lights (Halogen or LED types)					
1)	Wing Tip Navigation Lights	C	-	2	(M) One on each side must be operative and enabled for operations from sunset to sunrise.	
		C	-	0	Any or all may be inoperative for operations from sunrise to sunset.	
2)	Tail Navigation Lights	C	-	1	(M) One must be operative and enabled for operations from sunset to sunrise.	
		C	-	0	Any or all may be inoperative for operations from sunrise to sunset.	
43-01	Dual Function Anti-Collision Lights					
1)	White Strobes (Upper/Lower)	C	2	0	(O) Any or all may be inoperative for operations from sunrise to sunset.	
2)	Red Beacons (Upper/Lower)	C	2	0	May be inoperative provided the navigation lights and strobe lights are operative and used.	
43-02	Wing Tip Strobe Lights	D	2	0		

45-01	Logo Lights	D	2	0		

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
45-02	Wing Inspection Lights					
1)	Aircraft 20001 to 20143 <u>without</u> SB 100-30-04	C	2	0	May be inoperative provided: a) Aircraft is not operated in known or forecast icing conditions at night, and b) Ground deicing procedures do not require their use.	
2)	Aircraft 20001 to 20143 <u>with</u> SB 100-30-04, Aircraft 20144 and subsequent	C	2	0	(O) May be inoperative provided: a) Both Ice Detectors are operative, b) Wing ANTI-ICE is turned ON below 210 kn when icing conditions as defined in the AFM exist or anticipated, and c) Ground deicing procedures do not require their use.	
50-01	Exterior Emergency Lights	A	3	0	(O) Any or all may be inoperative for night operations provided: a) Minimum Flightcrew as defined in the AFM are the only occupants of the aircraft, b) Alternate procedures are established and used, and c) Repairs are made within 1 flight-day.	
		C	3	0	Any or all may be inoperative for other than night operations.	
50-02	Exit Identifiers and Emergency Escape Path Marking System (Seat Mounted Lighting System)					
1)	Passengers are Carried	-	1	1	System must be operative.	

(Continued)

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 33-7

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
50-02	Exit Identifiers and Emergency Escape Path Marking System (Seat Mounted Lighting System) (Cont'd)					
a)	Path Marking Light Fixtures (Bruce Industries Lights STC ST01569LA)	C	-	-	A minimum of one out of two bulbs in each fixture must be operative.	
b)	Exit Identifiers					
I)	Bruce Industries Light Model BR9661-series STC ST01569LA	C	2	2	A minimum of two out of five bulbs within each fixture must be operative.	
II)	EMTEQ LED type (P/N C300 ELES-001 and C300 ELES-002 only) Aircraft, 20139, 20143, 20146, 20148 and up.	C	4	3	A minimum of three full LED rows out of four within each fixture must be operative.	
2)	No Passengers are Carried	B	1	0		

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 34-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Integrated Standby Instrument System (ISIS)					
1)	ILS Function	C	1	0		
2)	Attitude Function	B	1	0	(M) May be inoperative provided: a) Operations are conducted in Day VMC only, b) Operations are not conducted into known or forecast over-the-top conditions, and c) Instrument attitude display is covered.	
10-02	Non-stabilized Magnetic Compass (Standby Compass)	B	1	0	(O) May be inoperative provided operations are conducted under positive radar control by ATC during the enroute flight phase.	
		B	1	0	(O) May be inoperative for flights that are entirely within areas of magnetic unreliability provided operations are conducted in conjunction with approved Free Gyro Navigation Techniques.	
11-01	Altitude Alerting System	A	1	0	(O) May be inoperative provided: a) Autopilot with altitude hold, and altitude capture operates normally, b) A minimum of two altitude tapes are operative on the displays, c) Enroute operations do not require its use, d) Airplane does not depart from a designated airport (as listed in the operator's MEL) where repair or replacement can be made, and e) Repairs are made within 3 flight-days.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
30-01 ***	Steep Approach Landing Push Button Annunciator					
1)	"ARM" or "ON" Light Function	B	1	0	May be inoperative provided: a) Operations with Steep Approach are not conducted, and b) STEEP APPR PBA is verified OFF.	
2)	Switch Failed In "OFF"	B	1	0	May be inoperative provided operations with Steep Approach are not conducted.	
34-01 ***	Synthetic Vision System (SVS) (including Database)	D	1	0	(O) May be inoperative provided SVS is selected OFF. NOTE: SVS is considered inoperative if associated database is out of date.	
41-01	Weather Radar System	D	1	-	Any in excess of those required by Regulations may be inoperative.	
42-01	Terrain Awareness Warning System (TAWS) (If Class A TAWS Equipment Required)					
1)	GPWS	A	1	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within 2 flight-days.	
a)	Modes 1-4	A	4	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within 2 flight-days.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
42-01	Terrain Awareness Warning System (TAWS) (Cont'd)					
	(If Class A TAWS Equipment Required) (Cont'd)					
1)	GPWS (Cont'd)					
b)	Test Mode	A	1	0	May be inoperative provided: a) GPWS/TAWS is considered inoperative, and b) Repairs are made within 2 flight-days.	
c)	Glideslope Deviation (Mode 5)	B	1	0		
d)	Advisory Callouts	B	-	0	(O) May be inoperative provided alternate procedures are established and used.	
		C	-	0	(O) May be inoperative provided: a) Advisory callout is not required by 14 CFR, and b) Alternate procedures are established and used.	
e) ***	Windshear Mode (Mode 7)	B	1	0	(O) May be inoperative provided alternate procedures are established and used.	
					NOTE: Operator's alternate procedures should include reviewing windshear avoidance and windshear recovery procedures.	
		C	1	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Windshear Detection and Avoidance (predictive) operates normally.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
42-01	Terrain Awareness Warning System (TAWS) (Cont'd)					
	(If Class A TAWS Equipment Required) (Cont'd)					
2) ***	Terrain System -Forward Looking Terrain Avoidance (FLTA) and Premature Descent Alert (PDA) Functions	B	1	0	(O) May be inoperative provided alternate procedures are established and used.	
3) ***	Runway Awareness and Advisory System (RAAS) (Includes Smart Runway and Smart Landing (SR/SL) functions) (If Class B TAWS Equipment Required)	C	1	0	(O) May be inoperative provided the RAAS system is selected OFF.	
1)	GPWS	A	1	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within 2 flight-days.	
a)	Modes 1 & 3	A	2	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within 2 flight-days.	
b)	Test mode	A	1	0	May be inoperative provided: a) GPWS/TAWS is considered inoperative, and b) Repairs are made within 2 flight-days.	
c) ***	Mode 2, 4 & 5	C	3	0		
(Continued)						

REVISION NO. 7

PAGE NO. 34-6

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
42-01	Terrain Awareness Warning System (TAWS) (Cont'd)					
	(If Class B TAWS Equipment Required) (Cont'd)					
1)	GPWS (Cont'd)					
d)	Advisory Callouts	B	-	0	(O) May be inoperative provided alternate procedures are established and used.	
		C	-	0	(O) May be inoperative provided: a) Advisory callout is not required by 14 CFR, and b) Alternate procedures are established and used.	
e) ***	Windshear Mode (Reactive)	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
2) ***	Terrain System - Forward Looking Terrain Avoidance (FLTA) and Premature Descent Alert (PDA) Functions	B	1	0		
3)	Terrain Displays (Terrain Overlay on MFD or PFD)	C	-	0		
4) ***	Runway Awareness and Advisory System (RAAS) (Includes Smart Runway and Smart Landing (SR/SL) functions)	C	1	0	(O) May be inoperative provided the RAAS system is selected OFF.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
43-01	Traffic Collision Avoidance System (TCAS) TCAS II (Including TCAS function of the Traffic Surveillance System (TSS) Aircraft 20408 and subs)	B	-	0	(M) May be inoperative provided: a) The system is deactivated and secured, and b) Enroute or approach procedures do not require its use.	
		C	-	0	(M) May be inoperative provided: a) It is not required by 14 CFR, b) System is deactivated and secured, and c) Enroute or approach procedures do not require its use.	
1)	Combined Traffic Alert (TA) and Resolution Advisory (RA) Dual Display Systems	C	2	1	May be inoperative on the non-flying pilot side provided: a) TA and RA visual display is operative on the flying pilot side, and b) TA and RA audio function is operative on the flying pilot side.	
2)	Resolution Advisory (RA) Display System(s)	C	2	1	May be inoperative on non-flying pilot side.	
		C	-	0	(O) May be inoperative provided: a) Traffic Alert (TA) visual display and audio functions are operative, b) TA only mode is selected by the crew, and c) Enroute or approach procedures do not require its use.	
3)	Traffic Alert (TA) Display System(s)	C	-	0	(O) May be inoperative provided: a) Resolution Advisory (RA) visual display and audio functions are operative, and b) Enroute or approach procedures do not require its use.	
4)	Audio Functions	B	1	0	May be inoperative provided enroute or approach procedures do not require TCAS use.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
44-01	Radio Altimeter	A	1	0	(M)(O) May be inoperative provided: a) Radio Altimeter is deactivated, b) Spoiler system is verified operative before each flight, c) TAWS is considered inoperative (34-42-01), d) TCAS is considered inoperative (34-43-01), e) Approach minimums or operating procedures are not dependent on its use, f) Repairs are made within 2 flight-days, and g) Operations with steep approach are not conducted.	
46-01 ***	Lightning Detection System	D	1	0		
51-01	VHF Navigation Systems (VOR/ILS)	C	2	1	NAV 2 may be inoperative.	
51-02	Automatic Direction Finding (ADF) System	D	-	-	Any in excess of those required by Regulations may be inoperative.	
51-03	Marker Beacon Systems	C	2	0	Any or all may be inoperative provided alternate procedures are established and used.	
		D	2	0	Any or all may be inoperative provided routine procedures do not require its use.	
53-01	Distance Measuring Equipment (DME) Systems	D	-	-	Any in excess of those required by Regulations may be inoperative.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
54-01	ATC Transponders and Automatic Altitude Reporting Systems (Including TCAS function of the Traffic Surveillance System (TSS) Aircraft 20408 and subs)	B	2	0	May be inoperative provided: a) Operations do not require its use, and b) Prior to flight, approval is obtained from ATC facilities having jurisdiction over the planned route of flight.	
		D	2	1	Any in excess of those required by 14 CFR may be inoperative. NOTE: Transponder and Flight Director/Autopilot must use same side ADC data for RVSM operations.	
1)	Elementary and Enhanced Downlink Aircraft Reportable Parameters Not Required by 14 CFR	A	2	0	May be inoperative provided: a) Operations do not require its use, b) Repairs are made prior to completion of the next heavy maintenance visit.	
55-01	Global Positioning System (GPS)	A	2	0	(O) Except where enroute operations or approach procedures require its use, may be inoperative for 2 flight-days provided: a) Terrain/Obstacle Awareness functions of Terrain Awareness Warning System are considered inoperative (34-42-01), b) Synthetic Vision System (34-34-01 ***) is considered inoperative, and c) Alternate procedures are established and used.	
		D	2	1	NOTE: At least one GPS system is required for ADS-B operations. May be inoperative except where enroute operations or approach procedures require dual GPS.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 34-10

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
56-01 ***	Automatic Dependent Surveillance-Broadcast (ADS-B) System	C	-	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) It is not required by 14 CFR. NOTE: Any ADS-B function that operates normally may be used.	
		D	-	0	May be inoperative provided: a) Enroute operations do not require its use, and b) It is not required by 14 CFR. NOTE: Any ADS-B function that operates normally may be used.	
		C	-	1	One must be operative as required by 14 CFR. NOTE: Any ADS-B function that operates normally may be used.	
***	ADS-B Out Extended Squitter Transmissions	C	-	0	(O) May be inoperative provided: a) Alternate procedures are established and used, b) Authorization is obtained from ATC facilities having jurisdiction over planned route of flight, and c) It is not required by 14 CFR. NOTE: Any ADS-B function that operates normally may be used.	
		C	-	1	One must be operative as required by 14 CFR. NOTE: Any ADS-B function that operates normally may be used.	

(Continued)

REVISION NO. 7

PAGE NO. 34-11

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
56-01 ***	Automatic Dependent Surveillance-Broadcast (ADS-B) System (Cont'd)					
***	ADS-B Out UAT Transmissions	C	-	0	(O) May be inoperative provided: a) Enroute operations do not require its use, b) Authorization is obtained from ATC facilities having jurisdiction over planned route of flight, and c) It is not required by 14 CFR.	
					NOTE: Any ADS-B function that operates normally may be used.	
		C	-	1	One must be operative as required by 14 CFR.	
					NOTE: Any ADS-B function that operates normally may be used.	
***	ADS-B In Transmissions	C	-	0	(O) May be inoperative provided alternate procedures are established and used.	
					NOTE: Any ADS-B function that operates normally may be used.	
		D	-	0	May be inoperative provided operations do not require its use.	
					NOTE: Any ADS-B function that operates normally may be used.	

REVISION NO. 7

PAGE NO. 34-12

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
61-01	Flight Management System (FMS)					
1)	Flight Management Computers	C	-	1	Right Flight Management Computer (FMC) may be inoperative provided Fuel Quantity Gaging Computer Channels (28-41-02) are operative.	
					NOTE: (Aircraft with SB 100-34-10) When operating with one FMS inoperative, FMS computed take off and approach performance must be verified using applicable AFM data.	
2)	Control Display Units	C	-	1	Right may be inoperative provided Adaptive Flight Displays are operative.	
3)	Navigation Database	A	-	0	May be inoperative provided: <ol style="list-style-type: none"> a) Operations do not require its use, b) It is not used in a primary navigation system required by 14 CFR, c) Alternate procedures are developed and used, d) The ICAO Flight Plan is updated (as required) to notify ATC of the navigation equipment status of the aircraft, and e) Is repaired within 10 flight-days. 	
					NOTE: An out-of-currency or out of date navigation database is not authorized MMEL relief per 14 CFR.	
62-01 ***	Data Base Unit	D	1	0		

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

35. Oxygen

Sequence No.	Item	1	2	3	4	Change Bar
12-01	EICAS Oxygen Quantity Readout	C	1	0	(O) May be inoperative provided Ground Service Panel Pressure Gauge is operative and checked before each flight.	
12-02	Oxygen Overpressure Relief Indicator	C	1	0	(O) May be inoperative (missing) provided alternate procedure is used to ensure that oxygen supply is at or above minimum requirements for flight.	
13-01	Ground Service Panel Pressure Gauge	C	1	0	May be inoperative provided EICAS Oxygen Quantity Readout is operative.	
13-02	Bottle(s) Pressure Gauge	C	-	0		
13-03	Filler Valve (Service Panel)	C	1	0	(M) May be inoperative provided replenished bottle(s) is installed with adequate oxygen for flight.	
20-02	Passenger Oxygen Circuit	B	1	0	(O) May be inoperative provided: a) PAX OXYGEN Control Panel rotary selector switch is selected to OFF, b) Operations are conducted so that minimum enroute altitude (MEA) is at or below 13,000 ft. MSL, c) Operations are conducted at or below FL 250, d) Portable oxygen units are provided for all crew members and for 10 percent of passengers for half an hour (supplemental oxygen), and e) Procedures are established to ensure that passengers are appropriately briefed.	
		C	1	0	May be inoperative provided: a) PAX OXYGEN Control Panel rotary selector switch is selected to OFF, and b) Passengers are not carried.	

(Continued)

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

35. Oxygen

Sequence No.	Item	1	2	3	4	Change Bar
20-02	Passenger Oxygen Circuit (Cont'd)					
1)	Automatic Presentation System	B	1	0	(M)(O) May be inoperative provided: a) Manual deployment is verified operative, and b) Operations are conducted at or below FL 300. NOTE: Flight planning has to take into account higher oxygen consumption in manual Deploy Mode.	
20-03 ***	Therapeutic Oxygen Circuit	D	1	0	May be inoperative provided PAX OXYGEN THERAPEUTIC switch is selected OFF.	
30-01	Portable Protective Breathing Equipment (PBE)	D	-	-	Any in excess of those required by 14 CFR may be inoperative or missing provided: a) Inoperative PBE remains in a certified location or is removed from the aircraft, b) Location placarding is removed or obscured, and c) Required distribution is maintained. NOTE: Inoperative PBE units removed from a certified location, or removed from the aircraft, are subject to 49 CFR dangerous goods regulations.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05	B	2	0	(M)(O) Any or all may be inoperative provided: a) Valves are secured CLOSED, b) XBLEED valve is selected OPEN, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) Trim Air Inlet Temperature Sensor is verified operative once each flight-day, f) Pack Inlet Temperature Sensor is verified operative once each flight-day, g) Bleed Loops are verified operative before each flight, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 190, and j) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
		B	2	0	(M)(O) Any or all may be inoperative provided: a) Valves are secured CLOSED, b) XBLEED valve is selected CLOSED, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) Trim Air Inlet Temperature Sensor is verified operative once each flight-day, f) Right Bleed Loop is verified operative before each flight, g) Right Flow Control Valve is operative, h) Trim Air System is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 190, and l) Operations are conducted within one hour from a suitable airport.	
		C	2	0	(M)(O) Any or all may be inoperative provided: a) Valves are secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-3

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
a)	L/H Bleed Valve	B	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) XBLEED valve is selected OPEN, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are verified operative before each flight, f) Trim Air Inlet Temperature Sensor is operative, g) Pack Inlet Temperature Sensor is verified operative once each flight-day, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-4

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
a)	L/H Bleed Valve (Cont'd)	B	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) XBLEED valve is selected CLOSED, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Right Bleed Loop is operative, f) Right Flow Control Valve is operative, g) Trim Air System is operative, h) Trim Air Inlet Temperature Sensor is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 250, and l) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-5

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
b)	R/H Bleed Valve	B	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) XBLEED valve is selected OPEN, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are verified operative before each flight, f) Trim Air Inlet Temperature Sensor is verified operative once each flight-day, g) Pack Inlet Temperature Sensor is operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-6

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
b)	R/H Bleed Valve (Cont'd)	B	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) XBLEED valve is selected CLOSED, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Left Bleed Loop is operative, f) Left Flow Control Valve is operative, g) Pack Inlet Temperature Sensor is operative, h) APU bleed is used for engines start only, i) Ram Air Valve is verified operative, j) Operations are conducted at or below FL 250, and k) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)	C	2	0	(M)(O) Any or all may be inoperative provided: a) Valves are secured CLOSED, b) XBLEED valve is selected CLOSED, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) Trim Air Inlet Temperature Sensor is verified operative once each flight-day, f) Right Bleed Loop is verified operative before each flight, g) Right Flow Control Valve is operative, h) Trim Air System is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 190, and l) Operations are conducted within one hour from a suitable airport.	
		C	2	0	(M)(O) Any or all may be inoperative provided: a) Valves are secured CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	

(Continued)

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-9

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)					
a)	L/H Bleed Valve	C	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) XBLEED valve is selected OPEN, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are verified operative before each flight, f) Trim Air Inlet Temperature Sensor is operative, g) Pack Inlet Temperature Sensor is verified operative once each flight-day, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-10

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)					
a)	L/H Bleed Valve	C	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) XBLEED valve is selected CLOSED, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Right Bleed Loop is operative, f) Right Flow Control Valve is operative, g) Trim Air System is operative, h) Trim Air Inlet Temperature Sensor is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 250, and l) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-11

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)					
b)	R/H Bleed Valve	C	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) XBLEED valve is selected OPEN, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are verified operative before each flight, f) Trim Air Inlet Temperature Sensor is verified operative once each flight-day, g) Pack Inlet Temperature Sensor is operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-12

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Bleed Valves (IPV) (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)					
b)	R/H Bleed Valve (Cont'd)	C	1	0	(M)(O) May be inoperative provided: a) Valve is secured CLOSED, b) XBLEED valve is selected CLOSED, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Left Bleed Loop is operative, f) Left Flow Control Valve is operative, g) Pack Inlet Temperature Sensor is operative, h) APU bleed is used for engines start only, i) Ram Air Valve is verified operative, j) Operations are conducted at or below FL 250, and k) Operations are conducted within one hour from a suitable airport.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-13

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05	B	2	0	(O) Any or all may be inoperative provided: a) Bleed Valves are selected CLOSED, b) XBLEED valve is selected CLOSED, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) Right Bleed Loop is operative, f) Right Flow Control Valve is operative, g) Trim Air System is operative, h) Trim Air Inlet Temperature Sensor is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 190, and l) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)	B	2	0	(O) Any or all may be inoperative provided: <ol style="list-style-type: none"> a) Bleed Valves are selected CLOSED, b) XBLEED valve is selected OPEN, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) Trim Air Inlet Temperature Sensor is operative, f) Pack Inlet Temperature Sensor is operative, g) Bleed Loops are operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 190, and j) Operations are conducted within one hour from a suitable airport. (O) Any or all may be inoperative provided: <ol style="list-style-type: none"> a) Bleed Valves are selected CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) Ram Air Valve is selected OPEN, d) PRESSURIZATION EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL. 	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
a)	L/H Bleed Pressure Indication System	B	1	0	(O) May be inoperative provided: <ol style="list-style-type: none"> a) L/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected OPEN, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are operative, f) Trim Air Inlet Temperature Sensor is operative, g) Pack Inlet Temperature Sensor is operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport. 	
(Continued)						

REVISION NO. 7

PAGE NO. 36-16

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
a)	L/H Bleed Pressure Indication System	B	1	0	(O) May be inoperative provided: <ol style="list-style-type: none"> a) L/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected OPEN, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are operative, f) Trim Air Inlet Temperature Sensor is operative, g) Pack Inlet Temperature Sensor is operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport. 	
(Continued)						

REVISION NO. 7

PAGE NO. 36-17

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
a)	L/H Bleed Pressure Indication System (Cont'd)					
		B	1	0	(O) May be inoperative provided:	
					a) L/H Bleed Valve is selected CLOSED,	
					b) XBLEED Valve is selected CLOSED,	
					c) R/H Bleed Valve is operative,	
					d) R/H Environmental Control Bleed Pressure Indication System is operative,	
					e) Right Bleed Loop is operative,	
					f) Right Flow Control Valve is operative,	
					g) Trim Air System is operative,	
					h) Trim Air Inlet Temperature Sensor is operative,	
					i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM,	
					j) Ram Air Valve is verified operative,	
					k) Operations are conducted at or below FL 250, and	
					l) Operations are conducted within one hour from a suitable airport.	
					(Continued)	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
b)	R/H Bleed Pressure Indication System	B	1	0	(O) May be inoperative provided: a) R/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected OPEN, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are operative, f) Trim Air Inlet Temperature Sensor is operative, g) Pack Inlet Temperature Sensor is operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-19

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
1)	Aircraft 20003 to 20100 <u>without</u> SB 100-21-05 (Cont'd)					
b)	R/H Bleed Pressure Indication System (Cont'd)					
		B	1	0	(O) May be inoperative provided: a) R/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected CLOSED, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Left Bleed Loop is operative, f) Left Flow Control Valve is operative, g) Pack Inlet Temperature Sensor is operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-20

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs	C	2	0	(O) Any or all may be inoperative provided: a) Bleed Valves are selected CLOSED, b) XBLEED valve is selected CLOSED, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) Right Bleed Loop is operative, f) Right Flow Control Valve is operative, g) Trim Air System is operative, h) Trim Air Inlet Temperature Sensor is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 190, and l) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
2)	Aircraft 20003 to 20100 with SB 100-21-05, Aircraft 20101 and subs (Cont'd)	C	2	0	(O) Any or all may be inoperative provided: <ol style="list-style-type: none"> a) Bleed Valves are selected CLOSED, b) XBLEED valve is selected OPEN, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) Trim Air Inlet Temperature Sensor is operative, f) Pack Inlet Temperature Sensor is operative, g) Bleed Loops are operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 190, and j) Operations are conducted within one hour from a suitable airport. 	
		C	2	0	(O) Any or all may be inoperative provided: <ol style="list-style-type: none"> a) Bleed Valves are selected CLOSED, b) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, c) Ram Air Valve is selected OPEN, d) PRESSURIZATION EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL. 	
(Continued)						

REVISION NO. 7

PAGE NO. 36-22

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)					
a)	L/H Bleed Pressure Indication System	C	1	0	(O) May be inoperative provided: <ol style="list-style-type: none"> a) L/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected OPEN, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are operative, f) Trim Air Inlet Temperature Sensor is operative, g) Pack Inlet Temperature Sensor is operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport. 	

(Continued)

REVISION NO. 7

PAGE NO. 36-23

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)					
a)	L/H Bleed Pressure Indication System (Cont'd)					
		C	1	0	(O) May be inoperative provided:	
					a) R/H Bleed Valve is selected CLOSED,	
					b) XBLEED valve is selected CLOSED,	
					c) L/H Bleed Valve is operative,	
					d) L/H Environmental Control Bleed Pressure Indication System is operative,	
					e) Left Bleed Loop is operative,	
					f) Left Flow Control Valve is operative,	
					g) Pack Inlet Temperature Sensor is operative,	
					h) Ram Air Valve is verified operative,	
					i) Operations are conducted at or below FL 250, and	
					j) Operations are conducted within one hour from a suitable airport.	
					(Continued)	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-24

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)					
b)	R/H Bleed Pressure Indication System	C	1	0	(O) May be inoperative provided: a) R/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected OPEN, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Bleed Loops are operative, f) Trim Air Inlet Temperature Sensor is operative, g) Pack Inlet Temperature Sensor is operative, h) Ram Air Valve is verified operative, i) Operations are conducted at or below FL 250, and j) Operations are conducted within one hour from a suitable airport.	
(Continued)						

REVISION NO. 7

PAGE NO. 36-25

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
10-02	Environmental Control Bleed Pressure Indication Systems (Cont'd)					
2)	Aircraft 20003 to 20100 <u>with</u> SB 100-21-05, Aircraft 20101 and subs (Cont'd)					
b)	R/H Bleed Pressure Indication System (Cont'd)					
		C	1	0	(O) May be inoperative provided:	
					a) R/H Bleed Valve is selected CLOSED,	
					b) XBLEED valve is selected CLOSED,	
					c) L/H Bleed Valve is operative,	
					d) L/H Environmental Control Bleed Pressure Indication System is operative,	
					e) Left Bleed Loop is operative,	
					f) Left Flow Control Valve is operative,	
					g) Pack Inlet Temperature Sensor is operative,	
					h) Ram Air Valve is verified operative,	
					i) Operations are conducted at or below FL 250, and	
					j) Operations are conducted within one hour from a suitable airport.	
10-03	AIR COND/BLEED L/R BLEED "OFF" Switch Light (light function only)	C	2	0		
10-04	AIR COND/BLEED XBLEED "-" Switch Light (light function only)	C	1	0		

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-26

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops					
1)	Environmental Control System Leak Detection Loops	B	7	0	(O) Any or all may be inoperative provided: a) Bleed Valves are selected CLOSED, b) Anti-ice System Wing/Pylon Leak Detection Loops are operative, c) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, d) Ram Air Valve is selected OPEN, e) PRESSURIZATION EMER DEPRESS switch is selected ON, f) APU bleed is used for engines start only, g) Cross bleed start procedure is not used for engine start in flight and on ground, and h) Operations are conducted unpressurized at or below 9000 ft. MSL.	
a)	Pylon Loops	C	2	0	Any or all may be inoperative provided Anti Ice System Wing/Pylon Leak Detection Loop on affected side is operative. NOTE: L/R Pylon loops include L/R Powerplant interface to L/R Bleed Valve (IPV).	
(Continued)						

REVISION NO. 7

PAGE NO. 36-27

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
1)	Environmental Control System Leak Detection Loops (Cont'd)					
b)	Bleed Loops (Aircraft 20003 to 20100 without SB 100-21-05)	B	2	1	(O) Right may be inoperative provided: <ol style="list-style-type: none"> a) R/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected CLOSED, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Left Flow Control Valve is operative, f) Pack Inlet Temperature Sensor is operative, g) APU bleed is used for engines start only, h) Cross bleed start procedure is not used for engines start in flight and on ground, i) Ram Air Valve is verified operative, j) Operations are conducted at or below FL 250, and k) Operations are conducted within one hour from a suitable airport. <p>NOTE: The right bleed ducting loop includes all the ducting downstream of the right Bleed Valve (IPV) down to the right Flow Control Valve (FCV) and the right ATS duct. The right bleed loop also includes the APU and high pressure ground connection ducting.</p>	
(Continued)						

REVISION NO. 7

PAGE NO. 36-28

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
1)	Environmental Control System Leak Detection Loops (Cont'd)					
b)	Bleed Loops (Aircraft 20003 to 20100 without SB 100-21-05) (Cont'd)	B	2	1	(O) Left may be inoperative provided: a) L/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected CLOSED, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Right Flow Control Valve is operative, f) Trim Air System is operative, g) Trim Air Inlet Temperature Sensor is operative, h) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, i) Cross bleed start procedure is not used for engine start in flight and on ground, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 250, and l) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
1)	Environmental Control System Leak Detection Loops (Cont'd)					
b)	Bleed Loops (Aircraft 20003 to 20100 without SB 100-21-05) (Cont'd)					
					(O) Left may be inoperative provided: <ol style="list-style-type: none"> a) L/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected CLOSED, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) R/H Environmental Control Bleed Pressure Indication System is operative, f) Right Flow Control Valve is operative, g) Trim Air System is operative, h) Trim Air Inlet Temperature Sensor is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Cross bleed start procedure is not used for engine start in flight and on ground, k) Ram Air Valve is verified operative, l) Operations are conducted at or below FL 190, and m) Operations are conducted within one hour from a suitable airport. <p>NOTE: The left bleed ducting loop includes all the ducting downstream of the left Bleed Valve (IPV) down to the left Flow Control Valve (FCV) and the left ATS duct.</p>	
					(Continued)	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
1)	Environmental Control System Leak Detection Loops (Cont'd)					
c)	Bleed Loops (Aircraft 20003 to 20100 with SB 100-21-05), Aircraft 20101 and subs	C	2	1	(O) Right may be inoperative provided: <ol style="list-style-type: none"> a) R/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected CLOSED, c) L/H Bleed Valve is operative, d) L/H Environmental Control Bleed Pressure Indication System is operative, e) Left Flow Control Valve is operative, f) Pack Inlet Temperature Sensor is operative, g) APU bleed is used for engines start only, h) Cross bleed start procedure is not used for engines start in flight and on ground, i) Ram Air Valve is verified operative, j) Operations are conducted at or below FL 250, and k) Operations are conducted within one hour from a suitable airport. <p>NOTE: The right bleed ducting loop includes all the ducting downstream of the right Bleed Valve (IPV) down to the right Flow Control Valve (FCV) and the right ATS duct. The right bleed loop also includes the APU and high pressure ground connection ducting.</p>	
(Continued)						

REVISION NO. 7

PAGE NO. 36-31

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
1)	Environmental Control System Leak Detection Loops (Cont'd)					
c)	Bleed Loops (Aircraft 20003 to 20100 with SB 100-21-05), Aircraft 20101 and subs (Cont'd)					
		C	2	1	(O) Left may be inoperative provided: a) L/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected CLOSED, c) R/H Bleed Valve is operative, d) R/H Environmental Control Bleed Pressure Indication System is operative, e) Right Flow Control Valve is operative, f) Trim Air System is operative, g) Trim Air Inlet Temperature Sensor is operative, h) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, i) Cross bleed start procedure is not used for engine start in flight and on ground, j) Ram Air Valve is verified operative, k) Operations are conducted at or below FL 250, and l) Operations are conducted within one hour from a suitable airport.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
1)	Environmental Control System Leak Detection Loops (Cont'd)					
c)	Bleed Loops (Aircraft 20003 to 20100 with SB 100-21-05), Aircraft 20101 and subs (Cont'd)	C	2	1	(O) Left may be inoperative provided: <ol style="list-style-type: none"> a) L/H Bleed Valve is selected CLOSED, b) XBLEED valve is selected CLOSED, c) APU is operative and used throughout flight, d) APU Load Control Valve is operative, e) R/H Environmental Control Bleed Pressure Indication System is operative, f) Right Flow Control Valve is operative, g) Trim Air System is operative, h) Trim Air Inlet Temperature Sensor is operative, i) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to NORM, j) Cross bleed start procedure is not used for engine start in flight and on ground, k) Ram Air Valve is verified operative, l) Operations are conducted at or below FL 190, and m) Operations are conducted within one hour from a suitable airport. <p>NOTE: The left bleed ducting loop includes all the ducting downstream of the left Bleed Valve (IPV) down to the left Flow Control Valve (FCV) and the left ATS duct.</p>	
(Continued)						

REVISION NO. 7

PAGE NO. 36-33

DATE: 03/12/2021

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
1)	Environmental Control System Leak Detection Loops (Cont'd)					
d)	Pack Loops	C	2	1		
		C	2	0	NOTE: The Air Conditioning System (ACS) pack ducting loop includes all the ducting downstream of the left FCV to the left Ozone Converter, left ACS Pack and Pre-cooler Cross-over Valve.	
e)	Trim Loop	B	1	0	May be inoperative provided Trim Air System is considered inoperative (21-61-03). NOTE: The trim air ducting loop includes all the ducting downstream of the right FCV to the mixing manifold.	
2)	Anti-Ice System Leak Detection Loops					
a)	Wing/Pylon Loops	C	2	0	Any or all may be inoperative provided: a) Environmental Control System Leak Detection Pylon Loop on affected side is operative, and b) Anti-Ice System Leak Detection Fuselage/Wing Loop on affected side is operative. NOTE: The L/R Wing/Pylon loops include the L/R powerplant interface to the IPV (part of ACS system) and HPV.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-34

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
2)	Anti-Ice System Leak Detection Loops (Cont'd)					
a)	Wing/Pylon Loops (Cont'd)					
		C	2	0	Any or all may be inoperative provided: a) Environmental Control System Leak Detection Pylon Loop on the affected side is operative, b) ANTI-ICE WING switch is selected OFF, c) Operations are not conducted in known or forecast icing conditions, and d) One Ice Detection System is operative. NOTE: The L/R Wing/Pylon loops include the L/R powerplant interface to the IPV (part of ACS system) and HPV.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 36-35

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
20-01	Leak Detection Loops (Cont'd)					
2)	Anti-Ice System Leak Detection Loops (Cont'd)					
b)	Fuselage/Wing Loops	C	2	0	Any or all may be inoperative provided Anti-Ice System Leak Detection Wing/Pylon Loop on affected side is operative.	
		C	2	0	Any or all may be inoperative provided: a) ANTI-ICE WING switch is selected OFF, b) Operations are not conducted in known or forecast icing conditions, and c) One Ice Detection System is operative.	
					NOTE: The L/R Fuselage/Wing loops include the ducting downstream of the L/R HPV down to the end of the L/R piccolo (including the Cross Bleed Valve).	

REVISION NO. 6
 DATE: 07/30/2018

PAGE NO. 38-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

38. Water/Waste

Sequence No.	Item	1	2	3	4	Change Bar
00-01	Water System					
1)	Potable Water System	C	1	0	(M) Individual components may be inoperative provided: a) Associated components are deactivated or isolated, and b) Associated components are verified not to have leaks. NOTE: Any portion of system which operates normally may be used.	
		C	1	0	(M) May be inoperative provided: a) System is drained, and b) Procedures are established to ensure that system is not serviced.	
2)	Lavatory Waste System	C	1	0	(M) Individual components may be inoperative provided: a) Associated components are deactivated or isolated, and b) Associated components are verified not to have leaks. NOTE: Any portion of system which operates normally may be used.	
		C	1	0	(M) Associated lavatory system may be inoperative provided: a) Associated components are deactivated or isolated to prevent leaks, and b) Associated lavatory door is secured closed and placarded INOPERATIVE – DO NOT ENTER. NOTE: These provisions are not intended to prohibit inspections by crewmembers.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 45-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

45. Central Maintenance System						
Sequence No.	Item	1	2	3	4	Change Bar
45-01	Maintenance Diagnostic Computer (MDC)	C	1	0	(M) May be inoperative provided alternate procedures are established and used.	

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

46. Information Systems

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Integrated Flight Information System (IFIS)					
1)	File Server Unit (FSU)					
a)	(Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 to 20181 with SB 100-46-02) (Aircraft 20182 and up with SB 100-46-01)	C	2	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	2	0	May be inoperative provided routine procedures do not require its use. NOTE: Any function which operates normally may be used.	
b)	(Aircraft 20182 and up without SB 100-46-01)	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	1	0	May be inoperative provided routine procedures do not require its use. NOTE: Any function which operates normally may be used.	
2)	Electronic Charts (Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 to 20181 with SB 100-46-02) (Aircraft 20182 and up with SB 100-46-01) (Aircraft 20182 and up without SB 100-46-01)	C	2	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	2	0	May be inoperative provided routine procedures do not require its use.	
(Continued)						

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

46. Information Systems

Sequence No.	Item	1	2	3	4	Change Bar
10-01	Integrated Flight Information System (IFIS) (Cont'd)					
3) ***	Graphical Weather Function (Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 and up with SB 100-46-03)	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	1	0	May be inoperative provided routine procedures do not require its use.	
4) ***	Enhanced Map Overlay Function (Aircraft 20000 to 20124 with STC ST01732LA-D) (Aircraft 20125 to 20181 with SB 100-46-02) (Aircraft 20182 and up with SB 100-46-01)	C	1	0	(O) May be inoperative on either or both MFDs provided alternate procedures are established and used.	
		D	1	0	May be inoperative on either or both MFDs provided routine procedures do not require its use.	
5) ***	Database Applications (Electronic Chart, Graphical Weather, Enhanced Map Overlay)	C	-	0	Any or all individual database may be inoperative or out of currency provided: a) Procedures do not require its use, and b) They are not used to define the route of flight. NOTE: Any current and operative functions may continue to be used.	
20-01	XM Satellite System	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
		D	1	0	May be inoperative provided routine procedures do not require its use.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 49-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

49. Airborne Auxiliary Power

Sequence No.	Item	1	2	3	4	Change Bar
11-01	Auxiliary Power Unit (APU)	B	1	0	(M) May be inoperative provided: a) Auxiliary Power Unit is deactivated, b) Engine Driven Generator Channels are operative, and c) Operations with steep approach are not conducted. NOTE: Appropriate bleed source performance data must be used.	
11-02	APU Hour Meter	C	1	0	(M) May be inoperative provided alternate method for checking APU hours is used.	
51-01	APU Load Control Valve	C	1	0	(M) May be inoperative provided it is deactivated CLOSED. NOTE 1: The APU is still available as source of electrical power, if required. NOTE 2: Appropriate bleed source performance data must be used.	
51-02	AIR COND/BLEED APU "ON" Switch Light (light function only)	C	1	0		

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 52-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

52. Doors

Sequence No.	Item	1	2	3	4	Change Bar
00-01 ***	Exterior Door Keyable Locks	D	-	0	May be inoperative provided affected lock does not affect associated door normal operation.	
10-01	Passenger Door Power Assist System	C	1	0	(M)(O) May be inoperative provided: a) Door is verified manually operative, and b) Opening damping feature is verified operative.	
30-02	Baggage Door Counterbalance Systems	C	2	0	(M) Any or all may be inoperative provided: a) Baggage door is verified closed, latched and not used, and b) Baggage door is placarded "BAGGAGE DOOR INOPERATIVE-DO NOT OPEN". NOTE: Baggage compartment is accessible through the door located in cabin.	
70-01	Door Indication Systems					
1)	Passenger Door Indication System	C	1	0	(M)(O) May be inoperative provided: a) Door is CLOSED and LATCHED before each departure, b) External handle is verified STOWED before each departure, c) External pressure vent flap is verified CLOSED before each departure, and d) Internal mechanism indicator flag is verified green before each departure.	
(Continued)						

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 52-2

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

52. Doors

Sequence No.	Item	1	2	3	4	Change Bar
70-01	Door Indication Systems (Cont'd)					
2)	Emergency Exit Indication System	C	1	0	(O) May be inoperative provided: a) Door is CLOSED and LATCHED before each departure, and b) External pressure vent flap is verified CLOSED before each departure.	
3)	Cargo Door Indication System	C	1	0	(O) May be inoperative provided: a) Door is CLOSED and LATCHED before each departure, b) External handle is verified STOWED before each departure, and c) External pressure vent flap is verified CLOSED before each departure.	
4)	Aft Equipment Bay Door Indication System	C	1	0	(O) May be inoperative provided door is CLOSED and LATCHED before each departure.	
5)	Battery Bay Door Indication System	C	1	0	(O) May be inoperative provided door is CLOSED and LATCHED before each departure.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 73-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

73. Engine Fuel and Control

Sequence No.	Item	1	2	3	4	Change Bar
00-01	Engine Control Systems	A	2	2	May be dispatched as indicated by "L or R ENGINE MINOR FAULT" advisory message provided repairs are made in accordance with times established by engine manufacturer. No repair interval extensions are permitted.	
30-01	Fuel Flow Readouts	B	2	1	(O) May be inoperative provided Fuel Used Readout is considered inoperative (73-30-02).	
30-02	Fuel Used Readout	C	1	0	May be inoperative provided Fuel Quantity Gaging Computer Channels are operative.	
40-01	Fuel Filter Impending Bypass Indication Systems	C	2	1	(M) May be inoperative provided fuel filter element on affected engine is replaced before the first flight after failure occurred and every 20 flight-hours thereafter.	
40-03	Fuel Low Temperature Indication Systems	C	2	1	May be inoperative provided icing inhibitor is added to the fuel.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 74-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

74. Ignition

Sequence No.	Item	1	2	3	4	Change Bar
21-01	Engine Ignition Systems	B	2	2	System(s) redundancy may be degraded as indicated by "L/R ENG IGN FAULT" advisory message. NOTE: At time of repair, any engine ignition system failure causing L/R ENG IGN FAULT advisory message to display must be corrected.	
31-01	ENGINE IGNITION "ON" Switch Light (light function only)	C	1	0		

REVISION NO. Original
 DATE: 11/18/2003

PAGE NO. 76-1

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

76. Engine Control

Sequence No.	Item	1	2	3	4	Change Bar
11-02	FADECs Automatic Engine Control Functions					
1)	SYNC Function	C	1	0		
2)	MACH HOLD Function	C	1	0		
20-01	ENGINE AUTO APR "OFF" Switch Light (light function only)	C	1	0		
20-02	ENGINE MACH HOLD "ON" Switch Light (light function only)	C	1	0		

REVISION NO. 1
 DATE: 11/26/2004

PAGE NO. 77-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

77. Engine Indicating

Sequence No.	Item	1	2	3	4	Change Bar
31-01	Engine Vibration Indications	B	2	1	May be inoperative provided: a) Operations are not conducted in known or forecast icing conditions, and b) One Ice Detection System is operative.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 78-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

78. Engine Exhaust

Sequence No.	Item	1	2	3	4	Change Bar
30-01	Thrust Reverser Systems	C	2	1	(M) May be inoperative provided: a) Affected Thrust Reverser is stowed and locked, b) Operations are conducted in accordance with AFM performance data, and c) Operations with steep approach are not conducted.	
		C	2	0	(M) Any or all may be inoperative provided: a) Affected Thrust Reverser is stowed and locked, b) Operations are not conducted on wet or contaminated runways, and c) Operations with steep approach are not conducted.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 79-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

79. Engine Oil

Sequence No.	Item	1	2	3	4	Change Bar
30-01	Remote Oil Level Indications (Refuel/Defuel panel)	C	2	0	Any or all may be inoperative provided associated oil tank sight gauge is used to determine oil level.	
30-02	Oil Filter Impending Bypass Indication Systems	A	2	1	(M) May be inoperative provided: a) Affected oil filter element is replaced, and b) Repairs are made within 3 flight-days.	

REVISION NO. Original
 DATE: 11/18/2003

PAGE NO. 80-1

AIRCRAFT: BD-100-1A10	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
--------------------------	--

80. Starting

Sequence No.	Item	1	2	3	4	Change Bar
11-01	Air Turbine Starter Valves	C	2	1	(M)(O) May be inoperative provided: a) Valve is deactivated, and b) Alternate starting procedures are established and used to start the affected engine.	

SECTION TWO

CREW ALERTING SYSTEM (CAS) MESSAGE RELIEF

REVISION NO. 6
DATE: 07/30/2018

PAGE NO. 2-2

AIRCRAFT:
BD-100-1A10

STATEMENT PAGE

1. Section Two of the MMEL will list only Crew Alerting system (CAS) Messages meeting the following requirements:
 - a) Equipment failure indications(s) that can be used to determine the airworthiness status of the airplane.
 - b) Messages that the crew can act upon from the cockpit with simple troubleshooting procedures without the assistance of a mechanic, and for which the crew has been trained.
 - c) Messages using the new self-diagnostic technology (virtual) actions for which the crew has been trained.
2. CAS message relief items not meeting these requirements will be listed in Section One of the MMEL.

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 2-3

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. DISPATCH CONSIDERATION

CAS Messages

Item	1	2	Change Bar
AIR COND FAULT (Advisory)	B	(O) May be inoperative provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	
AUTO PRESS FAIL (Caution)	B	(O) Aircraft may be dispatched provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	
AUX HYD PUMP FAIL ON (Advisory)	B	(O) Aircraft may be dispatched provided: a) The AUX pump is verified to stop when selected to OFF, and b) The AUX pump is selected OFF after takeoff, selected to AUTO before approach and OFF after landing.	
CABIN PRESS FAULT (Caution)	B	(O) Aircraft may be dispatched provided: a) Manual pressurization is verified operative before flight, b) No other CAS messages related to air conditioning or pressurization are posted, c) Ram Air Valve is verified operative, and d) Operations are conducted at or below FL 250.	
	B	(O) Aircraft may be dispatched provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 2-4

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. DISPATCH CONSIDERATION

CAS Messages

Item	1	2	Change Bar
ELECTRICAL FAULT (Advisory)	B	(O) Aircraft may be dispatched provided Battery temperature indications are verified operative before each flight.	
ICE DETECTOR FAIL (Caution)	C	(O) Aircraft may be dispatched for other than night operations provided: <ol style="list-style-type: none"> a) Affected detector is deactivated, and b) Anti-ice systems are turned ON when icing conditions exist as defined in AFM. 	
	C	(O) Aircraft may be dispatched for night operations provided: <ol style="list-style-type: none"> a) Affected detector is deactivated, and b) Anti-ice systems are turned ON when SAT is between +10 °C and -40 °C. 	
ICE DETECTOR FAULT (Advisory)	C	(O) Aircraft may be dispatched provided: <ol style="list-style-type: none"> a) Affected detector is deactivated, and b) Anti-ice systems are turned ON when icing conditions exist as defined in AFM. 	
L AUX BUS FAIL (Advisory)	C	(O) Aircraft may be dispatched provided procedures are in place to accommodate loss of cabin inverter.	
L WSHLD HEAT FAIL (Caution)	C	(O) Aircraft may be dispatched provided: <ol style="list-style-type: none"> a) None of following messages are displayed: <ul style="list-style-type: none"> • L or R WINDOW HEAT FAIL, • R WSHLD HEAT FAIL, or • ICE DETECTOR FAIL, b) Left windshield channel is deactivated, and c) Operations are not conducted in known or forecast icing conditions. 	

REVISION NO. 7
 DATE: 03/12/2021

PAGE NO. 2-5

AIRCRAFT:
 BD-100-1A10

TABLE KEY

1. REPAIR CATEGORY
2. DISPATCH CONSIDERATION

CAS Messages

Item	1	2	Change Bar
MANUAL PRESS FAIL (Advisory)	B	(O) Aircraft may be dispatched provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Manual Pressurization switch is selected OFF, c) Ram Air Valve is selected OPEN, d) Pressurization EMER DEPRESS switch is selected ON, and e) Operations are conducted unpressurized at or below 9000 ft. MSL.	
R WINDOW HEAT FAIL (Caution)	C	(O) Aircraft may be dispatched provided: a) Right Side Window Heating Channel is deactivated, b) No more than one of the following messages is displayed: • L WSHLD HEAT FAIL, • R WSHLD HEAT FAIL, and c) Operations are not conducted in known or forecast icing conditions.	
R WSHLD HEAT FAIL (Caution)	C	(O) Aircraft may be dispatched provided: a) None of following messages are displayed: • L or R WINDOW HEAT FAIL, • L WSHLD HEAT FAIL, and • ICE DETECTOR FAIL, b) Right windshield channel is deactivated, and c) Operations are not conducted in known or forecast icing conditions.	
STBY INST BATT FAULT (Advisory)	B	Aircraft may be dispatched provided operations are not conducted more than one hour from a suitable airport.	
TRIM AIR FAIL (Caution)	B	(O) Aircraft may be dispatched provided: a) AIR COND/BLEED AIR SOURCE rotary selector switch is selected to OFF, b) Ram Air Valve is selected OPEN, c) PRESSURIZATION EMER DEPRESS switch is selected ON, and d) Operations are conducted unpressurized at or below 9000 ft. MSL.	